



Java™ Servlet Specification

Version 3.1

Rajiv Mordani
Shing Wai Chan
June 2012

EARLY DRAFT
REVIEW

Oracle Corporation
www.oracle.com

Submit comments about this document to: users@servlet-spec.java.net

Specification: JSR-340 Java Servlet 3.1 Specification ("Specification")

Version: 3.1

Status: Early Draft Review

Release: 26 June 2012

Copyright 2012 Oracle America, Inc.
500 Oracle Parkway, Redwood City, California 94065, U.S.A

All rights reserved.

LIMITED LICENSE GRANTS

NOTICE

The Specification is protected by copyright and the information described therein may be protected by one or more U.S. patents, foreign patents, or pending applications. Except as provided under the following license, no part of the Specification may be reproduced in any form by any means without the prior written authorization of Oracle America, Inc. ("Oracle") and its licensors, if any. Any use of the Specification and the information described therein will be governed by the terms and conditions of this Agreement.

Subject to the terms and conditions of this license, including your compliance with Paragraphs 1 and 2 below, Oracle hereby grants you a fully-paid, non-exclusive, non-transferable, limited license (without the right to sublicense) under Oracle's intellectual property rights to:

1. Review the Specification for the purposes of evaluation. This includes: (i) developing implementations of the Specification for your internal, non-commercial use; (ii) discussing the Specification with any third party; and (iii) excerpting brief portions of the Specification in oral or written communications which discuss the Specification provided that such excerpts do not in the aggregate constitute a significant portion of the Technology.

2. Distribute implementations of the Specification to third parties for their testing and evaluation use, provided that any such implementation: (i) does not modify, subset, superset or otherwise extend the Licensor Name Space, or include any public or protected packages, classes, Java interfaces, fields or methods within the Licensor Name Space other than those required/authorized by the Specification or Specifications being implemented;

(ii) is clearly and prominently marked with the word "UNTESTED" or "EARLY ACCESS" or "INCOMPATIBLE" or "UNSTABLE" or "BETA" in any list of available builds and in proximity to every link initiating its download, where the list or link is under Licensee's control; and

(iii) includes the following notice:

"This is an implementation of an early-draft specification developed under the Java Community Process (JCP) and is made available for testing and evaluation purposes only. The code is not compatible with any specification of the JCP."

The grant set forth above concerning your distribution of implementations of the specification is contingent upon your agreement to terminate development and distribution of your "early draft" implementation as soon as feasible following final completion of the specification. If you fail to do so, the foregoing grant shall be considered null and void.

No provision of this Agreement shall be understood to restrict your ability to make and distribute to third parties applications written to the Specification.

Other than this limited license, you acquire no right, title or interest in or to the Specification or any other Oracle intellectual property, and the Specification may only be used in accordance with the license terms set forth herein. This license will expire on the earlier of: (a) two (2) years from the date of Release listed above; (b) the date on which the final version of the Specification is publicly released; or (c) the date on which the Java Specification Request (JSR) to which the Specification corresponds is withdrawn. In addition, this license will terminate immediately without notice from Oracle if you fail to comply with any provision of this license. Upon termination, you must cease use of or



Please
Recycle



Adobe PostScript

destroy the Specification.

"Licensor Name Space" means the public class or interface declarations whose names begin with "java", "javax", "com.oracle" or their equivalents in any subsequent naming convention adopted by Oracle through the Java Community Process, or any recognized successors or replacements thereof

TRADEMARKS

No right, title, or interest in or to any trademarks, service marks, or trade names of Oracle or Oracle's licensors is granted hereunder. Oracle, the Oracle logo, Java are trademarks or registered trademarks of Oracle USA, Inc. in the U.S. and other countries.

DISCLAIMER OF WARRANTIES

THE SPECIFICATION IS PROVIDED "AS IS" AND IS EXPERIMENTAL AND MAY CONTAIN DEFECTS OR DEFICIENCIES WHICH CANNOT OR WILL NOT BE CORRECTED BY ORACLE. ORACLE MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT THAT THE CONTENTS OF THE SPECIFICATION ARE SUITABLE FOR ANY PURPOSE OR THAT ANY PRACTICE OR IMPLEMENTATION OF SUCH CONTENTS WILL NOT INFRINGE ANY THIRD PARTY PATENTS, COPYRIGHTS, TRADE SECRETS OR OTHER RIGHTS. This document does not represent any commitment to release or implement any portion of the Specification in any product.

THE SPECIFICATION COULD INCLUDE TECHNICAL INACCURACIES OR TYPOGRAPHICAL ERRORS. CHANGES ARE PERIODICALLY ADDED TO THE INFORMATION THEREIN; THESE CHANGES WILL BE INCORPORATED INTO NEW VERSIONS OF THE SPECIFICATION, IF ANY. ORACLE MAY MAKE IMPROVEMENTS AND/OR CHANGES TO THE PRODUCT(S) AND/OR THE PROGRAM(S) DESCRIBED IN THE SPECIFICATION AT ANY TIME. Any use of such changes in the Specification will be governed by the then-current license for the applicable version of the Specification.

LIMITATION OF LIABILITY

TO THE EXTENT NOT PROHIBITED BY LAW, IN NO EVENT WILL ORACLE OR ITS LICENSORS BE LIABLE FOR ANY DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUE, PROFITS OR DATA, OR FOR SPECIAL, INDIRECT, CONSEQUENTIAL, INCIDENTAL OR PUNITIVE DAMAGES, HOWEVER CAUSED AND REGARDLESS OF THE THEORY OF LIABILITY, ARISING OUT OF OR RELATED TO ANY FURNISHING, PRACTICING, MODIFYING OR ANY USE OF THE SPECIFICATION, EVEN IF ORACLE AND/OR ITS LICENSORS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

You will hold Oracle (and its licensors) harmless from any claims based on your use of the Specification for any purposes other than the limited right of evaluation as described above, and from any claims that later versions or releases of any Specification furnished to you are incompatible with the Specification provided to you under this license.

RESTRICTED RIGHTS LEGEND

If this Software is being acquired by or on behalf of the U.S. Government or by a U.S. Government prime contractor or subcontractor (at any tier), then the Government's rights in the Software and accompanying documentation shall be only as set forth in this license; this is in accordance with 48 C.F.R. 227.7201 through 227.7202-4 (for Department of Defense (DoD) acquisitions) and with 48 C.F.R. 2.101 and 12.212 (for non-DoD acquisitions).

REPORT

You may wish to report any ambiguities, inconsistencies or inaccuracies you may find in connection with your evaluation of the Specification ("Feedback"). To the extent that you provide Oracle with any Feedback, you hereby: (i) agree that such Feedback is provided on a non-proprietary and non-confidential basis, and (ii) grant Oracle a perpetual, non-exclusive, worldwide, fully paid-up, irrevocable license, with the right to sublicense through multiple levels of sublicensees, to incorporate, disclose, and use without limitation the Feedback for any purpose related to the Specification and future versions, implementations, and test suites thereof.

GENERAL TERMS

Any action related to this Agreement will be governed by California law and controlling U.S. federal law. The U.N. Convention for the Inter-

national Sale of Goods and the choice of law rules of any jurisdiction will not apply.

The Specification is subject to U.S. export control laws and may be subject to export or import regulations in other countries. Licensee agrees to comply strictly with all such laws and regulations and acknowledges that it has the responsibility to obtain such licenses to export, re-export or import as may be required after delivery to Licensee.

This Agreement is the parties' entire agreement relating to its subject matter. It supersedes all prior or contemporaneous oral or written communications, proposals, conditions, representations and warranties and prevails over any conflicting or additional terms of any quote, order, acknowledgment, or other communication between the parties relating to its subject matter during the term of this Agreement. No modification to this Agreement will be binding, unless in writing and signed by an authorized representative of each party.

Preface

This document is the Java™ Servlet Specification, version 3.1. The standard for the Java Servlet API is described herein.

Additional Sources

The specification is intended to be a complete and clear explanation of Java Servlets, but if questions remain, the following sources may be consulted:

- A reference implementation (RI) has been made available which provides a behavioral benchmark for this specification. Where the specification leaves implementation of a particular feature open to interpretation, implementors may use the reference implementation as a model of how to carry out the intention of the specification.
- A compatibility test suite (CTS) has been provided for assessing whether implementations meet the compatibility requirements of the Java Servlet API standard. The test results have normative value for resolving questions about whether an implementation is standard.
- If further clarification is required, the working group for the Java Servlet API under the Java Community Process should be consulted, and is the final arbiter of such issues.

Comments and feedback are welcome, and will be used to improve future versions.

Who Should Read This Specification

The intended audience for this specification includes the following groups:

- Web server and application server vendors that want to provide servlet engines that conform to this standard.
- Authoring tool developers that want to support Web applications that conform to this specification
- Experienced servlet authors who want to understand the underlying mechanisms of servlet technology.

We emphasize that this specification is not a user's guide for servlet developers and is not intended to be used as such. References useful for this purpose are available from <http://java.sun.com/products/servlet>.

API Reference

The full specifications of classes, interfaces, and method signatures that define the Java Servlet API, as well as their accompanying Javadoc™ documentation, is available online.

Other Java Platform Specifications

The following Java API specifications are referenced throughout this specification:

- Java Platform, Enterprise Edition ("Java EE"), version 6
- JavaServer Pages™ ("JSP™"), version 2.2
- Java Naming and Directory Interface™ ("J.N.D.I.™").
- Context and Dependency Injection for the Java EE Platform
- Managed Beans specification

These specifications may be found at the Java Platform, Enterprise Edition Web site: <http://java.sun.com/javaee/>.

Other Important References

The following Internet specifications provide information relevant to the development and implementation of the Java Servlet API and standard servlet engines:

- RFC 1630 Uniform Resource Identifiers (URI)
- RFC 1738 Uniform Resource Locators (URL)
- RFC 2396 Uniform Resource Identifiers (URI): Generic Syntax
- RFC 1808 Relative Uniform Resource Locators
- RFC 1945 Hypertext Transfer Protocol (HTTP/1.0)
- RFC 2045 MIME Part One: Format of Internet Message Bodies
- RFC 2046 MIME Part Two: Media Types
- RFC 2047 MIME Part Three: Message Header Extensions for non-ASCII text
- RFC 2048 MIME Part Four: Registration Procedures
- RFC 2049 MIME Part Five: Conformance Criteria and Examples
- RFC 2109 HTTP State Management Mechanism
- RFC 2145 Use and Interpretation of HTTP Version Numbers
- RFC 2324 Hypertext Coffee Pot Control Protocol (HTCPCP/1.0)¹
- RFC 2616 Hypertext Transfer Protocol (HTTP/1.1)
- RFC 2617 HTTP Authentication: Basic and Digest Authentication
- RFC 3986 Uniform Resource Identifier (URI): Generic Syntax

Online versions of these RFCs are at <http://www.ietf.org/rfc/>.

The World Wide Web Consortium (<http://www.w3.org/>) is a definitive source of HTTP related information affecting this specification and its implementations.

The eXtensible Markup Language (XML) is used for the specification of the Deployment Descriptors described in Chapter 13 of this specification. More information about XML can be found at the following Web sites:

<http://java.sun.com/xml>

<http://www.xml.org/>

Providing Feedback

We welcome any and all feedback about this specification. Please e-mail your comments to jsr-315-comments@jcp.org.

Please note that due to the volume of feedback that we receive, you will not normally receive a reply from an engineer. However, each and every comment is read, evaluated, and archived by the specification team.

1. This reference is mostly tongue-in-cheek although most of the concepts described in the HTCPCP RFC are relevant to all well-designed Web servers.

Expert Group members

- Deepak Anupalli (Pramati Technologies)
- Ted Goddard (Icesoft Technologies Inc)
- Robert Goff (IBM)
- Richard Hightower
- Seth Hodgson (Adobe Systems Inc.)
- Remy Maucherat (RedHat)
- Minoru Nitta (Fujitsu Limited)
- Chang Paek (TmaxSoft, Inc)
- Ramesh PVK (Pramati Technnologies)
- Alex Rojkov (Caucho Technologies)
- Mark Thomas (VMware)
- Gregory John Wilkins
- Wenbo Zhu (Google Inc.)

Acknowledgements

Bill Shannon from Oracle has provided invaluable technical input to the specification. Ron Monzillo from Oracle has helped drive some of the proposals and technical discussions around security aspects.

Contents

Preface v

Additional Sources v

Who Should Read This Specification v

API Reference vi

Other Java Platform Specifications vi

Other Important References vi

Providing Feedback vii

Expert Group members viii

Acknowledgements viii

Contents ix

1. Overview 1

1.1 What is a Servlet? 1

1.2 What is a Servlet Container? 1

1.3 An Example 2

1.4 Comparing Servlets with Other Technologies 3

1.5 Relationship to Java Platform, Enterprise Edition 3

1.6 Compatibility with Java Servlet Specification Version 2.5 4

1.6.1 Listener ordering 4

1.6.2	Processing annotations	4
2.	The Servlet Interface	5
2.1	Request Handling Methods	5
2.1.1	HTTP Specific Request Handling Methods	5
2.1.2	Additional Methods	6
2.1.3	Conditional GET Support	6
2.2	Number of Instances	6
2.2.1	Note About The Single Thread Model	7
2.3	Servlet Life Cycle	7
2.3.1	Loading and Instantiation	7
2.3.2	Initialization	8
2.3.2.1	Error Conditions on Initialization	8
2.3.2.2	Tool Considerations	8
2.3.3	Request Handling	9
2.3.3.1	Multithreading Issues	9
2.3.3.2	Exceptions During Request Handling	9
2.3.3.3	Asynchronous processing	10
2.3.3.4	Thread Safety	20
2.3.3.5	Upgrade Processing	20
2.3.4	End of Service	21
3.	The Request	23
3.1	HTTP Protocol Parameters	23
3.1.1	When Parameters Are Available	24
3.2	File upload	24
3.3	Attributes	25
3.4	Headers	25
3.5	Request Path Elements	26

3.6	Path Translation Methods	27
3.7	Non Blocking IO	28
3.8	Cookies	29
3.9	SSL Attributes	29
3.10	Internationalization	30
3.11	Request data encoding	30
3.12	Lifetime of the Request Object	31
4.	Servlet Context	33
4.1	Introduction to the ServletContext Interface	33
4.2	Scope of a ServletContext Interface	33
4.3	Initialization Parameters	34
4.4	Configuration methods	34
4.4.1	Programmatically adding and configuring Servlets	35
4.4.1.1	addServlet(String servletName, String className)	35
4.4.1.2	addServlet(String servletName, Servlet servlet)	35
4.4.1.3	addServlet(String servletName, Class <? extends Servlet> servletClass)	35
4.4.1.4	<T extends Servlet> T createServlet(Class<T> clazz)	35
4.4.1.5	ServletRegistration getServletRegistration(String servletName)	36
4.4.1.6	Map<String, ? extends ServletRegistration> getServletRegistrations()	36
4.4.2	Programmatically adding and configuring Filters	36
4.4.2.1	addFilter(String filterName, String className)	36
4.4.2.2	addFilter(String filterName, Filter filter)	36
4.4.2.3	addFilter(String filterName, Class <? extends Filter> filterClass)	37
4.4.2.4	<T extends Filter> T createFilter(Class<T> clazz)	37
4.4.2.5	FilterRegistration getFilterRegistration(String filterName)	37

4.4.2.6	Map<String, ? extends FilterRegistration> getServletRegistrations()	37
4.4.3	Programmatically adding and configuring Listeners	38
4.4.3.1	void addListener(String className)	38
4.4.3.2	<T extends EventListener> void addListener(T t)	38
4.4.3.3	void addListener(Class <? extends EventListener> listenerClass)	39
4.4.3.4	<T extends EventListener> void createListener(Class<T> clazz)	39
4.4.3.5	Annotation processing requirements for programmatically added Servlets, Filters and Listeners	40
4.5	Context Attributes	40
4.5.1	Context Attributes in a Distributed Container	40
4.6	Resources	41
4.7	Multiple Hosts and Servlet Contexts	41
4.8	Reloading Considerations	42
4.8.1	Temporary Working Directories	42
5.	The Response	43
5.1	Buffering	43
5.2	Headers	44
5.3	Non Blocking IO	45
5.4	Convenience Methods	46
5.5	Internationalization	47
5.6	Closure of Response Object	48
5.7	Lifetime of the Response Object	48
6.	Filtering	49
6.1	What is a filter?	49
6.1.1	Examples of Filtering Components	50

6.2	Main Concepts	50
6.2.1	Filter Lifecycle	50
6.2.2	Wrapping Requests and Responses	52
6.2.3	Filter Environment	52
6.2.4	Configuration of Filters in a Web Application	53
6.2.5	Filters and the RequestDispatcher	56
7.	Sessions	59
7.1	Session Tracking Mechanisms	59
7.1.1	Cookies	59
7.1.2	SSL Sessions	60
7.1.3	URL Rewriting	60
7.1.4	Session Integrity	60
7.2	Creating a Session	60
7.3	Session Scope	61
7.4	Binding Attributes into a Session	61
7.5	Session Timeouts	62
7.6	Last Accessed Times	62
7.7	Important Session Semantics	63
7.7.1	Threading Issues	63
7.7.2	Distributed Environments	63
7.7.3	Client Semantics	64
8.	Annotations and pluggability	65
8.1	Annotations and pluggability	65
8.1.1	@WebServlet	65
8.1.2	@WebFilter	67
8.1.3	@WebInitParam	67
8.1.4	@WebListener	67

8.1.5	@MultipartConfig	68
8.1.6	Other annotations / conventions	68
8.2	Pluggability	69
8.2.1	Modularity of web.xml	69
8.2.2	Ordering of web.xml and web-fragment.xml	70
8.2.3	Assembling the descriptor from web.xml, web-fragment.xml and annotations	76
8.2.4	Shared libraries / runtimes pluggability	89
8.3	JSP container pluggability	91
8.4	Processing annotations and fragments	91
9.	Dispatching Requests	93
9.1	Obtaining a RequestDispatcher	93
9.1.1	Query Strings in Request Dispatcher Paths	94
9.2	Using a Request Dispatcher	94
9.3	The Include Method	95
9.3.1	Included Request Parameters	95
9.4	The Forward Method	96
9.4.1	Query String	96
9.4.2	Forwarded Request Parameters	96
9.5	Error Handling	97
9.6	Obtaining an AsyncContext	97
9.7	The Dispatch Method	98
9.7.1	Query String	98
9.7.2	Dispatched Request Parameters	98
10.	Web Applications	101
10.1	Web Applications Within Web Servers	101
10.2	Relationship to ServletContext	101
10.3	Elements of a Web Application	102

10.4	Deployment Hierarchies	102
10.5	Directory Structure	102
10.5.1	Example of Application Directory Structure	104
10.6	Web Application Archive File	104
10.7	Web Application Deployment Descriptor	104
10.7.1	Dependencies On Extensions	105
10.7.2	Web Application Class Loader	105
10.8	Replacing a Web Application	106
10.9	Error Handling	106
10.9.1	Request Attributes	106
10.9.2	Error Pages	107
10.9.3	Error Filters	108
10.10	Welcome Files	109
10.11	Web Application Environment	110
10.12	Web Application Deployment	111
10.13	Inclusion of a web.xml Deployment Descriptor	111
11.	Application Lifecycle Events	113
11.1	Introduction	113
11.2	Event Listeners	113
11.2.1	Event Types and Listener Interfaces	114
11.2.2	An Example of Listener Use	115
11.3	Listener Class Configuration	115
11.3.1	Provision of Listener Classes	115
11.3.2	Deployment Declarations	115
11.3.3	Listener Registration	116
11.3.4	Notifications At Shutdown	116
11.4	Deployment Descriptor Example	116
11.5	Listener Instances and Threading	117

11.6	Listener Exceptions	117
11.7	Distributed Containers	118
11.8	Session Events	118
12.	Mapping Requests to Servlets	119
12.1	Use of URL Paths	119
12.2	Specification of Mappings	120
12.2.1	Implicit Mappings	120
12.2.2	Example Mapping Set	121
13.	Security	123
13.1	Introduction	123
13.2	Declarative Security	124
13.3	Programmatic Security	124
13.4	Programmatic Access Control Annotations	126
13.4.1	@ServletSecurity Annotation	126
13.4.1.1	Examples	129
13.4.1.2	Mapping @ServletSecurity to security-constraint	130
13.4.1.3	Mapping @HttpConstraint and @HttpMethodConstraint to XML.	132
13.4.2	setServletSecurity of ServletRegistration.Dynamic	134
13.5	Roles	134
13.6	Authentication	135
13.6.1	HTTP Basic Authentication	135
13.6.2	HTTP Digest Authentication	136
13.6.3	Form Based Authentication	136
13.6.3.1	Login Form Notes	137
13.6.4	HTTPS Client Authentication	138
13.6.5	Additional Container Authentication Mechanisms	138
13.7	Server Tracking of Authentication Information	138

13.8	Specifying Security Constraints	139
13.8.1	Combining Constraints	140
13.8.2	Example	141
13.8.3	Processing Requests	143
13.9	Default Policies	144
13.10	Login and Logout	144
14.	Deployment Descriptor	147
14.1	Deployment Descriptor Elements	147
14.2	Rules for Processing the Deployment Descriptor	148
14.3	Deployment Descriptor	149
14.4	Deployment Descriptor Diagram	149
14.5	Examples	172
14.5.1	A Basic Example	173
14.5.2	An Example of Security	174
15.	Requirements related to other Specifications	177
15.1	Sessions	177
15.2	Web Applications	177
15.2.1	Web Application Class Loader	177
15.2.2	Web Application Environment	178
15.2.3	JNDI Name for Web Module Context Root URL	178
15.3	Security	179
15.3.1	Propagation of Security Identity in EJB™ Calls	180
15.3.2	Container Authorization Requirements	180
15.3.3	Container Authentication Requirements	180
15.4	Deployment	181
15.4.1	Deployment Descriptor Elements	181
15.4.2	Packaging and Deployment of JAX-WS Components	181

15.4.3	Rules for Processing the Deployment Descriptor	183
15.5	Annotations and Resource Injection	183
15.5.1	@DeclareRoles	184
15.5.2	@EJB Annotation	185
15.5.3	@EJBs Annotation	186
15.5.4	@Resource Annotation	186
15.5.5	@PersistenceContext Annotation	187
15.5.6	@PersistenceContexts Annotation	187
15.5.7	@PersistenceUnit Annotation	188
15.5.8	@PersistenceUnits Annotation	188
15.5.9	@PostConstruct Annotation	188
15.5.10	@PreDestroy Annotation	189
15.5.11	@Resources Annotation	189
15.5.12	@RunAs Annotation	190
15.5.13	@WebServiceRef Annotation	191
15.5.14	@WebServiceRefs Annotation	191
15.5.15	Managed Beans and JSR 299 requirements	191
A.	Change Log	193
A.1	Changes since Servlet 3.0	193
A.2	Changes since Servlet 3.0 Proposed Final Draft	194
A.3	Changes since Servlet 3.0 Public Review	194
A.4	Changes since Servlet 3.0 EDR	195
A.5	Changes since Servlet 2.5 MR6	195
A.6	Changes since Servlet 2.5 MR 5	196
A.6.1	Clarify SRV 8.4 "The Forward Method"	196
A.6.2	Update Deployment descriptor "http-method values allowed"	196
A.6.3	Clarify SRV 7.7.1 "Threading Issues"	196

A.7	Changes Since Servlet 2.5 MR 2	197
A.7.1	Updated Annotation Requirements for Java EE containers	197
A.7.2	Updated Java Enterprise Edition Requirements	197
A.7.3	Clarified <code>HttpServletRequest.getRequestURL()</code>	197
A.7.4	Removal of <code>IllegalStateException</code> from <code>HttpSession.getId()</code>	198
A.7.5	<code>ServletContext.getContextPath()</code>	198
A.7.6	Requirement for <code>web.xml</code> in web applications	198
A.8	Changes Since Servlet 2.4	199
A.8.1	Session Clarification	199
A.8.2	Filter All Dispatches	199
A.8.3	Multiple Occurrences of Servlet Mappings	200
A.8.4	Multiple Occurrences Filter Mappings	200
A.8.5	Support Alternative HTTP Methods with Authorization Constraints	202
A.8.6	Minimum J2SE Requirement	203
A.8.7	Annotations and Resource Injection	203
A.8.8	SRV.9.9 ("Error Handling") Requirement Removed	203
A.8.9	<code>HttpServletRequest.isRequestedSessionIdValid()</code> Clarification	203
A.8.10	SRV.5.5 ("Closure of Response Object") Clarification	203
A.8.11	<code>ServletRequest.setCharacterEncoding()</code> Clarified	204
A.8.12	Java Enterprise Edition Requirements	204
A.8.13	Servlet 2.4 MR Change Log Updates Added	204
A.8.14	Synchronized Access Session Object Clarified	204
A.9	Changes Since Servlet 2.3	204

Overview

1.1 What is a Servlet?

A servlet is a Java™ technology-based Web component, managed by a container, that generates dynamic content. Like other Java technology-based components, servlets are platform-independent Java classes that are compiled to platform-neutral byte code that can be loaded dynamically into and run by a Java technology-enabled Web server. Containers, sometimes called servlet engines, are Web server extensions that provide servlet functionality. Servlets interact with Web clients via a request/response paradigm implemented by the servlet container.

1.2 What is a Servlet Container?

The servlet container is a part of a Web server or application server that provides the network services over which requests and responses are sent, decodes MIME-based requests, and formats MIME-based responses. A servlet container also contains and manages servlets through their lifecycle.

A servlet container can be built into a host Web server, or installed as an add-on component to a Web Server via that server's native extension API. Servlet containers can also be built into or possibly installed into Web-enabled application servers.

All servlet containers must support HTTP as a protocol for requests and responses, but additional request/response-based protocols such as HTTPS (HTTP over SSL) may be supported. The required versions of the HTTP specification that a container must implement are HTTP/1.0 and HTTP/1.1. Because the container may have a caching mechanism described in RFC2616 (HTTP/1.1), it may modify requests from

the clients before delivering them to the servlet, may modify responses produced by servlets before sending them to the clients, or may respond to requests without delivering them to the servlet under the compliance with RFC2616.

A servlet container may place security restrictions on the environment in which a servlet executes. In a Java Platform, Standard Edition (J2SE, v.1.3 or above) or Java Platform, Enterprise Edition (Java EE, v.1.3 or above) environment, these restrictions should be placed using the permission architecture defined by the Java platform. For example, high-end application servers may limit the creation of a `Thread` object to insure that other components of the container are not negatively impacted.

Java SE 6 is the minimum version of the underlying Java platform with which servlet containers must be built.

1.3 An Example

The following is a typical sequence of events:

1. A client (e.g., a Web browser) accesses a Web server and makes an HTTP request.
2. The request is received by the Web server and handed off to the servlet container. The servlet container can be running in the same process as the host Web server, in a different process on the same host, or on a different host from the Web server for which it processes requests.
3. The servlet container determines which servlet to invoke based on the configuration of its servlets, and calls it with objects representing the request and response.
4. The servlet uses the request object to find out who the remote user is, what HTTP `POST` parameters may have been sent as part of this request, and other relevant data. The servlet performs whatever logic it was programmed with, and generates data to send back to the client. It sends this data back to the client via the response object.
5. Once the servlet has finished processing the request, the servlet container ensures that the response is properly flushed, and returns control back to the host Web server.

1.4 Comparing Servlets with Other Technologies

In functionality, servlets lie somewhere between Common Gateway Interface (CGI) programs and proprietary server extensions such as the Netscape Server API (NSAPI) or Apache Modules.

Servlets have the following advantages over other server extension mechanisms:

- They are generally much faster than CGI scripts because a different process model is used.
- They use a standard API that is supported by many Web servers.
- They have all the advantages of the Java programming language, including ease of development and platform independence.
- They can access the large set of APIs available for the Java platform.

1.5 Relationship to Java Platform, Enterprise Edition

The Java Servlet API v.3.0 is a required API of the Java Platform, Enterprise Edition, v.6¹. Servlet containers and servlets deployed into them must meet additional requirements, described in the Java EE specification, for executing in a Java EE environment.

1. Please see the Java™ Platform, Enterprise Edition specification available at <http://java.sun.com/javaee/>

1.6 Compatibility with Java Servlet Specification Version 2.5

1.6.1 Listener ordering

Prior to this release of the specification, listeners were invoked in a random order. As of servlet 3.0, the order in which listeners are invoked is defined in “Assembling the descriptor from web.xml, web-fragment.xml and annotations” on page 8 76

1.6.2 Processing annotations

In Servlet 2.5, `metadata-complete` only affected the scanning of annotations at deployment time. The notion of web-fragments did not exist in servlet 2.5. However in servlet 3.0 `metadata-complete` affects scanning of all annotations and web-fragments at deployment time. The version of the descriptor **MUST** not affect which annotations you scan for in a web application. An implementation of a particular version of the specification **MUST** scan for all annotations supported in that configuration, unless `metadata-complete` is specified.

The Servlet Interface

The `Servlet` interface is the central abstraction of the Java Servlet API. All servlets implement this interface either directly, or more commonly, by extending a class that implements the interface. The two classes in the Java Servlet API that implement the `Servlet` interface are `GenericServlet` and `HttpServlet`. For most purposes, Developers will extend `HttpServlet` to implement their servlets.

2.1 Request Handling Methods

The basic `Servlet` interface defines a `service` method for handling client requests. This method is called for each request that the servlet container routes to an instance of a servlet.

The handling of concurrent requests to a Web application generally requires that the Web Developer design servlets that can deal with multiple threads executing within the `service` method at a particular time.

Generally the Web container handles concurrent requests to the same servlet by concurrent execution of the `service` method on different threads.

2.1.1 HTTP Specific Request Handling Methods

The `HttpServlet` abstract subclass adds additional methods beyond the basic `Servlet` interface that are automatically called by the `service` method in the `HttpServlet` class to aid in processing HTTP-based requests. These methods are:

- `doGet` for handling HTTP `GET` requests
- `doPost` for handling HTTP `POST` requests
- `doPut` for handling HTTP `PUT` requests
- `doDelete` for handling HTTP `DELETE` requests

- `doHead` for handling HTTP HEAD requests
- `doOptions` for handling HTTP OPTIONS requests
- `doTrace` for handling HTTP TRACE requests

Typically when developing HTTP-based servlets, a Servlet Developer will only concern himself with the `doGet` and `doPost` methods. The other methods are considered to be methods for use by programmers very familiar with HTTP programming.

2.1.2 Additional Methods

The `doPut` and `doDelete` methods allow Servlet Developers to support HTTP/1.1 clients that employ these features. The `doHead` method in `HttpServlet` is a specialized form of the `doGet` method that returns only the headers produced by the `doGet` method. The `doOptions` method responds with which HTTP methods are supported by the servlet. The `doTrace` method generates a response containing all instances of the headers sent in the TRACE request.

2.1.3 Conditional GET Support

The `HttpServlet` interface defines the `getLastModified` method to support conditional GET operations. A conditional GET operation requests a resource be sent only if it has been modified since a specified time. In appropriate situations, implementation of this method may aid efficient utilization of network resources.

2.2 Number of Instances

The servlet declaration which is either via the annotation as described in Chapter 8, “Annotations and pluggability” or part of the deployment descriptor of the Web application containing the servlet, as described in Chapter 14, “Deployment Descriptor”, controls how the servlet container provides instances of the servlet.

For a servlet not hosted in a distributed environment (the default), the servlet container must use only one instance per servlet declaration. However, for a servlet implementing the `SingleThreadModel` interface, the servlet container may instantiate multiple instances to handle a heavy request load and serialize requests to a particular instance.

In the case where a servlet was deployed as part of an application marked in the deployment descriptor as distributable, a container may have only one instance per servlet declaration per Java Virtual Machine (JVM™)¹. However, if the servlet in a distributable application implements the `SingleThreadModel` interface, the container may instantiate multiple instances of that servlet in each JVM of the container.

2.2.1 Note About The Single Thread Model

The use of the `SingleThreadModel` interface guarantees that only one thread at a time will execute in a given servlet instance's `service` method. It is important to note that this guarantee only applies to each servlet instance, since the container may choose to pool such objects. Objects that are accessible to more than one servlet instance at a time, such as instances of `HttpSession`, may be available at any particular time to multiple servlets, including those that implement `SingleThreadModel`.

It is recommended that a developer take other means to resolve those issues instead of implementing this interface, such as avoiding the usage of an instance variable or synchronizing the block of the code accessing those resources. The `SingleThreadModel` interface is deprecated in this version of the specification.

2.3 Servlet Life Cycle

A servlet is managed through a well defined life cycle that defines how it is loaded and instantiated, is initialized, handles requests from clients, and is taken out of service. This life cycle is expressed in the API by the `init`, `service`, and `destroy` methods of the `javax.servlet.Servlet` interface that all servlets must implement directly or indirectly through the `GenericServlet` or `HttpServlet` abstract classes.

2.3.1 Loading and Instantiation

The servlet container is responsible for loading and instantiating servlets. The loading and instantiation can occur when the container is started, or delayed until the container determines the servlet is needed to service a request.

1. The terms "Java virtual machine" and "JVM" mean a virtual machine for the Java(™) platform.

When the servlet engine is started, needed servlet classes must be located by the servlet container. The servlet container loads the servlet class using normal Java class loading facilities. The loading may be from a local file system, a remote file system, or other network services.

After loading the `Servlet` class, the container instantiates it for use.

2.3.2 Initialization

After the servlet object is instantiated, the container must initialize the servlet before it can handle requests from clients. Initialization is provided so that a servlet can read persistent configuration data, initialize costly resources (such as JDBC™ API-based connections), and perform other one-time activities. The container initializes the servlet instance by calling the `init` method of the `Servlet` interface with a unique (per servlet declaration) object implementing the `ServletConfig` interface. This configuration object allows the servlet to access name-value initialization parameters from the Web application's configuration information. The configuration object also gives the servlet access to an object (implementing the `ServletContext` interface) that describes the servlet's runtime environment. See Chapter 4, "Servlet Context" for more information about the `ServletContext` interface.

2.3.2.1 Error Conditions on Initialization

During initialization, the servlet instance can throw an `UnavailableException` or a `ServletException`. In this case, the servlet must not be placed into active service and must be released by the servlet container. The `destroy` method is not called as it is considered unsuccessful initialization.

A new instance may be instantiated and initialized by the container after a failed initialization. The exception to this rule is when an `UnavailableException` indicates a minimum time of unavailability, and the container must wait for the period to pass before creating and initializing a new servlet instance.

2.3.2.2 Tool Considerations

The triggering of static initialization methods when a tool loads and introspects a Web application is to be distinguished from the calling of the `init` method. Developers should not assume a servlet is in an active container runtime until the `init` method of the `Servlet` interface is called. For example, a servlet should not try to establish connections to databases or Enterprise JavaBeans™ containers when only static (class) initialization methods have been invoked.

2.3.3 Request Handling

After a servlet is properly initialized, the servlet container may use it to handle client requests. Requests are represented by request objects of type `ServletRequest`. The servlet fills out response to requests by calling methods of a provided object of type `ServletResponse`. These objects are passed as parameters to the `service` method of the `Servlet` interface.

In the case of an HTTP request, the objects provided by the container are of types `HttpServletRequest` and `HttpServletResponse`.

Note that a servlet instance placed into service by a servlet container may handle no requests during its lifetime.

2.3.3.1 Multithreading Issues

A servlet container may send concurrent requests through the `service` method of the servlet. To handle the requests, the Servlet Developer must make adequate provisions for concurrent processing with multiple threads in the `service` method.

Although it is not recommended, an alternative for the Developer is to implement the `SingleThreadModel` interface which requires the container to guarantee that there is only one request thread at a time in the `service` method. A servlet container may satisfy this requirement by serializing requests on a servlet, or by maintaining a pool of servlet instances. If the servlet is part of a Web application that has been marked as distributable, the container may maintain a pool of servlet instances in each JVM that the application is distributed across.

For servlets not implementing the `SingleThreadModel` interface, if the `service` method (or methods such as `doGet` or `doPost` which are dispatched to the `service` method of the `HttpServletRequest` abstract class) has been defined with the `synchronized` keyword, the servlet container cannot use the instance pool approach, but must serialize requests through it. It is strongly recommended that Developers not synchronize the `service` method (or methods dispatched to it) in these circumstances because of detrimental effects on performance.

2.3.3.2 Exceptions During Request Handling

A servlet may throw either a `ServletException` or an `UnavailableException` during the service of a request. A `ServletException` signals that some error occurred during the processing of the request and that the container should take appropriate measures to clean up the request.

An `UnavailableException` signals that the servlet is unable to handle requests either temporarily or permanently.

If a permanent unavailability is indicated by the `UnavailableException`, the servlet container must remove the servlet from service, call its `destroy` method, and release the servlet instance. Any requests refused by the container by that cause must be returned with a `SC_NOT_FOUND` (404) response.

If temporary unavailability is indicated by the `UnavailableException`, the container may choose to not route any requests through the servlet during the time period of the temporary unavailability. Any requests refused by the container during this period must be returned with a `SC_SERVICE_UNAVAILABLE` (503) response status along with a `Retry-After` header indicating when the unavailability will terminate.

The container may choose to ignore the distinction between a permanent and temporary unavailability and treat all `UnavailableExceptions` as permanent, thereby removing a servlet that throws any `UnavailableException` from service.

2.3.3.3 Asynchronous processing

Some times a filter and/or servlet is unable to complete the processing of a request without waiting for a resource or event before generating a response. For example, a servlet may need to wait for an available JDBC connection, for a response from a remote web service, for a JMS message, or for an application event, before proceeding to generate a response. Waiting within the servlet is an inefficient operation as it is a blocking operation that consumes a thread and other limited resources. Frequently a slow resource such as a database may have many threads blocked waiting for access and can cause thread starvation and poor quality of service for an entire web container.

Servlet 3.0 introduces the ability for asynchronous processing of requests so that the thread may return to the container and perform other tasks. When asynchronous processing begins on the request, another thread or callback may either generate the response and call `complete` or `dispatch` the request so that it may run in the context of the container using the `AsyncContext.dispatch` method. A typical sequence of events for asynchronous processing is:

1. The request is received and passed via normal filters for authentication etc. to the servlet.
2. The servlet processes the request parameters and/or content to determine the nature of the request.
3. The servlet issues requests for resources or data, for example, sends a remote web service request or joins a queue waiting for a JDBC connection.
4. The servlet returns without generating a response.
5. After some time, the requested resource becomes available, the thread handling that event continues processing either in the same thread or by dispatching to a resource in the container using the `AsyncContext`.

Java Enterprise Edition features such as Section 15.2.2, “Web Application Environment” on page 15-178 and Section 15.3.1, “Propagation of Security Identity in EJB™ Calls” on page 15-180 are available only to threads executing the initial request or when the request is dispatched to the container via the `AsyncContext.dispatch` method. Java Enterprise Edition features may be available to other threads operating directly on the response object via the `AsyncContext.start(Runnable)` method.

The `@WebServlet` and `@WebFilter` annotations described in Chapter 8 have an attribute - `asyncSupported` that is a boolean with a default value of `false`. When `asyncSupported` is set to `true` the application can start asynchronous processing in a separate thread by calling `startAsync` (see below), passing it a reference to the request and response objects, and then exit from the container on the original thread. This means that the response will traverse (in reverse order) the same filters (or filter chain) that were traversed on the way in. The response isn't committed till `complete` (see below) is called on the `AsyncContext`. The application is responsible to handle concurrent access to the request and response objects if the `async` task is executing before the container-initiated dispatch that called `startAsync` has returned to the container.

Dispatching from a servlet that has `asyncSupported=true` to one where `asyncSupported` is set to `false` is allowed. In this case, the response will be committed when the service method of the servlet that does not support `async` is exited, and it is the container's responsibility to call `complete` on the `AsyncContext` so that any interested `AsyncListener` instances will be notified. The `AsyncListener.onComplete` notification should also be used by filters as a mechanism to clear up resources that it has been holding on to for the `async` task to complete.

Dispatching from a synchronous servlet to an asynchronous servlet would be illegal. However the decision of throwing an `IllegalStateException` is deferred to the point when the application calls `startAsync`. This would allow a servlet to either function as a synchronous or an asynchronous servlet.

The `async` task that the application is waiting for could write directly to the response, on a different thread than the one that was used for the initial request. This thread knows nothing about any filters. If a filter wanted to manipulate the response in the new thread, it would have to wrap the response when it was processing the initial request "on the way in", and passed the wrapped response to the next filter in the chain, and eventually to the servlet. So if the response was wrapped (possibly multiple times, once per filter), and the application processes the request and writes directly to the response, it is really writing to the response wrapper(s), i.e., any output added to the response will still be processed by the response wrapper(s). When an application reads from a request in a separate thread, and adds output to the response, it really reads from the request wrapper(s), and writes to the response wrapper(s), so any input and/or output manipulation intended by the wrapper(s) will continue to occur.

Alternately if the application chooses to do so it can use the `AsyncContext` to `dispatch` the request from the new thread to a resource in the container. This would enable using content generation technologies like JSP within the scope of the container.

In addition to the annotation attributes we have the following methods / classes added:

- `ServletRequest`

- `public AsyncContext startAsync(ServletRequest req, ServletResponse res)`. This method puts the request into asynchronous mode and initializes it's `AsyncContext` with the given request and response objects and the time out returned by `getAsyncTimeout`. The `ServletRequest` and `ServletResponse` parameters **MUST** be either the same objects as were passed to the calling servlet's `service`, or the filter's `doFilter` method, or be subclasses of `ServletRequestWrapper` or `ServletResponseWrapper` classes that wrap them. A call to this method ensures that the response isn't committed when the application exits out of the `service` method. It is committed when `AsyncContext.complete` is called on the returned `AsyncContext` or the `AsyncContext` times out and there are no listeners associated to handle the time out. The timer for async time outs will not start until the request and it's associated response have returned from the container. The `AsyncContext` could be used to write to the response from the async thread. It can also be used to just notify that the response is not closed and committed.

It is illegal to call `startAsync` if the request is within the scope of a servlet or filter that does not support asynchronous operations, or if the response has been committed and closed, or is called again during the same `dispatch`. The `AsyncContext` returned from a call to `startAsync` can then be used for further asynchronous processing. Calling the `AsyncContext.hasOriginalRequestResponse()` on the returned `AsyncContext` will return `false`, unless the passed `ServletRequest` and `ServletResponse` arguments are the original ones or do not carry application provided wrappers. Any filters invoked in the *outbound* direction after this request was put into asynchronous mode **MAY** use this as an indication that some of the request and / or response wrappers that they added during their *inbound* invocation **MAY** need to stay in place for the duration of the asynchronous operation, and their associated resources **MAY** not be released. A `ServletRequestWrapper` applied during the *inbound* invocation of a filter **MAY** be released by the *outbound* invocation of the filter only if the given `ServletRequest` which is used to initialize the `AsyncContext` and will be returned by a call to `AsyncContext.getRequest()`, does not contain the said `ServletRequestWrapper`. The same holds true for `ServletResponseWrapper` instances.

- `public AsyncContext startAsync()` is provided as a convenience that uses the original request and response objects for the async processing. Please note users of this method SHOULD flush the response if they are wrapped before calling this method if you wish, to ensure that any data written to the wrapped response isn't lost.
- `public AsyncContext getAsyncContext()` - returns the `AsyncContext` that was created or re initialized by the invocation of `startAsync`. It is illegal to call `getAsyncContext` if the request has not been put in asynchronous mode.
- `public boolean isAsyncSupported()` - Returns `true` if the request supports async processing, and `false` otherwise. Async support will be disabled as soon as the request has passed a filter or servlet that does not support async processing (either via the designated annotation or declaratively).
- `public boolean isAsyncStarted()` - Returns `true` if async processing has started on this request, and `false` otherwise. If this request has been dispatched using one of the `AsyncContext.dispatch` methods since it was put in asynchronous mode, or a call to `AsyncContext.complete` is made, this method returns `false`.
- `public DispatcherType getDispatcherType()` - Returns the dispatcher type of a request. The dispatcher type of a request is used by the container to select the filters that need to be applied to the request. Only filters with the matching dispatcher type and url patterns will be applied. Allowing a filter that has been configured for multiple dispatcher types to query a request for it's dispatcher type allows the filter to process the request differently depending on it's dispatcher type. The initial dispatcher type of a request is defined as `DispatcherType.REQUEST`. The dispatcher type of a request dispatched via `RequestDispatcher.forward(ServletRequest, ServletResponse)` OR `RequestDispatcher.include(ServletRequest, ServletResponse)` is given as `DispatcherType.FORWARD` OR `DispatcherType.INCLUDE` respectively, while a dispatcher type of an asynchronous request dispatched via one of the `AsyncContext.dispatch` methods is given as `DispatcherType.ASYNC`. Finally the dispatcher type of a request dispatched to an error page by the container's error handling mechanism is given as `DispatcherType.ERROR`.
- `AsyncContext` - This class represents the execution context for the asynchronous operation that was started on the `ServletRequest`. An `AsyncContext` is created and initialized by a call to `ServletRequest.startAsync` as described above. The following methods are in the `AsyncContext`:
 - `public ServletRequest getRequest()` - returns the request that was used to initialize the `AsyncContext` by calling one of the `startAsync` methods. Calling `getRequest` when `complete` or any of the `dispatch` methods has been previously called in the asynchronous cycle will result in an `IllegalStateException`.
 - `public ServletResponse getResponse()` - returns the response that was used to initialize the `AsyncContext` by calling one of the `startAsync` methods. Calling `getResponse` when `complete` or any of the `dispatch` methods has been previously called in the asynchronous cycle will result in an `IllegalStateException`.

- `public void setTimeout(long timeoutMilliseconds)` - Sets the time out for the asynchronous processing to occur in milliseconds. A call to this method overrides the time out set by the container. If the time out is not specified via the call to the `setTimeout`, then a container default will be used. A value of 0 or less indicates that the asynchronous operation will never time out. The time out applies to the `AsyncContext` once the container-initiated dispatch during which one of the `ServletRequest.startAsync` methods was called has returned to the container. It is illegal to set the time out if this method is called after the container-initiated dispatch on which the asynchronous cycle was started has returned to the container and will result in an `IllegalStateException`.
- `public long getTimeout()` - Gets the time out, in milliseconds, associated with the `AsyncContext`. This method returns the container's default time out, or the time out value set via the most recent invocation of `setTimeout` method.
- `public void addListener(AsyncListener listener, ServletRequest req, ServletResponse res)` - Registers the given listener for notifications of `onTimeout`, `onError`, `onComplete` or `onStartAsync`. The first three are associated with the most recent asynchronous cycle started by calling one of the `ServletRequest.startAsync` methods. The `onStartAsync` is associated to a new asynchronous cycle via one of the `ServletRequest.startAsync` methods. Async listeners will be notified in the order in which they were added to the request. The request and response objects passed in to the method are the exact same ones that are available from the `AsyncEvent.getSuppliedRequest()` and `AsyncEvent.getSuppliedResponse()` when the `AsyncListener` is notified. These objects should not be read from or written to, because additional wrapping may have occurred since the given `AsyncListener` was registered, but may be used in order to release any resources associated with them. It is illegal to call this method after the container-initiated dispatch on which the asynchronous cycle was started has returned to the container and before a new asynchronous cycle was started and will result in an `IllegalStateException`.
- `public <T extends AsyncListener> createListener(Class<T> clazz)` - Instantiates the given `AsyncListener` class. The returned `AsyncListener` instance may be further customized before it is registered with the `AsyncContext` via a call to one of the `addListener` methods specified below. The given `AsyncListener` class MUST define a zero argument constructor, which is used to instantiate it. This method supports any annotations applicable to the `AsyncListener`.
- `public void addListener(AsyncListener)` - Registers the given listener for notifications of `onTimeout`, `onError`, `onComplete` or `onStartAsync`. The first three are associated with the most recent asynchronous cycle started by calling one of the `ServletRequest.startAsync` methods. The `onStartAsync` is associated to a new asynchronous cycle via one of the `ServletRequest.startAsync` methods. If `startAsync(req, res)` or `startAsync()` is called on the request, the exact same request and response objects are available from the `AsyncEvent` when the `AsyncListener` is notified. The request and response may or may not be wrapped. Async listeners will be notified in the order in which they were added to the request. It is illegal to call this method after the container-initiated

dispatch on which the asynchronous cycle was started has returned to the container and before a new asynchronous cycle was started and will result in an `IllegalStateException`.

- `public void dispatch(String path)` - Dispatches the request and response that were used to initialize the `AsyncContext` to the resource with the given path. The given path is interpreted as relative to the `ServletContext` that initialized the `AsyncContext`. All path related query methods of the request MUST reflect the dispatch target, while the original request URI, context path, path info and query string may be obtained from the request attributes as defined in Section 9.7.2, “Dispatched Request Parameters” on page 9-98. These attributes MUST always reflect the original path elements, even after multiple dispatches.
- `public void dispatch()` - Provided as a convenience to dispatch the request and response used to initialize the `AsyncContext` as follows. If the `AsyncContext` was initialized via the `startAsync(ServletRequest, ServletResponse)` and the request passed is an instance of `HttpServletRequest`, then the dispatch is to the URI returned by `HttpServletRequest.getRequestURI()`. Otherwise the dispatch is to the URI of the request when it was last dispatched by the container. The examples CODE EXAMPLE 2-1, CODE EXAMPLE 2-2 and CODE EXAMPLE 2-3 shown below demonstrate what the target URI of dispatch would be in the different cases.

CODE EXAMPLE 2-1

```
// REQUEST to /url/A
AsyncContext ac = request.startAsync();
...
ac.dispatch(); // ASYNC dispatch to /url/A
```

CODE EXAMPLE 2-2

```
// REQUEST to /url/A
// FORWARD to /url/B
request.getRequestDispatcher("/url/B").forward(request,
response);
// Start async operation from within the target of the FORWARD
AsyncContext ac = request.startAsync();
ac.dispatch(); // ASYNC dispatch to /url/A
```

CODE EXAMPLE 2-3

```
// REQUEST to /url/A
// FORWARD to /url/B
request.getRequestDispatcher("/url/B").forward(request,
response);
```


```
// Start async operation from within the target of the FORWARD
AsyncContext ac = request.startAsync(request, response);
ac.dispatch(); // ASYNC dispatch to /url/B
```

- `public void dispatch(ServletContext context, String path)` - dispatches the request and response used to initialize the `AsyncContext` to the resource with the given path in the given `ServletContext`.
- For all the 3 variations of the `dispatch` methods defined above, calls to the methods returns immediately after passing the request and response objects to a container managed thread, on which the dispatch operation will be performed. The dispatcher type of the request is set to `ASYNC`. Unlike `RequestDispatcher.forward(ServletRequest, ServletResponse)` dispatches, the response buffer and headers will not be reset, and it is legal to dispatch even if the response has already been committed. Control over the request and response is delegated to the dispatch target, and the response will be closed when the dispatch target has completed execution, unless `ServletRequest.startAsync()` or `ServletRequest.startAsync(ServletRequest, ServletResponse)` is called. If any of the dispatch methods are called before the container-initiated dispatch that called `startAsync` has returned to the container, then the call will not take effect until after the container-initiated dispatch has returned to the container. Invocation of the `AsyncListener.onComplete(AsyncEvent)`, `AsyncListener.onTimeout(AsyncEvent)` and `AsyncListener.onError(AsyncEvent)` will also be delayed till after the container-initiated dispatch has returned to the container. There can be at most one asynchronous dispatch operation per asynchronous cycle, which is started by a call to one of the `ServletRequest.startAsync` methods. There can be at most one asynchronous dispatch per asynchronous cycle, which is started by a call to `ServletRequest.startAsync`. Any attempt to perform additional asynchronous dispatch operation within the same asynchronous cycle is illegal and will result in an `IllegalStateException`. If `startAsync` is subsequently called on the dispatched request, then any of the `dispatch` methods may be called with the same restriction as above.
- Any errors or exceptions that may occur during the execution of the `dispatch` methods MUST be caught and handled by the container as follows:
 - i. invoke the `AsyncListener.onError(AsyncEvent)` method for all instances of the `AsyncListener` registered with the `ServletRequest` for which the `AsyncContext` was created and make the caught `Throwable` available via the `AsyncEvent.getThrowable()`.
 - ii. If none of the listeners called `AsyncContext.complete` or any of the `AsyncContext.dispatch` methods, then perform an error dispatch with a status code equal to `HttpServletResponse.SC_INTERNAL_SERVER_ERROR` and make the `Throwable` available as the value of the `RequestDispatcher.ERROR_EXCEPTION` request attribute.

- iii. If no matching error page is found, or the error page does not call `AsyncContext.complete()` or any of the `AsyncContext.dispatch` methods, then the container **MUST** call `AsyncContext.complete`.
- `public boolean hasOriginalRequestAndResponse()` - This method checks if the `AsyncContext` was initialized with the original request and response objects by calling `ServletRequest.startAsync()` or if it was initialized by calling `ServletRequest.startAsync(ServletRequest, ServletResponse)` and neither the `ServletRequest` nor the `ServletResponse` argument carried any application provided wrappers, in which case it returns `true`. If the `AsyncContext` was initialized with wrapped request and/or response objects using `ServletRequest.startAsync(ServletRequest, ServletResponse)`, it returns `false`. This information may be used by filters invoked in the *outbound* direction, after a request was put into asynchronous mode, to determine whether any request and/or response wrappers that they added during their *inbound* invocation need to be preserved for the duration of the asynchronous operation or may be released.
 - `public void start(Runnable r)` - This method causes the container to dispatch a thread, possibly from a managed thread pool, to run the specified `Runnable`. The container may propagate appropriate contextual information to the `Runnable`.
 - `public void complete()` - If `request.startAsync` is called then this method **MUST** be called to complete the async processing and commit and close the response. The `complete` method can be invoked by the container if the request is dispatched to a servlet that does not support async processing, or the target servlet called by `AsyncContext.dispatch` does not do a subsequent call to `startAsync`. In this case, it is the container's responsibility to call `complete()` as soon as that servlet's service method is exited. An `IllegalStateException` **MUST** be thrown if `startAsync` was not called. It is legal to call this method anytime after a call to `ServletRequest.startAsync()` or `ServletRequest.startAsync(ServletRequest, ServletResponse)` and before a call to one of the dispatch methods. If this method is called before the container-initiated dispatch that called `startAsync` has returned to the container, then the call will not take effect until after the container-initiated dispatch has returned to the container. Invocation of the `AsyncListener.onComplete(AsyncEvent)` will also be delayed till after the container-initiated dispatch has returned to the container.
 - `ServletRequestWrapper`
 - `public boolean isWrapperFor(ServletRequest req)`- Checks recursively if this wrapper wraps the given `ServletRequest` and returns `true` if it does, else it returns `false`
 - `ServletResponseWrapper`
 - `public boolean isWrapperFor(ServletResponse res)`- Checks recursively if this wrapper wraps the given `ServletResponse` and returns `true` if it does, else it returns `false`.
 - `AsyncListener`

- `public void onComplete(AsyncEvent event)` - Is used to notify the listener of completion of the asynchronous operation started on the `ServletRequest`.
- `public void onTimeout(AsyncEvent event)` - Is used to notify the listener of a time out of the asynchronous operation started on the `ServletRequest`.
- `public void onError(AsyncEvent event)` - Is used to notify the listener that the asynchronous operation has failed to complete.
- `public void onStartAsync(AsyncEvent event)` - Is used to notify the listener that a new asynchronous cycle is being initiated via a call to one of the `ServletRequest.startAsync` methods. The `AsyncContext` corresponding to the asynchronous operation that is being reinitialized may be obtained by calling `AsyncEvent.getAsyncContext` on the given event.
- In the event that an asynchronous operation times out, the container must run through the following steps:
 - Invoke the `AsyncListener.onTimeout` method on all the `AsyncListener` instances registered with the `ServletRequest` on which the asynchronous operation was initiated.
 - If none of the listeners called `AsyncContext.complete()` or any of the `AsyncContext.dispatch` methods, perform an error dispatch with a status code equal to `HttpServletResponse.SC_INTERNAL_SERVER_ERROR`.
 - If no matching error page was found, or the error page did not call `AsyncContext.complete()` or any of the `AsyncContext.dispatch` methods, the container **MUST** call `AsyncContext.complete()`.
- Async processing in JSP would not be supported by default as it is used for content generation and async processing would have to be done before the content generation. It is up to the container how to handle this case. Once all the async activities are done, a dispatch to the JSP page using the `AsyncContext.dispatch` can be used for generating content.
- Figure 2-1 shown below is a diagram depicting the state transitions for various asynchronous operations.

FIGURE 2-1 State transition diagram for asynchronous operations



2.3.3.4 Thread Safety

Other than the `startAsync` and `complete` methods, implementations of the request and response objects are not guaranteed to be thread safe. This means that they should either only be used within the scope of the request handling thread or the application must ensure that access to the request and response objects are thread safe.

If a thread created by the application uses the container-managed objects, such as the request or response object, those objects must be accessed only within the object's life cycle as defined in sections 3.10 and 5.6. Be aware that other than the `startAsync`, and `complete` methods, the request and response objects are not thread safe. If those objects were accessed in the multiple threads, the access should be synchronized or be done through a wrapper to add the thread safety, for instance, synchronizing the call of the methods to access the request attribute, or using a local output stream for the response object within a thread.

2.3.3.5 Upgrade Processing

In HTTP/1.1, the Upgrade general-header allows the client to specify the additional communication protocols that it supports and would like to use. If the server finds it appropriate to switch protocols, then new protocols will be used in subsequent communication.

The servlet container provides an HTTP upgrade mechanism. However the servlet container itself does not have knowledge about the upgraded protocol. The protocol processing is encapsulated in the protocol handler. Data reading or writing between the servlet container and the protocol handler is in byte streams.

When an upgrade request is received, the servlet can invoke the `HttpServletRequest.upgrade` method to start the upgrade process. The application prepares and sends an appropriate response to the client. After exiting the `service` method of the servlet, the servlet container completes the processing of all filters and marks the connection to be handled by the protocol handler. It then calls the protocol handler's `init` method, passing a `WebConnection` to allow the protocol handler access to the data streams.

The servlet filters only process the initial HTTP request and response. They are not involved in subsequent communications. In other words, they are not invoked once the request has been upgraded.

The `ProtocolHandler` may use non blocking IO to consume and produce messages.

2.3.4 End of Service

The servlet container is not required to keep a servlet loaded for any particular period of time. A servlet instance may be kept active in a servlet container for a period of milliseconds, for the lifetime of the servlet container (which could be a number of days, months, or years), or any amount of time in between.

When the servlet container determines that a servlet should be removed from service, it calls the `destroy` method of the `Servlet` interface to allow the servlet to release any resources it is using and save any persistent state. For example, the container may do this when it wants to conserve memory resources, or when it is being shut down.

Before the servlet container calls the `destroy` method, it must allow any threads that are currently running in the `service` method of the servlet to complete execution, or exceed a server-defined time limit.

Once the `destroy` method is called on a servlet instance, the container may not route other requests to that instance of the servlet. If the container needs to enable the servlet again, it must do so with a new instance of the servlet's class.

After the `destroy` method completes, the servlet container must release the servlet instance so that it is eligible for garbage collection.

The Request

The request object encapsulates all information from the client request. In the HTTP protocol, this information is transmitted from the client to the server in the HTTP headers and the message body of the request.

3.1 HTTP Protocol Parameters

Request parameters for the servlet are the strings sent by the client to a servlet container as part of its request. When the request is an `HttpServletRequest` object, and conditions set out in “When Parameters Are Available” on page 24 are met, the container populates the parameters from the URI query string and POST-ed data.

The parameters are stored as a set of name-value pairs. Multiple parameter values can exist for any given parameter name. The following methods of the `ServletRequest` interface are available to access parameters:

- `getParameter`
- `getParameterNames`
- `getParameterValues`
- `getParameterMap`

The `getParameterValues` method returns an array of `String` objects containing all the parameter values associated with a parameter name. The value returned from the `getParameter` method must be the first value in the array of `String` objects returned by `getParameterValues`. The `getParameterMap` method returns a `java.util.Map` of the parameter of the request, which contains names as keys and parameter values as map values.

Data from the query string and the post body are aggregated into the request parameter set. Query string data is presented before post body data. For example, if a request is made with a query string of `a=hello` and a post body of `a=goodbye&a=world`, the resulting parameter set would be ordered `a=(hello, goodbye, world)`.

Path parameters that are part of a GET request (as defined by HTTP 1.1) are not exposed by these APIs. They must be parsed from the `String` values returned by the `getRequestURI` method or the `getPathInfo` method.

3.1.1 When Parameters Are Available

The following are the conditions that must be met before post form data will be populated to the parameter set:

1. The request is an HTTP or HTTPS request.
2. The HTTP method is POST.
3. The content type is `application/x-www-form-urlencoded`.
4. The servlet has made an initial call of any of the `getParameter` family of methods on the request object.

If the conditions are not met and the post form data is not included in the parameter set, the post data must still be available to the servlet via the request object's input stream. If the conditions are met, post form data will no longer be available for reading directly from the request object's input stream.

3.2 File upload

Servlet container allows files to be uploaded when data is sent as `multipart/form-data`.

The servlet container provides `multipart/form-data` processing if any one of the following conditions is met.

- The servlet handling the request is annotated with the `@MultipartConfig` as defined in Section 8.1.5, “`@MultipartConfig`” on page 8-68.
- Deployment descriptors contain a `multipart-config` element for the servlet handling the request.

How data in a request of type `multipart/form-data` is made available depends on whether the servlet container provides `multipart/form-data` processing:

- If the servlet container provides `multipart/form-data` processing, the data is made available through the following methods in `HttpServletRequest`:
 - `public Collection<Part> getParts()`
 - `public Part getPart(String name)`

Each part provides access to the headers, content type related with it and the content via the `Part.getInputStream` method.

For parts with `form-data` as the `Content-Disposition`, but without a filename, the string value of the part will also be available through the `getParameter` and `getParameterValues` methods on `HttpServletRequest`, using the name of the part.

- If the servlet container does not provide the `multi-part/form-data` processing, the data will be available through the `HttpServletRequest.getInputStream`.

3.3 Attributes

Attributes are objects associated with a request. Attributes may be set by the container to express information that otherwise could not be expressed via the API, or may be set by a servlet to communicate information to another servlet (via the `RequestDispatcher`). Attributes are accessed with the following methods of the `ServletRequest` interface:

- `getAttribute`
- `getAttributeNames`
- `setAttribute`

Only one attribute value may be associated with an attribute name.

Attribute names beginning with the prefixes of `java.` and `javax.` are reserved for definition by this specification. Similarly, attribute names beginning with the prefixes of `sun.`, and `com.sun.` are reserved for definition by Sun Microsystems. It is suggested that all attributes placed in the attribute set be named in accordance with the reverse domain name convention suggested by the Java Programming Language Specification¹ for package naming.

3.4 Headers

A servlet can access the headers of an HTTP request through the following methods of the `HttpServletRequest` interface:

- `getHeader`
- `getHeaders`
- `getHeaderNames`

1. The Java Programming Language Specification is available at <http://java.sun.com/docs/books/jls>

The `getHeader` method returns a header given the name of the header. There can be multiple headers with the same name, e.g. `Cache-Control` headers, in an HTTP request. If there are multiple headers with the same name, the `getHeader` method returns the first header in the request. The `getHeaders` method allows access to all the header values associated with a particular header name, returning an Enumeration of `String` objects.

Headers may contain `String` representations of `int` or `Date` data. The following convenience methods of the `HttpServletRequest` interface provide access to header data in a one of these formats:

- `getIntHeader`
- `getDateHeader`

If the `getIntHeader` method cannot translate the header value to an `int`, a `NumberFormatException` is thrown. If the `getDateHeader` method cannot translate the header to a `Date` object, an `IllegalArgumentException` is thrown.

3.5 Request Path Elements

The request path that leads to a servlet servicing a request is composed of many important sections. The following elements are obtained from the request URI path and exposed via the request object:

- **Context Path:** The path prefix associated with the `ServletContext` that this servlet is a part of. If this context is the “default” context rooted at the base of the Web server’s URL name space, this path will be an empty string. Otherwise, if the context is not rooted at the root of the server’s name space, the path starts with a `/` character but does not end with a `/` character.
- **Servlet Path:** The path section that directly corresponds to the mapping which activated this request. This path starts with a `'/'` character except in the case where the request is matched with the `'/*'` or `''` pattern, in which case it is an empty string.
- **PathInfo:** The part of the request path that is not part of the Context Path or the Servlet Path. It is either null if there is no extra path, or is a string with a leading `'/'`.

The following methods exist in the `HttpServletRequest` interface to access this information:

- `getContextPath`
- `getServletPath`
- `getPathInfo`

It is important to note that, except for URL encoding differences between the request URI and the path parts, the following equation is always true:

```
requestURI = contextPath + servletPath + pathInfo
```

To give a few examples to clarify the above points, consider the following:

TABLE 3-1 Example Context Set Up

Context Path	/catalog
Servlet Mapping	Pattern: /lawn/* Servlet: LawnServlet
Servlet Mapping	Pattern: /garden/* Servlet: GardenServlet
Servlet Mapping	Pattern: *.jsp Servlet: JSPServlet

The following behavior is observed:

TABLE 3-2 Observed Path Element Behavior

Request Path	Path Elements
/catalog/lawn/index.html	ContextPath: /catalog ServletPath: /lawn PathInfo: /index.html
/catalog/garden/implements/	ContextPath: /catalog ServletPath: /garden PathInfo: /implements/
/catalog/help/feedback.jsp	ContextPath: /catalog ServletPath: /help/feedback.jsp PathInfo: null

3.6 Path Translation Methods

There are two convenience methods in the API which allow the Developer to obtain the file system path equivalent to a particular path. These methods are:

- `ServletContext.getRealPath`
- `HttpServletRequest.getPathTranslated`

The `getRealPath` method takes a `String` argument and returns a `String` representation of a file on the local file system to which a path corresponds. The `getPathTranslated` method computes the real path of the `pathInfo` of the request.

In situations where the servlet container cannot determine a valid file path for these methods, such as when the Web application is executed from an archive, on a remote file system not accessible locally, or in a database, these methods must return null. Resources inside the `META-INF/resources` directory of JAR file must be considered only if the container has unpacked them from their containing JAR file when a call to `getRealPath()` is made, and in this case **MUST** return the unpacked location.

3.7 Non Blocking IO

Non-blocking request processing in the Web Container helps improve the ever increasing demand for improved Web Container scalability, increase the number of connections that can simultaneously be handled by the Web Container. Non-blocking IO in the Servlet container allows developers to read data as it becomes available or write data when possible to do so.

The `ReadListener` provides the following callback methods for non blocking IO -

- `ReadListener`
 - `onDataAvailable()`. The `onDataAvailable` method is invoked on the `ReadListener` when data is available to read from the incoming request stream. The container will invoke the method. This method will be invoked once for every set of data available.
 - `onAllDataRead()`. The `onAllDataRead` method is invoked when you have finished reading all the data for the `ServletRequest` for which the listener was registered.
 - `onError(Throwable t)`. The `onError` method is invoked if there is any error or exception that occurs while processing the request.

In addition to the `ReadListener` defined above, the following methods have been added to `ServletInputStream` class -

- `ServletInputStream`
 - `boolean isFinished()`. The `isFinished` method returns `true` when all the data for the request associated with the `ServletReader` / `ServletInputStream` has been read. Otherwise it returns `false`.
 - `boolean isReady()`. The `isReady` method returns `true` if data can be read without blocking. If no data can be read without blocking it returns `false`. If `isReady` returns `false` it is illegal to call the `read` method.
 - `void setReadListener(ReadListener listener)`. Sets the `ReadListener` defined above to get invoked to read data in a non-blocking fashion. Once the listener is associated for the given `ServletInputStream`, the container invokes the methods on the `ReadListener` when data is available to read, all the data

has been read or if there was an error processing the request. Registering a `ReadListener` will start non-blocking IO. It is illegal to switch to the traditional blocking IO at that point.

3.8 Cookies

The `HttpServletRequest` interface provides the `getCookies` method to obtain an array of cookies that are present in the request. These cookies are data sent from the client to the server on every request that the client makes. Typically, the only information that the client sends back as part of a cookie is the cookie name and the cookie value. Other cookie attributes that can be set when the cookie is sent to the browser, such as comments, are not typically returned. The specification also allows for the cookies to be `HttpOnly` cookies. `HttpOnly` cookies indicate to the client that they should not be exposed to client-side scripting code (It's not filtered out unless the client knows to look for this attribute). The use of `HttpOnly` cookies helps mitigate certain kinds of cross-site scripting attacks.

3.9 SSL Attributes

If a request has been transmitted over a secure protocol, such as HTTPS, this information must be exposed via the `isSecure` method of the `ServletRequest` interface. The Web container must expose the following attributes to the servlet programmer:

TABLE 3-3 Protocol Attributes

Attribute	Attribute Name	Java Type
cipher suite	<code>javax.servlet.request.cipher_suite</code>	String
bit size of the algorithm	<code>javax.servlet.request.key_size</code>	Integer
SSL session id	<code>javax.servlet.request.ssl_session_id</code>	String

If there is an SSL certificate associated with the request, it must be exposed by the servlet container to the servlet programmer as an array of objects of type `java.security.cert.X509Certificate` and accessible via a `ServletRequest` attribute of `javax.servlet.request.X509Certificate`.

The order of this array is defined as being in ascending order of trust. The first certificate in the chain is the one set by the client, the next is the one used to authenticate the first, and so on.

3.10 Internationalization

Clients may optionally indicate to a Web server what language they would prefer the response be given in. This information can be communicated from the client using the `Accept-Language` header along with other mechanisms described in the HTTP/1.1 specification. The following methods are provided in the `ServletRequest` interface to determine the preferred locale of the sender:

- `getLocale`
- `getLocales`

The `getLocale` method will return the preferred locale for which the client wants to accept content. See section 14.4 of RFC 2616 (HTTP/1.1) for more information about how the `Accept-Language` header must be interpreted to determine the preferred language of the client.

The `getLocales` method will return an Enumeration of `Locale` objects indicating, in decreasing order starting with the preferred locale, the locales that are acceptable to the client.

If no preferred locale is specified by the client, the locale returned by the `getLocale` method must be the default locale for the servlet container and the `getLocales` method must contain an enumeration of a single `Locale` element of the default locale.

3.11 Request data encoding

Currently, many browsers do not send a `char` encoding qualifier with the `Content-Type` header, leaving open the determination of the character encoding for reading HTTP requests. The default encoding of a request the container uses to create the request reader and parse POST data must be "ISO-8859-1" if none has been specified by the client request. However, in order to indicate to the developer, in this case, the failure of the client to send a character encoding, the container returns `null` from the `getCharacterEncoding` method.

If the client hasn't set character encoding and the request data is encoded with a different encoding than the default as described above, breakage can occur. To remedy this situation, a new method `setCharacterEncoding(String enc)` has been added to the `ServletRequest` interface. Developers can override the character encoding supplied by the container by calling this method. It must be called prior to parsing any post data or reading any input from the request. Calling this method once data has been read will not affect the encoding.

3.12 Lifetime of the Request Object

Each request object is valid only within the scope of a servlet's `service` method, or within the scope of a filter's `doFilter` method, unless the asynchronous processing is enabled for the component and the `startAsync` method is invoked on the request object. In the case where asynchronous processing occurs, the request object remains valid until `complete` is invoked on the `AsyncContext`. Containers commonly recycle request objects in order to avoid the performance overhead of request object creation. The developer must be aware that maintaining references to request objects for which `startAsync` has not been called outside the scope described above is not recommended as it may have indeterminate results.

Servlet Context

4.1 Introduction to the ServletContext Interface

The `ServletContext` interface defines a servlet's view of the Web application within which the servlet is running. The Container Provider is responsible for providing an implementation of the `ServletContext` interface in the servlet container. Using the `ServletContext` object, a servlet can log events, obtain URL references to resources, and set and store attributes that other servlets in the context can access.

A `ServletContext` is rooted at a known path within a Web server. For example, a servlet context could be located at `http://www.mycorp.com/catalog`. All requests that begin with the `/catalog` request path, known as the *context path*, are routed to the Web application associated with the `ServletContext`.

4.2 Scope of a ServletContext Interface

There is one instance object of the `ServletContext` interface associated with each Web application deployed into a container. In cases where the container is distributed over many virtual machines, a Web application will have an instance of the `ServletContext` for each JVM.

Servlets in a container that were not deployed as part of a Web application are implicitly part of a “default” Web application and have a default `ServletContext`. In a distributed container, the default `ServletContext` is non-distributable and must only exist in one JVM.

4.3 Initialization Parameters

The following methods of the `ServletContext` interface allow the servlet access to context initialization parameters associated with a Web application as specified by the Application Developer in the deployment descriptor:

- `getInitParameter`
- `getInitParameterNames`

Initialization parameters are used by an Application Developer to convey setup information. Typical examples are a Webmaster’s e-mail address, or the name of a system that holds critical data.

4.4 Configuration methods

The following methods are added to `ServletContext` since Servlet 3.0 to enable programmatic definition of servlets, filters and the url pattern that they map to. These methods can only be called during the initialization of the application either from the `contextInitialized` method of a `ServletContextListener` implementation or from the `onStartup` method of a `ServletContainerInitializer` implementation. In addition to adding Servlets and Filters, one can also look up an instance of a `Registration` object corresponding to a Servlet or Filter or a map of all the `Registration` objects for the Servlets or Filters. If the `ServletContext` passed to the `ServletContextListener`’s `contextInitialized` method was neither declared in `web.xml` or `web-fragment.xml` nor annotated with `@WebListener` then an `UnsupportedOperationException` MUST be thrown for all the methods defined for programmatic configuration of servlets, filters and listeners.

4.4.1 Programmatically adding and configuring Servlets

The ability to programmatically add a servlet to a context is useful for framework developers. For example a framework could declare a controller servlet using this method. The return value of this method is a `ServletRegistration` or a `ServletRegistration.Dynamic` object which further allows you to setup the other parameters of the servlet like `init-params`, `url-mappings` etc. There are three overloaded versions of the method as described below.

4.4.1.1 `addServlet(String servletName, String className)`

This method allows the application to declare a servlet programmatically. It adds the servlet with the given name, and class name to the servlet context.

4.4.1.2 `addServlet(String servletName, Servlet servlet)`

This method allows the application to declare a servlet programmatically. It adds the servlet with the given name, and servlet instance to the servlet context.

4.4.1.3 `addServlet(String servletName, Class <? extends Servlet> servletClass)`

This method allows the application to declare a servlet programmatically. It adds the servlet with the given name, and an instance of the servlet class to the servlet context.

4.4.1.4 `<T extends Servlet> T createServlet(Class<T> clazz)`

This method instantiates the given `Servlet` class. The method must support all the annotations applicable to Servlets except `@WebServlet`. The returned `Servlet` instance may be further customized before it is registered with the `ServletContext` via a call to `addServlet(String, Servlet)` as defined above.

4.4.1.5 ServletRegistration getServletRegistration(String servletName)

This method returns the `ServletRegistration` corresponding to the servlet with the given name, or null if no `ServletRegistration` exists under that name. An `UnsupportedOperationException` is thrown if the `ServletContext` was passed to the `contextInitialized` method of a `ServletContextListener` that was neither declared in the `web.xml` or `web-fragment.xml`, nor annotated with `javax.servlet.annotation.WebListener`.

4.4.1.6 Map<String, ? extends ServletRegistration> getServletRegistrations()

This method returns a map of `ServletRegistration` objects, keyed by name corresponding to all servlets registered with the `ServletContext`. If there are no servlets registered with the `ServletContext` an empty map is returned. The returned Map includes the `ServletRegistration` objects corresponding to all declared and annotated servlets, as well as the `ServletRegistration` objects corresponding to all servlets that have been added via one of the `addServlet` methods. Any changes to the returned Map MUST not affect the `ServletContext`. An `UnsupportedOperationException` is thrown if the `ServletContext` was passed to the `contextInitialized` method of a `ServletContextListener` that was neither declared in the `web.xml` or `web-fragment.xml`, nor annotated with `javax.servlet.annotation.WebListener`.

4.4.2 Programmatically adding and configuring Filters

4.4.2.1 addFilter(String filterName, String className)

This method allows the application to declare a filter programmatically. It adds the filter with the given name, and class name to the web application.

4.4.2.2 addFilter(String filterName, Filter filter)

This method allows the application to declare a filter programmatically. It adds the filter with the given name, and filter instance to the web application.

4.4.2.3 `addFilter(String filterName, Class <? extends Filter> filterClass)`

This method allows the application to declare a filter programmatically. It adds the filter with the given name, and an instance of the filter class to the web application.

4.4.2.4 `<T extends Filter> T createFilter(Class<T> clazz)`

This method instantiates the given `Filter` class. The method must support all the annotations applicable to `Filters`. The returned `Filter` instance may be further customized before it is registered with the `ServletContext` via a call to `addFilter(String, Filter)` as defined above. The given `Filter` class must define a zero argument constructor, which is used to instantiate it.

4.4.2.5 `FilterRegistration getFilterRegistration(String filterName)`

This method returns the `FilterRegistration` corresponding to the filter with the given name, or null if no `FilterRegistration` exists under that name. An `UnsupportedOperationException` is thrown if the `ServletContext` was passed to the `contextInitialized` method of a `ServletContextListener` that was neither declared in the `web.xml` or `web-fragment.xml`, nor annotated with `javax.servlet.annotation.WebListener`.

4.4.2.6 `Map<String, ? extends FilterRegistration> getServletRegistrations()`

This method returns a map of `ServletRegistration` objects, keyed by name corresponding to all filters registered with the `ServletContext`. If there are no filters registered with the `ServletContext` an empty map is returned. The returned `Map` includes the `FilterRegistration` objects corresponding to all declared and annotated filters, as well as the `FilterRegistration` objects corresponding to all filters that have been added via one of the `addFilter` methods. Any changes to the returned `Map` MUST not affect the `ServletContext`. An `UnsupportedOperationException` is thrown if the `ServletContext` was passed to the `contextInitialized` method of a `ServletContextListener` that was neither declared in the `web.xml` or `web-fragment.xml`, nor annotated with `javax.servlet.annotation.WebListener`.

4.4.3 Programmatically adding and configuring Listeners

4.4.3.1 `void addListener(String className)`

Add the listener with the given class name to the `ServletContext`. The class with the given name will be loaded using the classloader associated with the application represented by the `ServletContext`, and **MUST** implement one or more of the following interfaces:

- `javax.servlet.ServletContextAttributeListener`
- `javax.servlet.ServletRequestListener`
- `javax.servlet.ServletRequestAttributeListener`
- `javax.servlet.http.HttpSessionListener`
- `javax.servlet.http.HttpSessionAttributeListener`

If the `ServletContext` was passed to the `ServletContainerInitializer`'s `onStartup` method, then the class with the given name **MAY** also implement `javax.servlet.ServletContextListener` in addition to the interfaces listed above. As part of this method call, the container **MUST** load the class with the specified class name to ensure that it implements one of the required interfaces. If the class with the given name implements a listener interface whose invocation order corresponds to the declaration order, that is, if it implements `javax.servlet.ServletRequestListener` or `javax.servlet.http.HttpSessionListener`, then the new listener will be added to the end of the ordered list of listeners of that interface.

4.4.3.2 `<T extends EventListener> void addListener(T t)`

Add the given listener to the `ServletContext`. The given listener **MUST** be an instance of one or more of the following interfaces:

- `javax.servlet.ServletContextAttributeListener`
- `javax.servlet.ServletRequestListener`
- `javax.servlet.ServletRequestAttributeListener`
- `javax.servlet.http.HttpSessionListener`
- `javax.servlet.http.HttpSessionAttributeListener`

If the `ServletContext` was passed to the `ServletContainerInitializer`'s `onStartup` method, then the given listener **MAY** also be an instance of `javax.servlet.ServletContextListener` in addition to the interfaces listed above. If the given listener is an instance of a listener interface whose invocation

order corresponds to the declaration order, that is, if it implements `javax.servlet.ServletRequestListener` or `javax.servlet.http.HttpSessionListener`, then the new listener will be added to the end of the ordered list of listeners of that interface.

4.4.3.3 `void addListener(Class <? extends EventListener> listenerClass)`

Add the listener of the given class type to the `ServletContext`. The given listener class **MUST** implement one or more of the following interfaces:

- `javax.servlet.ServletContextAttributeListener`
- `javax.servlet.ServletRequestListener`
- `javax.servlet.ServletRequestAttributeListener`
- `javax.servlet.http.HttpSessionListener`
- `javax.servlet.http.HttpSessionAttributeListener`

If the `ServletContext` was passed to the `ServletContainerInitializer`'s `onStartup` method, then the given listener class **MAY** also implement `javax.servlet.ServletContextListener` in addition to the interfaces listed above. If the given listener class implements a listener interface whose invocation order corresponds to the declaration order, that is, if it implements `javax.servlet.ServletRequestListener` or `javax.servlet.http.HttpSessionListener`, then the new listener will be added to the end of the ordered list of listeners of that interface.

4.4.3.4 `<T extends EventListener> void createListener(Class<T> clazz)`

This method instantiates the given `EventListener` class. The specified `EventListener` class **MUST** implement at least one of the following interfaces:

- `javax.servlet.ServletContextAttributeListener`
- `javax.servlet.ServletRequestListener`
- `javax.servlet.ServletRequestAttributeListener`
- `javax.servlet.http.HttpSessionListener`
- `javax.servlet.http.HttpSessionAttributeListener`

This method **MUST** support all annotations applicable to the above listener interfaces as defined by this specification. The returned `EventListener` instance may be further customized before it is registered with the `ServletContext` via a call to `addListener(T t)`. The given `EventListener` class **MUST** define a zero argument constructor, which is used to instantiate it.

4.4.3.5 Annotation processing requirements for programmatically added Servlets, Filters and Listeners

When using the programmatic API to add a servlet or create a servlet, apart from the `addServlet` that takes an instance, the following annotations must be introspected in the class in question and the metadata defined in it **MUST** be used unless it is overridden by calls to the API in the `ServletRegistration.Dynamic / ServletRegistration`.

`@ServletSecurity`, `@RunAs`, `@DeclareRoles`, `@MultipartConfig`.

For Filters and Listeners no annotations need to be introspected.

Resource injection on all components (Servlets, Filters and Listeners) added programmatically or created programmatically, other than the ones added via the methods that takes an instance, will only be supported when the component is a Managed Bean. For details about what is a Managed Bean please refer to the Managed Bean specification defined as part of Java EE 6 and JSR 299.

4.5 Context Attributes

A servlet can bind an object attribute into the context by name. Any attribute bound into a context is available to any other servlet that is part of the same Web application. The following methods of `ServletContext` interface allow access to this functionality:

- `setAttribute`
- `getAttribute`
- `getAttributeNames`
- `removeAttribute`

4.5.1 Context Attributes in a Distributed Container

Context attributes are local to the JVM in which they were created. This prevents `ServletContext` attributes from being a shared memory store in a distributed container. When information needs to be shared between servlets running in a distributed environment, the information should be placed into a session (See Chapter 7, “Sessions”), stored in a database, or set in an Enterprise JavaBeans™ component.

4.6 Resources

The `ServletContext` interface provides direct access only to the hierarchy of static content documents that are part of the Web application, including HTML, GIF, and JPEG files, via the following methods of the `ServletContext` interface:

- `getResource`
- `getResourceAsStream`

The `getResource` and `getResourceAsStream` methods take a `String` with a leading `"/` as an argument that gives the path of the resource relative to the root of the context or relative to the `META-INF/resources` directory of a JAR file inside the web application's `WEB-INF/lib` directory. These methods will first search the root of the web application context for the requested resource before looking at any of the JAR files in the `WEB-INF/lib` directory. The order in which the JAR files in the `WEB-INF/lib` directory are scanned is undefined. This hierarchy of documents may exist in the server's file system, in a Web application archive file, on a remote server, or at some other location.

These methods are not used to obtain dynamic content. For example, in a container supporting the JavaServer Pages™ specification¹, a method call of the form `getResource("/index.jsp")` would return the JSP source code and not the processed output. See Chapter 9, "Dispatching Requests" for more information about accessing dynamic content.

The full listing of the resources in the Web application can be accessed using the `getResourcePaths(String path)` method. The full details on the semantics of this method may be found in the API documentation in this specification.

4.7 Multiple Hosts and Servlet Contexts

Web servers may support multiple logical hosts sharing one IP address on a server. This capability is sometimes referred to as "virtual hosting". In this case, each logical host must have its own servlet context or set of servlet contexts. Servlet contexts can not be shared across virtual hosts.

1. The JavaServer Pages™ specification can be found at <http://java.sun.com/products/jsp>

4.8 Reloading Considerations

Although a Container Provider implementation of a class reloading scheme for ease of development is not required, any such implementation must ensure that all servlets, and classes that they may use², are loaded in the scope of a single class loader. This requirement is needed to guarantee that the application will behave as expected by the Developer. As a development aid, the full semantics of notification to session binding listeners should be supported by containers for use in the monitoring of session termination upon class reloading.

Previous generations of containers created new class loaders to load a servlet, distinct from class loaders used to load other servlets or classes used in the servlet context. This could cause object references within a servlet context to point at unexpected classes or objects, and cause unexpected behavior. The requirement is needed to prevent problems caused by demand generation of new class loaders.

4.8.1 Temporary Working Directories

A temporary storage directory is required for each servlet context. Servlet containers must provide a private temporary directory for each servlet context, and make it available via the `javax.servlet.context.tempdir` context attribute. The objects associated with the attribute must be of type `java.io.File`.

The requirement recognizes a common convenience provided in many servlet engine implementations. The container is not required to maintain the contents of the temporary directory when the servlet container restarts, but is required to ensure that the contents of the temporary directory of one servlet context is not visible to the servlet contexts of other Web applications running on the servlet container.

2. An exception is system classes that the servlet may use in a different class loader.

The Response

The response object encapsulates all information to be returned from the server to the client. In the HTTP protocol, this information is transmitted from the server to the client either by HTTP headers or the message body of the request.

5.1 Buffering

A servlet container is allowed, but not required, to buffer output going to the client for efficiency purposes. Typically servers that do buffering make it the default, but allow servlets to specify buffering parameters.

The following methods in the `ServletResponse` interface allow a servlet to access and set buffering information:

- `getBufferSize`
- `setBufferSize`
- `isCommitted`
- `reset`
- `resetBuffer`
- `flushBuffer`

These methods are provided on the `ServletResponse` interface to allow buffering operations to be performed whether the servlet is using a `ServletOutputStream` or a `Writer`.

The `getBufferSize` method returns the size of the underlying buffer being used. If no buffering is being used, this method must return the `int` value of 0 (zero).

The servlet can request a preferred buffer size by using the `setBufferSize` method. The buffer assigned is not required to be the size requested by the servlet, but must be at least as large as the size requested. This allows the container to reuse a set of fixed size buffers, providing a larger buffer than requested if appropriate. The

method must be called before any content is written using a `ServletOutputStream` or `Writer`. If any content has been written or the response object has been committed, this method must throw an `IllegalStateException`.

The `isCommitted` method returns a boolean value indicating whether any response bytes have been returned to the client. The `flushBuffer` method forces content in the buffer to be written to the client.

The `reset` method clears data in the buffer when the response is not committed. Headers, status codes and the state of calling `getWriter` or `getOutputStream` set by the servlet prior to the reset call must be cleared as well. The `resetBuffer` method clears content in the buffer if the response is not committed without clearing the headers and status code.

If the response is committed and the `reset` or `resetBuffer` method is called, an `IllegalStateException` must be thrown. The response and its associated buffer will be unchanged.

When using a buffer, the container must immediately flush the contents of a filled buffer to the client. If this is the first data that is sent to the client, the response is considered to be committed.

5.2 Headers

A servlet can set headers of an HTTP response via the following methods of the `HttpServletResponse` interface:

- `setHeader`
- `addHeader`

The `setHeader` method sets a header with a given name and value. A previous header is replaced by the new header. Where a set of header values exist for the name, the values are cleared and replaced with the new value.

The `addHeader` method adds a header value to the set with a given name. If there are no headers already associated with the name, a new set is created.

Headers may contain data that represents an `int` or a `Date` object. The following convenience methods of the `HttpServletResponse` interface allow a servlet to set a header using the correct formatting for the appropriate data type:

- `setIntHeader`
- `setDateHeader`
- `addIntHeader`
- `addDateHeader`

To be successfully transmitted back to the client, headers must be set before the response is committed. Headers set after the response is committed will be ignored by the servlet container.

Servlet programmers are responsible for ensuring that the `Content-Type` header is appropriately set in the response object for the content the servlet is generating. The HTTP 1.1 specification does not require that this header be set in an HTTP response. Servlet containers must not set a default content type when the servlet programmer does not set the type.

It is recommended that containers use the `X-Powered-By` HTTP header to publish its implementation information. The field value should consist of one or more implementation types, such as "Servlet/3.0". Optionally, the supplementary information of the container and the underlying Java platform can be added after the implementation type within parentheses. The container should be configurable to suppress this header.

Here's the examples of this header.

```
X-Powered-By: Servlet/3.1
```

```
X-Powered-By: Servlet/3.1 JSP/2.2 (GlassFish v3 JRE/1.6.0)
```

5.3 Non Blocking IO

To support non-blocking writes in the Servlet container, in addition to the changes made in the `ServletRequest` as described in Section 3.7, "Non Blocking IO" on page 3-28, the following changes have been made to handle response related classes / interfaces.

The `WriteListener` provides the following callback methods which the container invokes appropriately.

- `WriteListener`
 - `void onWritePossible()`. When a `WriteListener` is registered with the `ServletOutputStream`, this method will be invoked by the container if and only if `canWrite` method on `ServletOutputStream`, described below, has been called and has returned `false`.
 - `onError(Throwable t)`. Invoked when an error occurs processing the response.

Along with the `WriteListener`, the following methods have been added to `ServletOutputStream` class to allow the developer to check with the runtime whether or not it is possible to write the data to be sent to the client.

- `ServletOutputStream`

- `boolean canWrite()`. This method returns `true` if a write to the `ServletOutputStream` will succeed, otherwise it will return `false`. If this method returns `true`, a write operation can be performed on the `ServletOutputStream`. If no further data can be written to the `ServletOutputStream`, then this method will return `false` till the underlying data is flushed at which point the container will invoke the `onWritePossible` method of the `WriteListener`. A subsequent call to this method will return `true`.
- `void setWriteListener(WriteListener listener)`. Associates the `WriteListener` with this `ServletOutputStream`, for the container to invoke the callback methods on the `WriteListener` when it is possible to write data. Registering a `WriteListener` will start non-blocking IO. It is illegal to switch to the traditional blocking IO at that point.

5.4 Convenience Methods

The following convenience methods exist in the `HttpServletResponse` interface:

- `sendRedirect`
- `sendError`

The `sendRedirect` method will set the appropriate headers and content body to redirect the client to a different URL. It is legal to call this method with a relative URL path, however the underlying container must translate the relative path to a fully qualified URL for transmission back to the client. If a partial URL is given and, for whatever reason, cannot be converted into a valid URL, then this method must throw an `IllegalArgumentException`.

The `sendError` method will set the appropriate headers and content body for an error message to return to the client. An optional `String` argument can be provided to the `sendError` method which can be used in the content body of the error.

These methods will have the side effect of committing the response, if it has not already been committed, and terminating it. No further output to the client should be made by the servlet after these methods are called. If data is written to the response after these methods are called, the data is ignored.

If data has been written to the response buffer, but not returned to the client (i.e. the response is not committed), the data in the response buffer must be cleared and replaced with the data set by these methods. If the response is committed, these methods must throw an `IllegalStateException`.

5.5 Internationalization

Servlets should set the locale and the character encoding of a response. The locale is set using the `ServletResponse.setLocale` method. The method can be called repeatedly; but calls made after the response is committed have no effect. If the servlet does not set the locale before the page is committed, the container's default locale is used to determine the response's locale, but no specification is made for the communication with a client, such as `Content-Language` header in the case of HTTP.

```
<locale-encoding-mapping-list>
  <locale-encoding-mapping>
    <locale>ja</locale>
    <encoding>Shift_JIS</encoding>
  </locale-encoding-mapping>
</locale-encoding-mapping-list>
```

If the element does not exist or does not provide a mapping, `setLocale` uses a container dependent mapping. The `setCharacterEncoding`, `setContentType`, and `setLocale` methods can be called repeatedly to change the character encoding. Calls made after the servlet response's `getWriter` method has been called or after the response is committed have no effect on the character encoding. Calls to `setContentType` set the character encoding only if the given content type string provides a value for the `charset` attribute. Calls to `setLocale` set the character encoding only if neither `setCharacterEncoding` nor `setContentType` has set the character encoding before.

If the servlet does not specify a character encoding before the `getWriter` method of the `ServletResponse` interface is called or the response is committed, the default ISO-8859-1 is used.

Containers must communicate the locale and the character encoding used for the servlet response's writer to the client if the protocol in use provides a way for doing so. In the case of HTTP, the locale is communicated via the `Content-Language` header, the character encoding as part of the `Content-Type` header for text media types. Note that the character encoding cannot be communicated via HTTP headers if the servlet does not specify a content type; however, it is still used to encode text written via the servlet response's writer.

5.6 Closure of Response Object

When a response is closed, the container must immediately flush all remaining content in the response buffer to the client. The following events indicate that the servlet has satisfied the request and that the response object is to be closed:

- The termination of the `service` method of the servlet.
- The amount of content specified in the `setContentLength` or `setContentLengthLong` method of the response has been greater than zero and has been written to the response.
- The `sendError` method is called.
- The `sendRedirect` method is called.
- The `complete` method on `AsyncContext` is called.

5.7 Lifetime of the Response Object

Each response object is valid only within the scope of a servlet's `service` method, or within the scope of a filter's `doFilter` method, unless the associated request object has asynchronous processing enabled for the component. If asynchronous processing on the associated request is started, then the request object remains valid until `complete` method on `AsyncContext` is called. Containers commonly recycle response objects in order to avoid the performance overhead of response object creation. The developer must be aware that maintaining references to response objects for which `startAsync` on the corresponding request has not been called, outside the scope described above may lead to non-deterministic behavior.

Filtering

Filters are Java components that allow on the fly transformations of payload and header information in both the request into a resource and the response from a resource

This chapter describes the Java Servlet v.3.0 API classes and methods that provide a lightweight framework for filtering active and static content. It describes how filters are configured in a Web application, and conventions and semantics for their implementation.

API documentation for servlet filters is provided online. The configuration syntax for filters is given by the deployment descriptor schema in Chapter 14, “Deployment Descriptor”. The reader should use these sources as references when reading this chapter.

6.1 What is a filter?

A filter is a reusable piece of code that can transform the content of HTTP requests, responses, and header information. Filters do not generally create a response or respond to a request as servlets do, rather they modify or adapt the requests for a resource, and modify or adapt responses from a resource.

Filters can act on dynamic or static content. For the purposes of this chapter, dynamic and static content are referred to as Web resources.

Among the types of functionality available to the developer needing to use filters are the following:

- The accessing of a resource before a request to it is invoked.
- The processing of the request for a resource before it is invoked.
- The modification of request headers and data by wrapping the request in customized versions of the request object.

- The modification of response headers and response data by providing customized versions of the response object.
- The interception of an invocation of a resource after its call.
- Actions on a servlet, on groups of servlets, or static content by zero, one, or more filters in a specifiable order.

6.1.1 Examples of Filtering Components

- Authentication filters
- Logging and auditing filters
- Image conversion filters
- Data compression filters
- Encryption filters
- Tokenizing filters
- Filters that trigger resource access events
- XSL/T filters that transform XML content
- MIME-type chain filters
- Caching filters

6.2 Main Concepts

The main concepts of this filtering model are described in this section.

The application developer creates a filter by implementing the `javax.servlet.Filter` interface and providing a public constructor taking no arguments. The class is packaged in the Web Archive along with the static content and servlets that make up the Web application. A filter is declared using the `<filter>` element in the deployment descriptor. A filter or collection of filters can be configured for invocation by defining `<filter-mapping>` elements in the deployment descriptor. This is done by mapping filters to a particular servlet by the servlet's logical name, or mapping to a group of servlets and static content resources by mapping a filter to a URL pattern.

6.2.1 Filter Lifecycle

After deployment of the Web application, and before a request causes the container to access a Web resource, the container must locate the list of filters that must be applied to the Web resource as described below. The container must ensure that it has instantiated a filter of the appropriate class for each filter in the list, and called its `init(FilterConfig config)` method. The filter may throw an exception to

indicate that it cannot function properly. If the exception is of type `UnavailableException`, the container may examine the `isPermanent` attribute of the exception and may choose to retry the filter at some later time.

Only one instance per `<filter>` declaration in the deployment descriptor is instantiated per JVM of the container. The container provides the filter `config` as declared in the filter's deployment descriptor, the reference to the `ServletContext` for the Web application, and the set of initialization parameters.

When the container receives an incoming request, it takes the first filter instance in the list and calls its `doFilter` method, passing in the `ServletRequest` and `ServletResponse`, and a reference to the `FilterChain` object it will use.

The `doFilter` method of a filter will typically be implemented following this or some subset of the following pattern:

1. The method examines the request's headers.
2. The method may wrap the request object with a customized implementation of `ServletRequest` or `HttpServletRequest` in order to modify request headers or data.
3. The method may wrap the response object passed in to its `doFilter` method with a customized implementation of `ServletResponse` or `HttpServletResponse` to modify response headers or data.
4. The filter may invoke the next entity in the filter chain. The next entity may be another filter, or if the filter making the invocation is the last filter configured in the deployment descriptor for this chain, the next entity is the target Web resource. The invocation of the next entity is effected by calling the `doFilter` method on the `FilterChain` object, and passing in the request and response with which it was called or passing in wrapped versions it may have created.

The filter chain's implementation of the `doFilter` method, provided by the container, must locate the next entity in the filter chain and invoke its `doFilter` method, passing in the appropriate request and response objects.

Alternatively, the filter chain can block the request by not making the call to invoke the next entity, leaving the filter responsible for filling out the response object.

The `service` method is required to run in the same thread as all filters that apply to the servlet.

5. After invocation of the next filter in the chain, the filter may examine response headers.
6. Alternatively, the filter may have thrown an exception to indicate an error in processing. If the filter throws an `UnavailableException` during its `doFilter` processing, the container must not attempt continued processing down the filter chain. It may choose to retry the whole chain at a later time if the exception is not marked permanent.

7. When the last filter in the chain has been invoked, the next entity accessed is the target servlet or resource at the end of the chain.
8. Before a filter instance can be removed from service by the container, the container must first call the `destroy` method on the filter to enable the filter to release any resources and perform other cleanup operations.

6.2.2 Wrapping Requests and Responses

Central to the notion of filtering is the concept of wrapping a request or response in order that it can override behavior to perform a filtering task. In this model, the developer not only has the ability to override existing methods on the request and response objects, but to provide new API suited to a particular filtering task to a filter or target web resource down the chain. For example, the developer may wish to extend the response object with higher level output objects that the output stream or the writer, such as API that allows DOM objects to be written back to the client.

In order to support this style of filter the container must support the following requirement. When a filter invokes the `doFilter` method on the container's filter chain implementation, the container must ensure that the request and response object that it passes to the next entity in the filter chain, or to the target web resource if the filter was the last in the chain, is the same object that was passed into the `doFilter` method by the calling filter.

The same requirement of wrapper object identity applies to the calls from a servlet or a filter to `RequestDispatcher.forward` OR `RequestDispatcher.include`, when the caller wraps the request or response objects. In this case, the request and response objects seen by the called servlet must be the same wrapper objects that were passed in by the calling servlet or filter.

6.2.3 Filter Environment

A set of initialization parameters can be associated with a filter using the `<init-params>` element in the deployment descriptor. The names and values of these parameters are available to the filter at runtime via the `getInitParameter` and `getInitParameterNames` methods on the filter's `FilterConfig` object. Additionally, the `FilterConfig` affords access to the `ServletContext` of the Web application for the loading of resources, for logging functionality, and for storage of state in the `ServletContext`'s attribute list. A Filter and the target servlet or resource at the end of the filter chain must execute in the same invocation thread.

6.2.4 Configuration of Filters in a Web Application

A filter is defined either via the `@WebFilter` annotation as defined in Section 8.1.2, “`@WebFilter`” on page 8-67 of the specification or in the deployment descriptor using the `<filter>` element. In this element, the programmer declares the following:

- `filter-name`: used to map the filter to a servlet or URL
- `filter-class`: used by the container to identify the filter type
- `init-params`: initialization parameters for a filter

Optionally, the programmer can specify icons, a textual description, and a display name for tool manipulation. The container must instantiate exactly one instance of the Java class defining the filter per filter declaration in the deployment descriptor. Hence, two instances of the same filter class will be instantiated by the container if the developer makes two filter declarations for the same filter class.

Here is an example of a filter declaration:

```
<filter>
  <filter-name>Image Filter</filter-name>
  <filter-class>com.acme.ImageServlet</filter-class>
</filter>
```

Once a filter has been declared in the deployment descriptor, the assembler uses the `<filter-mapping>` element to define servlets and static resources in the Web application to which the filter is to be applied. Filters can be associated with a servlet using the `<servlet-name>` element. For example, the following code example maps the Image Filter filter to the ImageServlet servlet:

```
<filter-mapping>
  <filter-name>Image Filter</filter-name>
  <servlet-name>ImageServlet</servlet-name>
</filter-mapping>
```

Filters can be associated with groups of servlets and static content using the `<url-pattern>` style of filter mapping:

```
<filter-mapping>
  <filter-name>Logging Filter</filter-name>
  <url-pattern>/*</url-pattern>
</filter-mapping>
```

Here the Logging Filter is applied to all the servlets and static content pages in the Web application, because every request URI matches the `'/*'` URL pattern.

When processing a `<filter-mapping>` element using the `<url-pattern>` style, the container must determine whether the `<url-pattern>` matches the request URI using the path mapping rules defined in Chapter 12, “Mapping Requests to Servlets”.

The order the container uses in building the chain of filters to be applied for a particular request URI is as follows:

1. First, the `<url-pattern>` matching filter mappings in the same order that these elements appear in the deployment descriptor.
2. Next, the `<servlet-name>` matching filter mappings in the same order that these elements appear in the deployment descriptor.

If a filter mapping contains both `<servlet-name>` and `<url-pattern>`, the container must expand the filter mapping into multiple filter mappings (one for each `<servlet-name>` and `<url-pattern>`), preserving the order of the `<servlet-name>` and `<url-pattern>` elements. For example, the following filter mapping:

```
<filter-mapping>
  <filter-name>Multiple Mappings Filter</filter-name>
  <url-pattern>/foo/*</url-pattern>
  <servlet-name>Servlet1</servlet-name>
  <servlet-name>Servlet2</servlet-name>
  <url-pattern>/bar/*</url-pattern>
</filter-mapping>
```

is equivalent to:

```
<filter-mapping>
  <filter-name>Multiple Mappings Filter</filter-name>
  <url-pattern>/foo/*</url-pattern>
</filter-mapping>

<filter-mapping>
  <filter-name>Multiple Mappings Filter</filter-name>
  <servlet-name>Servlet1</servlet-name>
</filter-mapping>

<filter-mapping>
  <filter-name>Multiple Mappings Filter</filter-name>
  <servlet-name>Servlet2</servlet-name>
</filter-mapping>

<filter-mapping>
  <filter-name>Multiple Mappings Filter</filter-name>
  <url-pattern>/bar/*</url-pattern>
</filter-mapping>
```

The requirement about the order of the filter chain means that the container, when receiving an incoming request, processes the request as follows:

- Identifies the target Web resource according to the rules of “Specification of Mappings” on page 120.
- If there are filters matched by servlet name and the Web resource has a `<servlet-name>`, the container builds the chain of filters matching in the order declared in the deployment descriptor. The last filter in this chain corresponds to the last `<servlet-name>` matching filter and is the filter that invokes the target Web resource.
- If there are filters using `<url-pattern>` matching and the `<url-pattern>` matches the request URI according to the rules of Section 12.2, “Specification of Mappings”, the container builds the chain of `<url-pattern>` matched filters in the same order as declared in the deployment descriptor. The last filter in this chain is the last `<url-pattern>` matching filter in the deployment descriptor for this request URI. The last filter in this chain is the filter that invokes the first filter in the `<servlet-name>` matching chain, or invokes the target Web resource if there are none.

It is expected that high performance Web containers will cache filter chains so that they do not need to compute them on a per-request basis.

6.2.5 Filters and the RequestDispatcher

New since version 2.4 of the Java Servlet specification is the ability to configure filters to be invoked under request dispatcher `forward()` and `include()` calls.

By using the new `<dispatcher>` element in the deployment descriptor, the developer can indicate for a filter-mapping whether he would like the filter to be applied to requests when:

1. The request comes directly from the client.

This is indicated by a `<dispatcher>` element with value *REQUEST*, or by the absence of any `<dispatcher>` elements.

2. The request is being processed under a request dispatcher representing the Web component matching the `<url-pattern>` or `<servlet-name>` using a `forward()` call.

This is indicated by a `<dispatcher>` element with value *FORWARD*.

3. The request is being processed under a request dispatcher representing the Web component matching the `<url-pattern>` or `<servlet-name>` using an `include()` call.

This is indicated by a `<dispatcher>` element with value *INCLUDE*.

4. The request is being processed with the error page mechanism specified in "Error Handling" on page 106 to an error resource matching the `<url-pattern>`.

This is indicated by a `<dispatcher>` element with the value *ERROR*.

5. The request is being processed with the async context dispatch mechanism specified in "Asynchronous processing" on page 10 to a web component using a `dispatch` call.

This is indicated by a `<dispatcher>` element with the value *ASYNC*.

6. Or any combination of 1, 2, 3, 4 or 5 above.

For example:

```
<filter-mapping>
  <filter-name>Logging Filter</filter-name>
  <url-pattern>/products/*</url-pattern>
</filter-mapping>
```

would result in the Logging Filter being invoked by client requests starting `/products/...` but not underneath a request dispatcher call where the request dispatcher has path commencing `/products/...`. The `LoggingFilter` would be invoked both on the initial dispatch of the request and on resumed request. The following code:

```
<filter-mapping>
  <filter-name>Logging Filter</filter-name>
  <servlet-name>ProductServlet</servlet-name>
  <dispatcher>INCLUDE</dispatcher>
</filter-mapping>
```

would result in the Logging Filter not being invoked by client requests to the `ProductServlet`, nor underneath a request dispatcher `forward()` call to the `ProductServlet`, but would be invoked underneath a request dispatcher `include()` call where the request dispatcher has a name commencing `ProductServlet`. The following code:

```
<filter-mapping>
  <filter-name>Logging Filter</filter-name>
  <url-pattern>/products/*</url-pattern>
  <dispatcher>FORWARD</dispatcher>
  <dispatcher>REQUEST</dispatcher>
</filter-mapping>
```

would result in the Logging Filter being invoked by client requests starting `/products/...` and underneath a request dispatcher `forward()` call where the request dispatcher has path commencing `/products/...`

Finally, the following code uses the special servlet name `'*'`:

```
<filter-mapping>
  <filter-name>All Dispatch Filter</filter-name>
  <servlet-name>*</servlet-name>
  <dispatcher>FORWARD</dispatcher>
</filter-mapping>
```

This code would result in the All Dispatch Filter being invoked on request dispatcher `forward()` calls for all request dispatchers obtained by name or by path.

Sessions

The Hypertext Transfer Protocol (HTTP) is by design a stateless protocol. To build effective Web applications, it is imperative that requests from a particular client be associated with each other. Many strategies for session tracking have evolved over time, but all are difficult or troublesome for the programmer to use directly.

This specification defines a simple `HttpSession` interface that allows a servlet container to use any of several approaches to track a user's session without involving the Application Developer in the nuances of any one approach.

7.1 Session Tracking Mechanisms

The following sections describe approaches to tracking a user's sessions

7.1.1 Cookies

Session tracking through HTTP cookies is the most used session tracking mechanism and is required to be supported by all servlet containers.

The container sends a cookie to the client. The client will then return the cookie on each subsequent request to the server, unambiguously associating the request with a session. The standard name of the session tracking cookie must be `JSESSIONID`, which must be supported by all 3.0 compliant containers. Containers may allow the name of the session tracking cookie to be customized through container specific configuration.

All servlet containers **MUST** provide an ability to configure whether or not the container marks the session tracking cookie as `HttpOnly`. The established configuration must apply to all contexts for which a context specific configuration has not been established (see `SessionCookieConfig` javadoc for more details).

If a web application configures a custom name for its session tracking cookies, the same custom name will also be used as the name of the URI parameter if the session id is encoded in the URL (provided that URL rewriting has been enabled).

7.1.2 SSL Sessions

Secure Sockets Layer, the encryption technology used in the HTTPS protocol, has a built-in mechanism allowing multiple requests from a client to be unambiguously identified as being part of a session. A servlet container can easily use this data to define a session.

7.1.3 URL Rewriting

URL rewriting is the lowest common denominator of session tracking. When a client will not accept a cookie, URL rewriting may be used by the server as the basis for session tracking. URL rewriting involves adding data, a session ID, to the URL path that is interpreted by the container to associate the request with a session.

The session ID must be encoded as a path parameter in the URL string. The name of the parameter must be `jsessionid`. Here is an example of a URL containing encoded path information:

```
http://www.myserver.com/catalog/index.html;jsessionid=1234
```

URL rewriting exposes session identifiers in logs, bookmarks, referer headers, cached HTML, and the URL bar. URL rewriting should not be used as a session tracking mechanism where cookies or SSL sessions are supported and suitable.

7.1.4 Session Integrity

Web containers must be able to support the HTTP session while servicing HTTP requests from clients that do not support the use of cookies. To fulfill this requirement, Web containers commonly support the URL rewriting mechanism.

7.2 Creating a Session

A session is considered “new” when it is only a prospective session and has not been established. Because HTTP is a request-response based protocol, an HTTP session is considered to be new until a client “joins” it. A client joins a session when session

tracking information has been returned to the server indicating that a session has been established. Until the client joins a session, it cannot be assumed that the next request from the client will be recognized as part of a session.

The session is considered to be “new” if either of the following is true:

- The client does not yet know about the session
- The client chooses not to join a session.

These conditions define the situation where the servlet container has no mechanism by which to associate a request with a previous request.

A Servlet Developer must design his application to handle a situation where a client has not, can not, or will not join a session.

7.3 Session Scope

`HttpSession` objects must be scoped at the application (or servlet context) level. The underlying mechanism, such as the cookie used to establish the session, can be the same for different contexts, but the object referenced, including the attributes in that object, must never be shared between contexts by the container.

To illustrate this requirement with an example: if a servlet uses the `RequestDispatcher` to call a servlet in another Web application, any sessions created for and visible to the servlet being called must be different from those visible to the calling servlet.

Additionally, sessions of a context must be resumable by requests into that context regardless of whether their associated context was being accessed directly or as the target of a request dispatch at the time the sessions were created.

7.4 Binding Attributes into a Session

A servlet can bind an object attribute into an `HttpSession` implementation by name. Any object bound into a session is available to any other servlet that belongs to the same `ServletContext` and handles a request identified as being a part of the same session.

Some objects may require notification when they are placed into, or removed from, a session. This information can be obtained by having the object implement the `HttpSessionBindingListener` interface. This interface defines the following methods that will signal an object being bound into, or being unbound from, a session.

- `valueBound`
- `valueUnbound`

The `valueBound` method must be called before the object is made available via the `getAttribute` method of the `HttpSession` interface. The `valueUnbound` method must be called after the object is no longer available via the `getAttribute` method of the `HttpSession` interface.

7.5 Session Timeouts

In the HTTP protocol, there is no explicit termination signal when a client is no longer active. This means that the only mechanism that can be used to indicate when a client is no longer active is a time out period.

The default time out period for sessions is defined by the servlet container and can be obtained via the `getMaxInactiveInterval` method of the `HttpSession` interface. This time out can be changed by the Developer using the `setMaxInactiveInterval` method of the `HttpSession` interface. The time out periods used by these methods are defined in seconds. By definition, if the time out period for a session is set to 0 or lesser value, the session will never expire. The session invalidation will not take effect until all servlets using that session have exited the service method. Once the session invalidation is initiated, a new request must not be able to see that session.

7.6 Last Accessed Times

The `getLastAccessedTime` method of the `HttpSession` interface allows a servlet to determine the last time the session was accessed before the current request. The session is considered to be accessed when a request that is part of the session is first handled by the servlet container.

7.7 Important Session Semantics

7.7.1 Threading Issues

Multiple servlets executing request threads may have active access to the same session object at the same time. The container must ensure that manipulation of internal data structures representing the session attributes is performed in a thread safe manner. The Developer has the responsibility for thread safe access to the attribute objects themselves. This will protect the attribute collection inside the `HttpSession` object from concurrent access, eliminating the opportunity for an application to cause that collection to become corrupted.

7.7.2 Distributed Environments

Within an application marked as distributable, all requests that are part of a session must be handled by one JVM at a time. The container must be able to handle all objects placed into instances of the `HttpSession` class using the `setAttribute` or `putValue` methods appropriately. The following restrictions are imposed to meet these conditions:

- The container must accept objects that implement the `Serializable` interface.
- The container may choose to support storage of other designated objects in the `HttpSession`, such as references to Enterprise JavaBeans components and transactions.
- Migration of sessions will be handled by container-specific facilities.

The distributed servlet container must throw an `IllegalArgumentException` for objects where the container cannot support the mechanism necessary for migration of the session storing them.

The distributed servlet container must support the mechanism necessary for migrating objects that implement `Serializable`.

These restrictions mean that the Developer is ensured that there are no additional concurrency issues beyond those encountered in a non-distributed container.

The Container Provider can ensure scalability and quality of service features like load-balancing and failover by having the ability to move a session object, and its contents, from any active node of the distributed system to a different node of the system.

If distributed containers persist or migrate sessions to provide quality of service features, they are not restricted to using the native JVM Serialization mechanism for serializing `HttpSessions` and their attributes. Developers are not guaranteed that containers will call `readObject` and `writeObject` methods on session attributes if they implement them, but are guaranteed that the `Serializable` closure of their attributes will be preserved.

Containers must notify any session attributes implementing the `HttpSessionActivationListener` during migration of a session. They must notify listeners of passivation prior to serialization of a session, and of activation after deserialization of a session.

Application Developers writing distributed applications should be aware that since the container may run in more than one Java virtual machine, the developer cannot depend on static variables for storing an application state. They should store such states using an enterprise bean or a database.

7.7.3 Client Semantics

Due to the fact that cookies or SSL certificates are typically controlled by the Web browser process and are not associated with any particular window of the browser, requests from all windows of a client application to a servlet container might be part of the same session. For maximum portability, the Developer should always assume that all windows of a client are participating in the same session.

Annotations and pluggability

This chapter talks about the annotations defined in Servlet 3.0 specification and the enhancements to enable pluggability of frameworks and libraries for use within a web application.

8.1 Annotations and pluggability

In a web application, classes using annotations will have their annotations processed only if they are located in the `WEB-INF/classes` directory, or if they are packaged in a jar file located in `WEB-INF/lib` within the application.

The web application deployment descriptor contains a new “`metadata-complete`” attribute on the `web-app` element. The “`metadata-complete`” attribute defines whether the web descriptor is complete, or whether the class files of the jar file should be examined for annotations and web fragments at deployment time. If “`metadata-complete`” is set to “`true`”, the deployment tool **MUST** ignore any servlet annotations present in the class files of the application and web fragments. If the `metadata-complete` attribute is not specified or is set to “`false`”, the deployment tool must examine the class files of the application for annotations, and scan for web fragments.

Following are the annotations that **MUST** be supported by a Servlet 3.0 compliant web container.

8.1.1 `@WebServlet`

This annotation is used to define a `Servlet` component in a web application. This annotation is specified on a class and contains metadata about the `Servlet` being declared. The `urlPatterns` or the `value` attribute on the annotation **MUST** be

present. All other attributes are optional with default settings (see javadocs for more details). It is recommended to use `value` when the only attribute on the annotation is the url pattern and to use the `urlPatterns` attribute when the other attributes are also used. It is illegal to have both `value` and `urlPatterns` attribute used together on the same annotation. The default name of the `Servlet` if not specified is the fully qualified class name. The annotated servlet MUST specify at least one url pattern to be deployed. If the same servlet class is declared in the deployment descriptor under a different name, a new instance of the servlet MUST be instantiated. If the same servlet class is added to the `ServletContext` via the programmatic API defined in Section 4.4.1, “Programmatically adding and configuring Servlets” on page 4-35 the values declared via the `@WebServlet` annotation MUST be ignored and a new instance of the servlet with the name specified MUST be created.

Classes annotated with `@WebServlet` class MUST extend the `javax.servlet.http.HttpServlet` class.

Following is an example of how this annotation would be used.

CODE EXAMPLE 8-1 `@WebServlet` Annotation Example

```
@WebServlet("/foo")
public class CalculatorServlet extends HttpServlet{
    //...
}
```

Following is an example of how this annotation would be used with some more of the attributes specified.

CODE EXAMPLE 8-2 `@WebServlet` annotation example using other annotation attributes specified

```
@WebServlet(name="MyServlet", urlPatterns={"/foo", "/bar"})
public class SampleUsingAnnotationAttributes extends HttpServlet{
    public void doGet(HttpServletRequest req, HttpServletResponse
res) {

    }
}
```

8.1.2 @WebFilter

This annotation is used to define a `Filter` in a web application. This annotation is specified on a class and contains metadata about the filter being declared. The default name of the `Filter` if not specified is the fully qualified class name. The `urlPatterns` attribute, `servletNames` attribute or the `value` attribute of the annotation **MUST** be specified. All other attributes are optional with default settings (see javadocs for more details). It is recommended to use `value` when the only attribute on the annotation is the url pattern and to use the `urlPatterns` attribute when the other attributes are also used. It is illegal to have both `value` and `urlPatterns` attribute used together on the same annotation.

Classes annotated with `@WebFilter` **MUST** implement `javax.servlet.Filter`.

Following is an example of how this annotation would be used.

CODE EXAMPLE 8-3 `@WebFilter` annotation example

```
@WebFilter("/foo")
public class MyFilter implements Filter {
    public void doFilter(HttpServletRequest req, HttpServletResponse
res)
    {
        ...
    }
}
```

8.1.3 @WebInitParam

This annotation is used to specify any init parameters that must be passed to the `Servlet` or the `Filter`. It is an attribute of the `WebServlet` and `WebFilter` annotation.

8.1.4 @WebListener

The `WebListener` annotation is used to annotate a listener to get events for various operations on the particular web application context. Classes annotated with `@WebListener` **MUST** implement one of the following interfaces:

- `javax.servlet.ServletContextListener`
- `javax.servlet.ServletContextAttributeListener`
- `javax.servlet.ServletRequestListener`
- `javax.servlet.ServletRequestAttributeListener`

- `javax.servlet.http.HttpSessionListener`
- `javax.servlet.http.HttpSessionAttributeListener`

An example:

```
@WebListener
public class MyListener implements ServletContextListener{
    public void contextInitialized(ServletContextEvent sce) {
        ServletContext sc = sce.getServletContext();
        sc.addServlet("myServlet", "Sample servlet",
            "foo.bar.MyServlet", null, -1);
        sc.addServletMapping("myServlet", new String[] {
            "/urlpattern/*" });
    }
}
```

8.1.5 @MultipartConfig

This annotation, when specified on a Servlet, indicates that the request it expects is of type `mime/multipart`. The `HttpServletRequest` object of the corresponding servlet MUST make available the mime attachments via the `getParts` and `getPart` methods to iterate over the various mime attachments. The `location` attribute of the `javax.servlet.annotation.MultipartConfig` and the `<location>` element of the `<multipart-config>` is interpreted as an absolute path and defaults to the value of the `javax.servlet.context.tempdir`. If a relative path is specified, it will be relative to the `tempdir` location. The test for absolute path vs relative path MUST be done via `java.io.File.isAbsolute`.

8.1.6 Other annotations / conventions

In addition to these annotations all the annotations defined in Section 15.5, “Annotations and Resource Injection” on page 15-183 will continue to work in the context of these new annotations.

By default all applications will have `index.html` and `index.jsp` in the list of `welcome-file-list`. The descriptor may be used to override these default settings.

The order in which the Listeners, Servlets are loaded from the various framework jars / classes in the `WEB-INF/classes` or `WEB-INF/lib` is unspecified when using annotations. If ordering is important then look at the section for modularity of `web.xml` and ordering of `web.xml` and `web-fragment.xml` below. The order can be specified in the deployment descriptor only.

8.2 Pluggability

8.2.1 Modularity of `web.xml`

Using the annotations defined above makes the use of `web.xml` optional. However for overriding either the default values or the values set via annotations, the deployment descriptor is used. As before, if the `metadata-complete` element is set to `true` in the `web.xml` descriptor, annotations in the class files and `web-fragments` bundled in jars will not be processed. It implies that all the metadata for the application is specified via the `web.xml` descriptor.

For better pluggability and less configuration for developers, in this version (Servlet 3.0) of the specification we are introducing the notion of web module deployment descriptor fragments (web fragment). A web fragment is a part or all of the `web.xml` that can be specified and included in a library or framework jar's `META-INF` directory. A plain old jar file in the `WEB-INF/lib` directory with no `web-fragment.xml` is also considered a fragment. Any annotations specified in it will be processed according to the rules defined in 8.2.3. The container will pick up and use the configuration as per the rules defined below.

A web fragment is a logical partitioning of the web application in such a way that the frameworks being used within the web application can define all the artifacts without asking developers to edit or add information in the `web.xml`. It can include almost all the same elements that the `web.xml` descriptor uses. However the top level element for the descriptor **MUST** be `web-fragment` and the corresponding descriptor file **MUST** be called `web-fragment.xml`. The ordering related elements also differ between the `web-fragment.xml` and `web.xml`. See the corresponding schema for web-fragments in the deployment descriptor section in Chapter 14.

If a framework is packaged as a jar file and has metadata information in the form of deployment descriptor then the `web-fragment.xml` descriptor must be in the `META-INF/` directory of the jar file.

If a framework wants its `META-INF/web-fragment.xml` honored in such a way that it augments a web application's `web.xml`, the framework must be bundled within the web application's `WEB-INF/lib` directory. In order for any other types of

resources (e.g., class files) of the framework to be made available to a web application, it is sufficient for the framework to be present anywhere in the classloader delegation chain of the web application. In other words, only JAR files bundled in a web application's `WEB-INF/lib` directory, but not those higher up in the class loading delegation chain, need to be scanned for `web-fragment.xml`

During deployment the container is responsible for scanning the location specified above and discovering the `web-fragment.xml` and processing them. The requirements about name uniqueness that exist currently for a single `web.xml` also apply to the union of a `web.xml` and all applicable `web-fragment.xml` files.

An example of what a library or framework can include is shown below

```
<web-fragment>
  <servlet>
    <servlet-name>welcome</servlet-name>
    <servlet-class>
      WelcomeServlet
    </servlet-class>
  </servlet>
  <listener>
    <listener-class>
      RequestListener
    </listener-class>
  </listener>
</web-fragment>
```

The above `web-fragment.xml` would be included in the `META-INF/` directory of the framework's jar file. The order in which configuration from `web-fragment.xml` and annotations should be applied is undefined. If ordering is an important aspect for a particular application please see rules defined below on how to achieve the order desired.

8.2.2 Ordering of `web.xml` and `web-fragment.xml`

Since the specification allows the application configuration resources to be composed of multiple configuration files (`web.xml` and `web-fragment.xml`), discovered and loaded from several different places in the application, the question of ordering must be addressed. This section specifies how configuration resource authors may declare the ordering requirements of their artifacts.

A `web-fragment.xml` may have a top level `<name>` element of type `javaee:java-identifierType`. There can only be one `<name>` element in a `web-fragment.xml`. If a `<name>` element is present, it must be considered for the ordering of artifacts (unless the duplicate name exception applies, as described below).

Two cases must be considered to allow application configuration resources to express their ordering preferences.

1. Absolute ordering: an `<absolute-ordering>` element in the `web.xml`. There can only be one `<absolute-ordering>` element in a `web.xml`.
 - a. In this case, ordering preferences that would have been handled by case 2 below must be ignored.
 - b. The `web.xml` and `WEB-INF/classes` MUST be processed before any of the web-fragments listed in the `absolute-ordering` element.
 - c. Any `<name>` element direct children of the `<absolute-ordering>` MUST be interpreted as indicating the absolute ordering in which those named web-fragments, which may or may not be present, must be processed.
 - d. The `<absolute-ordering>` element may contain zero or one `<others />` element. The required action for this element is described below. If the `<absolute-ordering>` element does not contain an `<others/>` element, any web-fragment not specifically mentioned within `<name />` elements MUST be ignored. Excluded jars are not scanned for annotated servlets, filters or listeners. However, if a servlet, filter or listener from an excluded jar is listed in `web.xml` or a non-excluded `web-fragment.xml`, then it's annotations will apply unless otherwise excluded by `metadata-complete`. `ServletContextListeners` discovered in TLD files of excluded jars are not able to configure filters and servlets using the programmatic APIs. Any attempt to do so will result in an `IllegalStateException`. If a discovered `ServletContainerInitializer` is loaded from an excluded jar, it will be ignored. Excluded jars are not scanned for classes to be handled by any `ServletContainerInitializer`.
 - e. Duplicate name exception: if, when traversing the children of `<absolute-ordering>`, multiple children with the same `<name>` element are encountered, only the first such occurrence must be considered.
2. Relative ordering: an `<ordering>` element within the `web-fragment.xml`. There can only be one `<ordering>` element in a `web-fragment.xml`.
 - a. A `web-fragment.xml` may have an `<ordering>` element. If so, this element must contain zero or one `<before>` element and zero or one `<after>` element. The meaning of these elements is explained below.
 - b. The `web.xml` and `WEB-INF/classes` MUST be processed before any of the web-fragments listed in the `ordering` element.

- c. Duplicate name exception: if, when traversing the web-fragments, multiple members with the same `<name>` element are encountered, the application must log an informative error message including information to help fix the problem, and must fail to deploy. For example, one way to fix this problem is for the user to use absolute ordering, in which case relative ordering is ignored.
- d. Consider this abbreviated but illustrative example. 3 web-fragments - `MyFragment1`, `MyFragment2` and `MyFragment3` are part of the application that also includes a `web.xml`.

```
web-fragment.xml
```

```
<web-fragment>
  <name>MyFragment1</name>
  <ordering><after><name>MyFragment2</name></after></ordering>
  ...
</web-fragment>
```

```
web-fragment.xml
```

```
<web-fragment>
  <name>MyFragment2</name>
  ..
</web-fragment>
```

```
web-fragment.xml
```

```
<web-fragment>
  <name>MyFragment3</name>
  <ordering><before><others/></before></ordering>
  ..
</web-fragment>
```

```
web.xml
```

```
<web-app>
  ...
</web-app>
```

In this example the processing order will be

```
web.xml
```

```
MyFragment3
```

MyFragment2

MyFragment1

The preceding example illustrates some, but not all, of the following principles.

- `<before>` means the document must be ordered before the document with the name matching what is specified within the nested `<name>` element.
- `<after>` means the document must be ordered after the document with the name matching what is specified within the nested `<name>` element.
- There is a special element `<others/>` which may be included zero or one time within the `<before>` or `<after>` element, or zero or one time directly within the `<absolute-ordering>` element. The `<others/>` element must be handled as follows.
 - If the `<before>` element contains a nested `<others/>`, the document will be moved to the beginning of the list of sorted documents. If there are multiple documents stating `<before><others/>`, they will all be at the beginning of the list of sorted documents, but the ordering within the group of such documents is unspecified.
 - If the `<after>` element contains a nested `<others/>`, the document will be moved to the end of the list of sorted documents. If there are multiple documents requiring `<after><others/>`, they will all be at the end of the list of sorted documents, but the ordering within the group of such documents is unspecified.
 - Within a `<before>` or `<after>` element, if an `<others/>` element is present, but is not the only `<name>` element within its parent element, the other elements within that parent must be considered in the ordering process.
 - If the `<others/>` element appears directly within the `<absolute-ordering>` element, the runtime must ensure that any web-fragments not explicitly named in the `<absolute-ordering>` section are included at that point in the processing order.
- If a `web-fragment.xml` file does not have an `<ordering>` or the `web.xml` does not have an `<absolute-ordering>` element the artifacts are assumed to not have any ordering dependency.
- If the runtime discovers circular references, an informative message must be logged, and the application must fail to deploy. Again, one course of action the user may take is to use absolute ordering in the `web.xml`.
- The previous example can be extended to illustrate the case when the `web.xml` contains an ordering section.

```
web.xml
<web-app>
<absolute-ordering>
    <name>MyFragment3</name>
    <name>MyFragment2</name>
```

```
</absolute-ordering>
...
</web-app>
```

In this example, the ordering for the various elements will be

web.xml

MyFragment3

MyFragment2

Some additional example scenarios are included below. All of these apply to relative ordering and not absolute ordering

Document A:

```
<after>
  <others/>
  <name>
    C
  </name>
</after>
```

Document B

```
<before>
  <others/>
</before>
```

Document C:

```
<after>
  <others/>
</after>
```

Document D: no ordering

Document E: no ordering

Document F:

```
<before>
  <others/>
  <name>
    B
```

```
</name>  
</before>
```

Resulting parse order:

web.xml, F, B, D, E, C, A.

Document <no id>:

```
<after>  
  <others/>  
</after>  
<before>  
  <name>  
    C  
  </name>  
</before>
```

Document B:

```
<before>  
  <others/>  
</before>
```

Document C: no ordering

Document D:

```
<after>  
  <others/>  
</after>
```

Document E:

```
<before>  
  <others/>  
</before>
```

Document F: no ordering

Resulting parse order can be one of the following:

- B, E, F, <no id>, C, D
- B, E, F, <no id>, D, C
- E, B, F, <no id>, C, D
- E, B, F, <no id>, D, C

- E, B, F, D, <no id>, C
- E, B, F, D, <no id>, D

Document A:

```
<after>
  <name>
    B
  </name>
</after>
```

Document B: no ordering

Document C:

```
<before>
  <others/>
</before>
```

Document D: no ordering

Resulting parse order: C, B, D, A. The parse order could also be: C, D, B, A or C, B, A, D

8.2.3 Assembling the descriptor from web.xml, web-fragment.xml and annotations

If the order in which the listeners, servlets, filters are invoked is important to an application then a deployment descriptor must be used. Also, if necessary, the ordering element defined above can be used. As described above, when using annotations to define the listeners, servlets and filters, the order in which they are invoked is unspecified. Below are a set of rules that apply for assembling the final deployment descriptor for the application:

1. The order for listeners, servlets, filters if relevant must be specified in either the `web-fragment.xml` or the `web.xml`.
2. The ordering will be based on the order in which they are defined in the descriptor and on the `absolute-ordering` element in the `web.xml` or an `ordering` element in the `web-fragment.xml`, if present.
 - a. Filters that match a request are chained in the order in which they are declared in the `web.xml`.

- b. Servlets are initialized either lazily at request processing time or eagerly during deployment. In the latter case, they are initialized in the order indicated by their `load-on-startup` elements.
- c. Prior to this release of the specification, context listeners were invoked in random order. As of Servlet 3.0, the listeners are invoked in the order in which they are declared in the `web.xml` as specified below:
 - i. Implementations of `javax.servlet.ServletContextListener` are invoked at their `contextInitialized` method in the order in which they have been declared, and at their `contextDestroyed` method in reverse order.
 - ii. Implementations of `javax.servlet.ServletRequestListener` are invoked at their `requestInitialized` method in the order in which they have been declared, and at their `requestDestroyed` method in reverse order.
 - iii. Implementations of `javax.servlet.http.HttpSessionListener` are invoked at their `sessionCreated` method in the order in which they have been declared, and at their `sessionDestroyed` method in reverse order.
 - iv. The invocation order for any of the other listener interfaces is unspecified.
- 3. If a servlet is disabled using the `enabled` element introduced in the `web.xml` then the servlet will not be available at the `url-pattern` specified for the servlet.
- 4. The `web.xml` of the web application has the highest precedence when resolving conflicts between the `web.xml`, `web-fragment.xml` and annotations.
- 5. If `metadata-complete` is not specified in the descriptors, or is set to `false` in the deployment descriptor, then the effective metadata for the application is derived by combining the metadata present in the annotations and the descriptors. The rules for merging are specified below -
 - a. Configuration settings in web fragments are used to augment those specified in the main `web.xml` in such a way as if they had been specified in the same `web.xml`.
 - b. The order in which configuration settings of web fragments are added to those in the main `web.xml` is as specified above in Section 8.2.2, "Ordering of `web.xml` and `web-fragment.xml`" on page 8-70
 - c. The `metadata-complete` attribute when set to `true` in the main `web.xml`, is considered complete and scanning of annotations and fragments will not occur at deployment time. The `absolute-ordering` and `ordering` elements will be ignored if present. When set to `true` on a fragment, the `metadata-complete` attribute applies only to scanning of annotations in that particular jar.

- d. Web fragments are merged into the main `web.xml` unless the `metadata-complete` is set to `true`. The merging takes place after annotation processing on the corresponding fragment.
- e. The following are considered configuration conflicts when augmenting a `web.xml` with web fragments:
 - i. Multiple `<init-param>` elements with the same `<param-name>` but different `<param-value>`
 - ii. Multiple `<mime-mapping>` elements with the same `<extension>` but different `<mime-type>`
- f. The above configuration conflicts are resolved as follows:
 - i. Configuration conflicts between the main `web.xml` and a web fragment are resolved such that the configuration in the `web.xml` takes precedence.
 - ii. Configuration conflicts between two web fragments, where the element at the center of the conflict is not present in the main `web.xml`, will result in an error. An informative message must be logged, and the application must fail to deploy.
- g. After the above conflicts have been resolved, these additional rules are applied
 - i. Elements that may be declared any number of times are additive across the `web-fragments` in the resulting `web.xml`. For example, `<context-param>` elements with different `<param-name>` are additive.
 - ii. Elements that may be declared any number of times, if specified in the `web.xml` overrides the values specified in the `web-fragments` with the same name.
 - iii. If an element with a minimum occurrence of zero, and a maximum occurrence of one, is present in a web fragment, and missing in the main `web.xml`, the main `web.xml` inherits the setting from the web fragment. If the element is present in both the main `web.xml` and the web fragment, the configuration setting in the main `web.xml` takes precedence. For example, if both the main `web.xml` and a web fragment declare the same servlet, and the servlet declaration in the web fragment specifies a `<load-on-startup>` element, whereas the one in the main `web.xml` does not, then the `<load-on-startup>` element from the web fragment will be used in the merged `web.xml`.
 - iv. It is considered an error if an element with a minimum occurrence of zero, and a maximum occurrence of one, is specified differently in two web fragments, while absent from the main `web.xml`. For example, if two web fragments declare the same servlet, but with different `<load-on-startup>` elements, and the same servlet is also declared in the main `web.xml`, but without any `<load-on-startup>`, then an error must be reported.

- v. `<welcome-file>` declarations are additive.
- vi. `<servlet-mapping>` elements with the same `<servlet-name>` are additive across web-fragments. `<servlet-mapping>` specified in the `web.xml` overrides values specified in the web-fragments with the same `<servlet-name>`.
- vii. `<filter-mapping>` elements with the same `<filter-name>` are additive across web-fragments. `<filter-mapping>` specified in the `web.xml` overrides values specified in the web-fragments with the same `<filter-name>`.
- viii. Multiple `<listener>` elements with the same `<listener-class>` are treated as a single `<listener>` declaration
- ix. The `web.xml` resulting from the merge is considered `<distributable>` only if all its web fragments are marked as `<distributable>` as well.
- x. The top-level `<icon>` and its children elements, `<display-name>`, and `<description>` elements of a web fragment are ignored.
- xi. `jsp-property-group` is additive. It is recommended that `jsp-config` element use the `url-pattern` as opposed to extension mappings when bundling static resources in the `META-INF/resources` directory of a jar file. Further more JSP resources for a fragment should be in a sub-directory same as the fragment name, if there exists one. This helps prevent a web-fragment's `jsp-property-group` from affecting the JSPs in the main doocroot of the application and the `jsp-property-group` from affecting the JSPs in a fragment's `META-INF/resources` directory.
- h. For all the resource reference elements (`env-entry`, `ejb-ref`, `ejb-local-ref`, `service-ref`, `resource-ref`, `resource-env-ref`, `message-destination-ref`, `persistence-context-ref` and `persistence-unit-ref`) the following rules apply:
 - i. If any resource reference element is present in a web fragment, and is missing in the main `web.xml`, the main `web.xml` inherits the value from the web fragment. If the element is present in both the main `web.xml` and the web fragment, with the same name, the `web.xml` takes precedence. None of the child elements from the fragment are merged into the main `web.xml` except for the `injection-target` as specified below. For example, if both the main `web.xml` and a web fragment declare a `<resource-ref>` with the same `<resource-ref-name>`, the `<resource-ref>` from the `web.xml` will be used without any child elements being merged from the fragment except `<injection-target>` as described below.
 - ii. If a resource reference element is specified in two fragments, while absent from the main `web.xml`, and all the attributes and child elements of the resource reference element are identical, the resource reference will be

merged into the main `web.xml`. It is considered an error if a resource reference element has the same name specified in two fragments, while absent from the main `web.xml` and the attributes and child elements are not identical in the two fragments. An error must be reported and the application MUST fail to deploy. For example, if two web fragments declare a `<resource-ref>` with the same `<resource-ref-name>` element but the type in one is specified as `javax.sql.DataSource` while the type in the other is that of a JavaMail resource, it is an error and the application will fail to deploy

iii. For resource reference element with the same name `<injection-target>` elements from the fragments will be merged into the main `web.xml`.

- i. In addition to the merging rules for `web-fragment.xml` defined above, the following rules apply when using the resource reference annotations (`@Resource`, `@Resources`, `@EJB`, `@EJBs`, `@WebServiceRef`, `@WebServiceRefs`, `@PersistenceContext`, `@PersistenceContexts`, `@PersistenceUnit`, and `@PersistenceUnits`)

If a resource reference annotation is applied on a class, it is equivalent to defining a resource, however it is not equivalent to defining an `injection-target`. The rules above apply for `injection-target` element in this case.

If a resource reference annotation is used on a field it is equivalent to defining the `injection-target` element in the `web.xml`. However if there is no `injection-target` element in the descriptor then the `injection-target` from the fragments will still be merged into the `web.xml` as defined above.

If on the other hand there is an `injection-target` in the main `web.xml` and there is a resource reference annotation with the same resource name, then it is considered an override for the resource reference annotation. In this case since there is an `injection-target` specified in the descriptor, the rules defined above would apply in addition to overriding the value for the resource reference annotation.

- j. If a `data-source` element is specified in two fragments, while absent from the main `web.xml`, and all the attributes and child elements of the `data-source` element are identical, the `data-source` will be merged into the main `web.xml`. It is considered an error if a `data-source` element has the same name specified in two fragments, while absent from the main `web.xml` and the attributes and child elements are not identical in the two fragments. In such a case an error must be reported and the application MUST fail to deploy.

Below are some examples that show the outcome in the different cases.

CODE EXAMPLE 8-4

`web.xml` - no resource-ref definition

Fragment 1

```

web-fragment.xml
<resource-ref>
  <resource-ref-name="foo">
    ...
  <injection-target>
    <injection-target-class>
      com.foo.Bar.class
    </injection-target-class>
    <injection-target-name>
      baz
    </injection-target-name>
  </injection-target>
</resource-ref>

```

The effective metadata would be

```

<resource-ref>
  <resource-ref-name="foo">
    ....
    <injection-target>
      <injection-target-class>
        com.foo.Bar.class
      </injection-target-class>
      <injection-target-name>
        baz
      </injection-target-name>
    </injection-target>
</resource-ref>

```

CODE EXAMPLE 8-5

```

web.xml
<resource-ref>
  <resource-ref-name="foo">
    ...
</resource-ref>

```

Fragment 1

web-fragment.xml

```
<resource-ref>
  <resource-ref-name="foo">
    ...
  <injection-target>
    <injection-target-class>
      com.foo.Bar.class
    </injection-target-class>
    <injection-target-name>
      baz
    </injection-target-name>
  </injection-target>
</resource-ref>
```

Fragment 2

web-fragment.xml

```
<resource-ref>
  <resource-ref-name="foo">
    ...
  <injection-target>
    <injection-target-class>
      com.foo.Bar2.class
    </injection-target-class>
    <injection-target-name>
      baz2
    </injection-target-name>
  </injection-target>
</resource-ref>
```

The effective metadata would be

```
<resource-ref>
  <resource-ref-name="foo">
    ....
  <injection-target>
    <injection-target-class>
```

```

        com.foo.Bar.class
    </injection-target-class>
    <injection-target-name>
        baz
    </injection-target-name>
</injection-target>

    <injection-target>
    <injection-target-class>
        com.foo.Bar2.class
    </injection-target-class>
    <injection-target-name>
        baz2
    </injection-target-name>
</injection-target>
</resource-ref>

```

CODE EXAMPLE 8-6

web.xml

```

<resource-ref>
    <resource-ref-name="foo">
    <injection-target>
    <injection-target-class>
        com.foo.Bar3.class
    </injection-target-class>
    <injection-target-name>
        baz3
    </injection-target-name>

    ...
</resource-ref>

```

Fragment 1

```

web-fragment.xml<resource-ref>
    <resource-ref-name="foo">

```

```

...
<injection-target>
  <injection-target-class>
    com.foo.Bar.class
  </injection-target-class>
  <injection-target-name>
    baz
  </injection-target-name>
</injection-target>
</resource-ref>

```

Fragment 2

```

web-fragment.xml<resource-ref>
  <resource-ref-name="foo">
    ...
  <injection-target>
    <injection-target-class>
      com.foo.Bar2.class
    </injection-target-class>
    <injection-target-name>
      baz2
    </injection-target-name>
  </injection-target>
</resource-ref>

```

The effective metadata would be

```

<resource-ref>
  <resource-ref-name="foo">
    <injection-target>
      <injection-target-class>
        com.foo.Bar3.class
      </injection-target-class>
      <injection-target-name>
        baz3
      </injection-target-name>
    </injection-target>
  </resource-ref>

```



```

<injection-target-class>
    com.foo.Bar.class
</injection-target-class>
<injection-target-name>
    baz
</injection-target-name>
<injection-target-class>
    com.foo.Bar2.class
</injection-target-class>
<injection-target-name>
    baz2
</injection-target-name>
</injection-target>

...
</resource-ref>

```

The `<injection-target>` from fragment 1 and 2 will be merged into the main `web.xml`

- k. If the main `web.xml` does not have any `<post-construct>` element specified and web-fragments have specified `<post-construct>` then the `<post-construct>` elements from the fragments will be merged into the main `web.xml`. However if in the main `web.xml` at least one `<post-construct>` element is specified then the `<post-construct>` elements from the fragment will not be merged. It is the responsibility of the author of the `web.xml` to make sure that the `<post-construct>` list is complete.
- l. If the main `web.xml` does not have any `<pre-destroy>` element specified and web-fragments have specified `<pre-destroy>` then the `<pre-destroy>` elements from the fragments will be merged into the main `web.xml`. However if in the main `web.xml` at least one `<pre-destroy>` element is specified then the `<pre-destroy>` elements from the fragment will not be merged. It is the responsibility of the author of the `web.xml` to make sure that the `<pre-destroy>` list is complete.
- m. After processing the `web-fragment.xml`, annotations from the corresponding fragment are processed to complete the effective metadata for the fragment before processing the next fragment. The following rules are used for processing annotations:

- n. Any metadata specified via an annotation that isn't already present in the descriptor will be used to augment the effective descriptor.
 - i. Configuration specified in the main `web.xml` or a web fragment takes precedence over the configuration specified via annotations.
 - ii. For a servlet defined via the `@WebServlet` annotation, to override values via the descriptor, the name of the servlet in the descriptor MUST match the name of the servlet specified via the annotation (explicitly specified or the default name, if one is not specified via the annotation).
 - iii. Init params for servlets and filters defined via annotations, will be overridden in the descriptor if the name of the init param exactly matches the name specified via the annotation. Init params are additive between the annotations and descriptors.
 - iv. `url-patterns`, when specified in a descriptor for a given servlet name overrides the url patterns specified via the annotation.
 - v. For a filter defined via the `@WebFilter` annotation, to override values via the descriptor, the name of the filter in the descriptor MUST match the name of the filter specified via the annotation (explicitly specified or the default name, if one is not specified via the annotation).
 - vi. `url-patterns` to which a filter is applied, when specified in a descriptor for a given filter name overrides the url patterns specified via the annotation.
 - vii. `DispatcherTypes` to which a filter applies, when specified in a descriptor for a given filter name overrides the `DispatcherTypes` specified via the annotation.
 - viii. The following examples demonstrates some of the above rules -

A Servlet declared via an annotation and packaged with the corresponding `web.xml` in the descriptor

```
@WebServlet(urlPatterns="/MyPattern", initParams=
  {@WebInitParam(name="ccc", value="333")})
public class com.acme.Foo extends HttpServlet
{
  ...
}
```

```
web.xml
<servlet>
```

```

    <servlet-class>com.acme.Foo</servlet-class>
    <servlet-name>Foo</servlet-name>
    <init-param>
        <param-name>aaa</param-name>
        <param-value>111</param-value>
    </init-param>
</servlet>

<servlet>
    <servlet-class>com.acme.Foo</servlet-class>
    <servlet-name>Fum</servlet-name>
    <init-param>
        <param-name>bbb</param-name>
        <param-value>222</param-value>
    </init-param>
</servlet>

<servlet-mapping>
    <servlet-name>Foo</servlet-name>
    <url-pattern>/foo/*</url-pattern>
</servlet-mapping>
<servlet-mapping>
    <servlet-name>Fum</servlet-name>
    <url-pattern>/fum/*</url-pattern>
</servlet-mapping>

```

Since the name of the servlet declared via the annotation does not match the name of the servlet declared in the `web.xml`, the annotation specifies a new servlet declaration in addition to the other declarations in `web.xml` and is equivalent to:

```

<servlet>
    <servlet-class>com.acme.Foo</servlet-class>
    <servlet-name>com.acme.Foo</servlet-name>
    <init-param>
        <param-name>ccc</param-name>
        <param-value>333</param-name>

```

```
</servlet>
```

If the above web.xml were replaced with the following

```
<servlet>  
  <servlet-class>com.acme.Foo</servlet-class>  
  <servlet-name>com.acme.Foo</servlet-name>  
  <init-param>  
    <param-name>aaa</param-name>  
    <param-value>111</param-value>  
  </init-param>  
</servlet>
```

```
<servlet-mapping>  
  <servlet-name>com.acme.Foo</servlet-name>  
  <url-pattern>/foo/*</url-pattern>  
</servlet-mapping>
```

Then the effective descriptor would be equivalent to <servlet>

```
<servlet-class>com.acme.Foo</servlet-class>  
<servlet-name>com.acme.Foo</servlet-name>  
<init-param>  
  <param-name>aaa</param-name>  
  <param-value>111</param-value>  
</init-param>  
<init-param>  
  <param-name>ccc</param-name>  
  <param-value>333</param-value>  
</init-param>  
</servlet>
```

```
<servlet-mapping>  
  <servlet-name>com.acme.Foo</servlet-name>  
  <url-pattern>/foo/*</url-pattern>  
</servlet-mapping>
```

8.2.4 Shared libraries / runtimes pluggability

In addition to supporting fragments and use of annotations one of the requirements is that not only we be able to plug-in things that are bundled in the `WEB-INF/lib` but also plugin shared copies of frameworks - including being able to plug-in to the web container things like JAX-WS, JAX-RS and JSF that build on top of the web container. The `ServletContainerInitializer` allows handling such a use case as described below.

An instance of the `ServletContainerInitializer` is looked up via the jar services API by the container at container / application startup time. The framework providing an implementation of the `ServletContainerInitializer` MUST bundle in the `META-INF/services` directory of the jar file a file called `javax.servlet.ServletContainerInitializer`, as per the jar services API, that points to the implementation class of the `ServletContainerInitializer`.

In addition to the `ServletContainerInitializer` we also have an annotation - `HandlesTypes`. The `HandlesTypes` annotation on the implementation of the `ServletContainerInitializer` is used to express interest in classes that may have annotations (type, method or field level annotations) specified in the value of the `HandlesTypes` or if it extends / implements one those classes anywhere in the class' super types. The container uses the `HandlesTypes` annotation to determine when to invoke the initializer's `onStartup` method. When examining the classes of an application to see if they match any of the criteria specified by the `HandlesTypes` annotation of a `ServletContainerInitializer`, the container may run into class loading problems if one or more of the application's optional JAR files are missing. Since the container is not in a position to decide whether these types of class loading failures will prevent the application from working correctly, it must ignore them, while at the same time providing a configuration option that would log them.

If an implementation of `ServletContainerInitializer` does not have the `@HandlesTypes` annotation, or if there are no matches to any of the `HandlesType` specified, then it will get invoked once for every application with `null` as the value of the `Set`. This will allow for the initializer to determine based on the resources available in the application whether it needs to initialize a servlet / filter or not.

The `onStartup` method of the `ServletContainerInitializer` will be invoked when the application is coming up before any of the listener's events are fired.

The `ServletContainerInitializer`'s `onStartup` method get's a `Set of Classes` that either extend / implement the classes that the initializer expressed interest in or if it is annotated with any of the classes specified via the `@HandlesTypes` annotation.

A concrete example below showcases how this would work.

Let's take the JAX-WS web services runtime.

The implementation of JAX-WS runtime isn't typically bundled in each and every war file. The implementation would bundle an implementation of the `ServletContainerInitializer` (shown below) and the container would look that up using the services API (the jar file will bundle in its `META-INF/services` directory a file called `javax.servlet.ServletContainerInitializer` that will point to the `JAXWSServletContainerInitializer` shown below).

```
@HandlesTypes(WebService.class)
JAXWSServletContainerInitializer
    implements ServletContainerInitializer
{
    public void onStartup(Set<Class<?>> c, ServletContext ctx)
        throws ServletException {
        // JAX-WS specific code here to initialize the runtime
        // and setup the mapping etc.

        ServletRegistration reg = ctx.addServlet("JAXWSServlet",
"com.sun.webservice.JAXWSServlet");
        reg.addServletMapping("/foo");
    }
}
```

The framework jar file can also be bundled in `WEB-INF/lib` directory of the war file. If the `ServletContainerInitializer` is bundled in a JAR file inside the `WEB-INF/lib` directory of an application, its `onStartup` method will be invoked only once during the startup of the bundling application. If, on the other hand, the `ServletContainerInitializer` is bundled in a JAR file outside of the `WEB-INF/lib` directory, but still discoverable by the runtime's service provider lookup mechanism, its `onStartup` method will be invoked every time an application is started.

Implementations of the `ServletContainerInitializer` interface will be discovered by the runtime's service lookup mechanism or a container specific mechanism that is semantically equivalent to it. In either case, `ServletContainerInitializer` services from web fragment JAR files that are excluded from an absolute ordering MUST be ignored, and the order in which these services are discovered MUST follow the application's class loading delegation model.

8.3 JSP container pluggability

The `ServletContainerInitializer` and programmatic registration features make it possible to provide a clear separation of responsibilities between the Servlet and JSP containers, by making the Servlet container responsible for parsing only `web.xml` and `web-fragment.xml` resources, and delegating the parsing of Tag Library Descriptor (TLD) resources to the JSP container.

Previously, a web container had to scan TLD resources for any listener declarations. With Servlet 3.0, this responsibility may be delegated to the JSP container. A JSP container that is embedded in a Servlet 3.0 compliant Servlet container may provide its own `ServletContainerInitializer` implementation, search the `ServletContext` passed to its `onStartup` method for any TLD resources, scan those resources for listener declarations, and register the corresponding listeners with the `ServletContext`.

In addition, prior to Servlet 3.0, a JSP container used to have to scan an application's deployment descriptor for any `jsp-config` related configuration. With Servlet 3.0, the Servlet container must make available, via the `ServletContext.getJspConfigDescriptor` method, any `jsp-config` related configuration from the application's `web.xml` and `web-fragment.xml` deployment descriptors.

Any `ServletContextListeners` that were discovered in a TLD and registered programmatically are limited in the functionality they provide. Any attempt to call a `ServletContext` API method on them that was added in Servlet 3.0 will result in an `UnsupportedOperationException`.

In addition, a Servlet 3.0 compliant Servlet container must provide a `ServletContext` attribute with name `javax.servlet.context.orderedLibs`, whose value (of type `java.util.List<java.lang.String>`) contains the list of names of JAR files in the `WEB-INF/lib` directory of the application represented by the `ServletContext`, ordered by their web fragment names (with possible exclusions if fragment JAR files have been excluded from `absolute-ordering`), or `null` if the application does not specify any absolute or relative ordering.

8.4 Processing annotations and fragments

Web applications can include both annotations and the `web.xml` / `web-fragment.xml` deployment descriptors. If there is no deployment descriptor, or there is one but does not have the `metadata-complete` set to `true`, `web.xml`, `web-`

`fragment.xml` and annotations if used in the application must be processed. The following table describes whether or not to process annotations and `web.xml` fragments.

TABLE 8-1 Annotations and web fragment processing requirements

Deployment descriptor	metadata-complete	process annotations and web fragments
web.xml 2.5	Yes	No
web.xml 2.5	no	yes
web.xml 3.0	yes	no
web.xml 3.0	no	yes

Dispatching Requests

When building a Web application, it is often useful to forward processing of a request to another servlet, or to include the output of another servlet in the response. The `RequestDispatcher` interface provides a mechanism to accomplish this.

When asynchronous processing is enabled on the request, the `AsyncContext` allows a user to dispatch the request back to the servlet container.

9.1 Obtaining a RequestDispatcher

An object implementing the `RequestDispatcher` interface may be obtained from the `ServletContext` via the following methods:

- `getRequestDispatcher`
- `getNamedDispatcher`

The `getRequestDispatcher` method takes a `String` argument describing a path within the scope of the `ServletContext`. This path must be relative to the root of the `ServletContext` and begin with a `'/'`, or be empty. The method uses the path to look up a servlet, using the servlet path matching rules in Chapter 12, “Mapping Requests to Servlets”, wraps it with a `RequestDispatcher` object, and returns the resulting object. If no servlet can be resolved based on the given path, a `RequestDispatcher` is provided that returns the content for that path.

The `getNamedDispatcher` method takes a `String` argument indicating the name of a servlet known to the `ServletContext`. If a servlet is found, it is wrapped with a `RequestDispatcher` object and the object is returned. If no servlet is associated with the given name, the method must return `null`.

To allow `RequestDispatcher` objects to be obtained using relative paths that are relative to the path of the current request (not relative to the root of the `ServletContext`), the `getRequestDispatcher` method is provided in the `ServletRequest` interface.

The behavior of this method is similar to the method of the same name in the `ServletContext`. The servlet container uses information in the request object to transform the given relative path against the current servlet to a complete path. For example, in a context rooted at `'/'` and a request to `/garden/tools.html`, a request dispatcher obtained via `ServletRequest.getRequestDispatcher("header.html")` will behave exactly like a call to `ServletContext.getRequestDispatcher("/garden/header.html")`.

9.1.1 Query Strings in Request Dispatcher Paths

The `ServletContext` and `ServletRequest` methods that create `RequestDispatcher` objects using path information allow the optional attachment of query string information to the path. For example, a Developer may obtain a `RequestDispatcher` by using the following code:

```
String path = "/raisins.jsp?orderno=5";
RequestDispatcher rd = context.getRequestDispatcher(path);
rd.include(request, response);
```

Parameters specified in the query string used to create the `RequestDispatcher` take precedence over other parameters of the same name passed to the included servlet. The parameters associated with a `RequestDispatcher` are scoped to apply only for the duration of the `include` or `forward` call.

9.2 Using a Request Dispatcher

To use a request dispatcher, a servlet calls either the `include` method or `forward` method of the `RequestDispatcher` interface. The parameters to these methods can be either the `request` and `response` arguments that were passed in via the `service` method of the `javax.servlet.Servlet` interface, or instances of subclasses of the request and response wrapper classes that were introduced for version 2.3 of the specification. In the latter case, the wrapper instances must wrap the request or response objects that the container passed into the `service` method.

The Container Provider should ensure that the dispatch of the request to a target servlet occurs in the same thread of the same JVM as the original request.

9.3 The Include Method

The `include` method of the `RequestDispatcher` interface may be called at any time. The target servlet of the `include` method has access to all aspects of the request object, but its use of the response object is more limited.

It can only write information to the `ServletOutputStream` or `Writer` of the response object and commit a response by writing content past the end of the response buffer, or by explicitly calling the `flushBuffer` method of the `ServletResponse` interface. It cannot set headers or call any method that affects the headers of the response, with the exception of the `HttpServletRequest.getSession()` and `HttpServletRequest.getSession(boolean)` methods. Any attempt to set the headers must be ignored, and any call to `HttpServletRequest.getSession()` or `HttpServletRequest.getSession(boolean)` that would require adding a `Cookie` response header must throw an `IllegalStateException` if the response has been committed.

If the default servlet is the target of a `RequestDispatcher.include()` and the requested resource does not exist, then the default servlet **MUST** throw `FileNotFoundException`. If the exception isn't caught and handled, and the response hasn't been committed, the status code **MUST** be set to 500.

9.3.1 Included Request Parameters

Except for servlets obtained by using the `getNamedDispatcher` method, a servlet that has been invoked by another servlet using the `include` method of `RequestDispatcher` has access to the path by which it was invoked.

The following request attributes must be set:

```
javax.servlet.include.request_uri
javax.servlet.include.context_path
javax.servlet.include.servlet_path
javax.servlet.include.path_info
javax.servlet.include.query_string
```

These attributes are accessible from the included servlet via the `getAttribute` method on the request object and their values must be equal to the request URI, context path, servlet path, path info, and query string of the included servlet, respectively. If the request is subsequently included, these attributes are replaced for that include.

If the included servlet was obtained by using the `getNamedDispatcher` method, these attributes must not be set.

9.4 The Forward Method

The `forward` method of the `RequestDispatcher` interface may be called by the calling servlet only when no output has been committed to the client. If output data exists in the response buffer that has not been committed, the content must be cleared before the target servlet's `service` method is called. If the response has been committed, an `IllegalStateException` must be thrown.

The path elements of the request object exposed to the target servlet must reflect the path used to obtain the `RequestDispatcher`.

The only exception to this is if the `RequestDispatcher` was obtained via the `getNamedDispatcher` method. In this case, the path elements of the request object must reflect those of the original request.

Before the `forward` method of the `RequestDispatcher` interface returns without exception, the response content must be sent and committed, and closed by the servlet container, unless the request was put into the asynchronous mode. If an error occurs in the target of the `RequestDispatcher.forward()` the exception may be propagated back through all the calling filters and servlets and eventually back to the container

9.4.1 Query String

The request dispatching mechanism is responsible for aggregating query string parameters when forwarding or including requests.

9.4.2 Forwarded Request Parameters

Except for servlets obtained by using the `getNamedDispatcher` method, a servlet that has been invoked by another servlet using the `forward` method of `RequestDispatcher` has access to the path of the original request.

The following request attributes must be set:

```
javax.servlet.forward.request_uri
javax.servlet.forward.context_path
javax.servlet.forward.servlet_path
javax.servlet.forward.path_info
javax.servlet.forward.query_string
```

The values of these attributes must be equal to the return values of the `HttpServletRequest` methods `getRequestURI`, `getContextPath`, `getServletPath`, `getPathInfo`, `getQueryString` respectively, invoked on the request object passed to the first servlet object in the call chain that received the request from the client.

These attributes are accessible from the forwarded servlet via the `getAttribute` method on the request object. Note that these attributes must always reflect the information in the original request even under the situation that multiple forwards and subsequent includes are called.

If the forwarded servlet was obtained by using the `getNamedDispatcher` method, these attributes must not be set.

9.5 Error Handling

If the servlet that is the target of a request dispatcher throws a runtime exception or a checked exception of type `ServletException` or `IOException`, it should be propagated to the calling servlet. All other exceptions should be wrapped as `ServletExceptions` and the root cause of the exception set to the original exception, as it should not be propagated.

9.6 Obtaining an `AsyncContext`

An object implementing the `AsyncContext` interface may be obtained from the `ServletRequest` via one of `startAsync` methods. Once you have an `AsyncContext`, you can use it to either complete the processing of the request via the `complete()` method or use one of the `dispatch` methods described below.

9.7 The Dispatch Method

The following methods can be used to dispatch requests from the `AsyncContext`:

- `dispatch(path)`

The `dispatch` method takes a `String` argument describing a path within the scope of the `ServletContext`. This path must be relative to the root of the `ServletContext` and begin with a `'/'`.

- `dispatch(servletContext, path)`

The `dispatch` method takes a `String` argument describing a path within the scope of the `ServletContext` specified. This path must be relative to the root of the `ServletContext` specified and begin with a `'/'`.

- `dispatch()`

The `dispatch` method takes no argument. It uses the original URI as the path. If the `AsyncContext` was initialized via the `startAsync(ServletRequest, ServletResponse)` and the request passed is an instance of `HttpServletRequest`, then the dispatch is to the URI returned by `HttpServletRequest.getRequestURI()`. Otherwise the dispatch is to the URI of the request when it was last dispatched by the container

One of the `dispatch` methods of the `AsyncContext` interface may be called by the application waiting for the asynchronous event to happen. If `complete()` has been called on the `AsyncContext`, an `IllegalStateException` must be thrown. All the variations of the `dispatch` methods returns immediately and do not commit the response.

The path elements of the request object exposed to the target servlet must reflect the path specified in the `AsyncContext.dispatch`.

9.7.1 Query String

The request dispatching mechanism is responsible for aggregating query string parameters when dispatching requests.

9.7.2 Dispatched Request Parameters

A servlet that has been invoked by using the `dispatch` method of `AsyncContext` has access to the path of the original request.

The following request attributes must be set:

```
javax.servlet.async.request_uri  
javax.servlet.async.context_path  
javax.servlet.async.servlet_path  
javax.servlet.async.path_info  
javax.servlet.async.query_string
```

The values of these attributes must be equal to the return values of the `HttpServletRequest` methods `getRequestURI`, `getContextPath`, `getServletPath`, `getPathInfo`, `getQueryString` respectively, invoked on the request object passed to the first servlet object in the call chain that received the request from the client.

These attributes are accessible from the dispatched servlet via the `getAttribute` method on the request object. Note that these attributes must always reflect the information in the original request even under the situation that multiple dispatches are called.

Web Applications

A Web application is a collection of servlets, HTML pages, classes, and other resources that make up a complete application on a Web server. The Web application can be bundled and run on multiple containers from multiple vendors.

10.1 Web Applications Within Web Servers

A Web application is rooted at a specific path within a Web server. For example, a catalog application could be located at `http://www.mycorp.com/catalog`. All requests that start with this prefix will be routed to the `ServletContext` which represents the catalog application.

A servlet container can establish rules for automatic generation of Web applications. For example a `~user/` mapping could be used to map to a Web application based at `/home/user/public_html/`.

By default, an instance of a Web application must run on one VM at any one time. This behavior can be overridden if the application is marked as “distributable” via its deployment descriptor. An application marked as distributable must obey a more restrictive set of rules than is required of a normal Web application. These rules are set out throughout this specification.

10.2 Relationship to ServletContext

The servlet container must enforce a one to one correspondence between a Web application and a `ServletContext`. A `ServletContext` object provides a servlet with its view of the application.

10.3 Elements of a Web Application

A Web application may consist of the following items:

- Servlets
- JSP™ Pages¹
- Utility Classes
- Static documents (HTML, images, sounds, etc.)
- Client side Java applets, beans, and classes
- Descriptive meta information that ties all of the above elements together

10.4 Deployment Hierarchies

This specification defines a hierarchical structure used for deployment and packaging purposes that can exist in an open file system, in an archive file, or in some other form. It is recommended, but not required, that servlet containers support this structure as a runtime representation.

10.5 Directory Structure

A Web application exists as a structured hierarchy of directories. The root of this hierarchy serves as the document root for files that are part of the application. For example, for a Web application with the context path `/catalog` in a Web container, the `index.html` file at the base of the Web application hierarchy or in a JAR file inside `WEB-INF/lib` that includes the `index.html` under `META-INF/resources` directory can be served to satisfy a request from `/catalog/index.html`. If an `index.html` is present both in the root context and in the `META-INF/resources` directory of a JAR file in the `WEB-INF/lib` directory of the application, then the file that is available in the root context **MUST** be used. The rules for matching URLs to context path are laid out in Chapter 12, “Mapping Requests to Servlets”. Since the context path of an application determines the URL namespace of the contents of the Web application, Web containers must reject Web applications defining a context path that could cause potential conflicts in this URL namespace. This may occur, for example, by attempting to deploy a second Web application with the same context

1. See the JavaServer Pages specification available from <http://java.sun.com/products/jsp>.

path. Since requests are matched to resources in a case-sensitive manner, this determination of potential conflict must be performed in a case-sensitive manner as well.

A special directory exists within the application hierarchy named “WEB-INF”. This directory contains all things related to the application that aren’t in the document root of the application. Most of the WEB-INF node is not part of the public document tree of the application. Except for static resources and JSPs packaged in the META-INF/resources of a JAR file that resides in the WEB-INF/lib directory, no other files contained in the WEB-INF directory may be served directly to a client by the container. However, the contents of the WEB-INF directory are visible to servlet code using the `getResource` and `getResourceAsStream` method calls on the `ServletContext`, and may be exposed using the `RequestDispatcher` calls. Hence, if the Application Developer needs access, from servlet code, to application specific configuration information that he does not wish to be exposed directly to the Web client, he may place it under this directory. Since requests are matched to resource mappings in a case-sensitive manner, client requests for `’/WEB-INF/foo’`, `’/WEB-INF/foo’`, for example, should not result in contents of the Web application located under `’/WEB-INF’` being returned, nor any form of directory listing thereof.

The contents of the WEB-INF directory are:

- The `’/WEB-INF/web.xml’` deployment descriptor.
- The `’/WEB-INF/classes/’` directory for servlet and utility classes. The classes in this directory must be available to the application class loader.
- The `’/WEB-INF/lib/*.jar’` area for Java ARchive files. These files contain servlets, beans, static resources and JSPs packaged in a JAR file and other utility classes useful to the Web application. The Web application class loader must be able to load classes from any of these archive files.

The Web application class loader must load classes from the `WEB-INF/classes` directory first, and then from library JARs in the `WEB-INF/lib` directory. Also, except for the case where static resources are packaged in JAR files, any requests from the client to access the resources in `WEB-INF/` directory must be returned with a `SC_NOT_FOUND(404)` response.

10.5.1 Example of Application Directory Structure

The following is a listing of all the files in a sample Web application:

```
/index.html
/howto.jsp
/feedback.jsp
/images/banner.gif
/images/jumping.gif
/WEB-INF/web.xml
/WEB-INF/lib/jspbean.jar
/WEB-INF/lib/catalog.jar!/META-
INF/resources/catalog/moreOffers/books.html
/WEB-INF/classes/com/mycorp/servlets/MyServlet.class
/WEB-INF/classes/com/mycorp/util/MyUtils.class
```

10.6 Web Application Archive File

Web applications can be packaged and signed into a Web ARchive format (WAR) file using the standard Java archive tools. For example, an application for issue tracking might be distributed in an archive file called `issuetrack.war`.

When packaged into such a form, a `META-INF` directory will be present which contains information useful to Java archive tools. This directory must not be directly served as content by the container in response to a Web client's request, though its contents are visible to servlet code via the `getResource` and `getResourceAsStream` calls on the `ServletContext`. Also, any requests to access the resources in `META-INF` directory must be returned with a `SC_NOT_FOUND(404)` response.

10.7 Web Application Deployment Descriptor

The Web application deployment descriptor (see Chapter 14, "Deployment Descriptor") includes the following types of configuration and deployment information:

- `ServletContext` Init Parameters
- Session Configuration
- Servlet/JSP Definitions
- Servlet/JSP Mappings

- MIME Type Mappings
- Welcome File list
- Error Pages
- Security

10.7.1 Dependencies On Extensions

When a number of applications make use of the same code or resources, they will typically be installed as library files in the container. These files are often common or standard APIs that can be used without sacrificing portability. Files used only by one or a few applications will be made available for access as part of the Web application. The container must provide a directory for these libraries. The files placed within this directory must be available across all Web applications. The location of this directory is container-specific. The class loader the servlet container uses for loading these library files must be the same for all Web applications within the same JVM. This class loader instance must be somewhere in the chain of parent class loaders of the Web application class loader.

Application developers need to know what extensions are installed on a Web container, and containers need to know what dependencies servlets in a WAR have on such libraries in order to preserve portability.

The application developer depending on such an extension or extensions must provide a `META-INF/MANIFEST.MF` entry in the WAR file listing all extensions needed by the WAR. The format of the manifest entry should follow standard JAR manifest format. During deployment of the Web application, the Web container must make the correct versions of the extensions available to the application following the rules defined by the *Optional Package Versioning* mechanism (<http://java.sun.com/j2se/1.4/docs/guide/extensions/>).

Web containers must also be able to recognize declared dependencies expressed in the manifest entry of any of the library JARs under the `WEB-INF/lib` entry in a WAR.

If a Web container is not able to satisfy the dependencies declared in this manner, it should reject the application with an informative error message.

10.7.2 Web Application Class Loader

The class loader that a container uses to load a servlet in a WAR must allow the developer to load any resources contained in library JARs within the WAR following normal Java SE semantics using `getResource`. As described in the Java EE license agreement, servlet containers that are not part of a Java EE product should not allow the application to override Java SE platform classes, such as those in the `java.*` and `javax.*` namespaces, that Java SE does not allow to be modified. The container

should not allow applications to override or access the container's implementation classes. It is recommended also that the application class loader be implemented so that classes and resources packaged within the WAR are loaded in preference to classes and resources residing in container-wide library JARs. An implementation MUST also guarantee that for every web application deployed in a container, a call to `Thread.currentThread().getContextClassLoader()` MUST return a `ClassLoader` instance that implements the contract specified in this section. Furthermore, the `ClassLoader` instance MUST be a separate instance for each deployed web application. The container is required to set the thread context `ClassLoader` as described above before making any callbacks (including listener callbacks) into the web application, and set it back to the original `ClassLoader`, once the callback returns.

10.8 Replacing a Web Application

A server should be able to replace an application with a new version without restarting the container. When an application is replaced, the container should provide a robust method for preserving session data within that application.

10.9 Error Handling

10.9.1 Request Attributes

A Web application must be able to specify that when errors occur, other resources in the application are used to provide the content body of the error response. The specification of these resources is done in the deployment descriptor.

If the location of the error handler is a servlet or a JSP page:

- The original unwrapped request and response objects created by the container are passed to the servlet or JSP page.
- The request path and attributes are set as if a `RequestDispatcher.forward` to the error resource had been performed.

- The request attributes in TABLE 10-1 must be set.

TABLE 10-1 Request Attributes and their types

Request Attributes	Type
<code>javax.servlet.error.status_code</code>	<code>java.lang.Integer</code>
<code>javax.servlet.error.exception_type</code>	<code>java.lang.Class</code>
<code>javax.servlet.error.message</code>	<code>java.lang.String</code>
<code>javax.servlet.error.exception</code>	<code>java.lang.Throwable</code>
<code>javax.servlet.error.request_uri</code>	<code>java.lang.String</code>
<code>javax.servlet.error.servlet_name</code>	<code>java.lang.String</code>

These attributes allow the servlet to generate specialized content depending on the status code, the exception type, the error message, the exception object propagated, and the URI of the request processed by the servlet in which the error occurred (as determined by the `getRequestURI` call), and the logical name of the servlet in which the error occurred.

With the introduction of the exception object to the attributes list for version 2.3 of this specification, the exception type and error message attributes are redundant. They are retained for backwards compatibility with earlier versions of the API.

10.9.2 Error Pages

To allow developers to customize the appearance of content returned to a Web client when a servlet generates an error, the deployment descriptor defines a list of error page descriptions. The syntax allows the configuration of resources to be returned by the container either when a servlet or filter calls `sendError` on the response for specific status codes, or if the servlet generates an exception or error that propagates to the container.

If the `sendError` method is called on the response, the container consults the list of error page declarations for the Web application that use the status-code syntax and attempts a match. If there is a match, the container returns the resource as indicated by the location entry.

A servlet or filter may throw the following exceptions during processing of a request:

- `runtime` exceptions or errors
- `ServletExceptions` or subclasses thereof
- `IOExceptions` or subclasses thereof

The Web application may have declared error pages using the `exception-type` element. In this case the container matches the exception type by comparing the exception thrown with the list of error-page definitions that use the `exception-type` element. A match results in the container returning the resource indicated in the location entry. The closest match in the class hierarchy wins.

If no `error-page` declaration containing an `exception-type` fits using the class-hierarchy match, and the exception thrown is a `ServletException` or subclass thereof, the container extracts the wrapped exception, as defined by the `ServletException.getRootCause` method. A second pass is made over the error page declarations, again attempting the match against the error page declarations, but using the wrapped exception instead.

Error-page declarations using the `exception-type` element in the deployment descriptor must be unique up to the class name of the exception-type. Similarly, error-page declarations using the `status-code` element must be unique in the deployment descriptor up to the status code.

The error page mechanism described does not intervene when errors occur when invoked using the `RequestDispatcher` or `filter.doFilter` method. In this way, a filter or servlet using the `RequestDispatcher` has the opportunity to handle errors generated.

If a servlet generates an error that is not handled by the error page mechanism as described above, the container must ensure to send a response with status 500.

The default servlet and container will use the `sendError` method to send 4xx and 5xx status responses, so that the error mechanism may be invoked. The default servlet and container will use the `setStatus` method for 2xx and 3xx responses and will not invoke the error page mechanism.

If the application is using asynchronous operations as described in Section 2.3.3.3, “Asynchronous processing” on page 2-10, it is the application’s responsibility to handle all errors in application created threads. The container MAY take care of the errors from the thread issued via `AsyncContext.start`. For handling errors that occur during `AsyncContext.dispatch` see Section n, “Any errors or exceptions that may occur during the execution of the `dispatch` methods MUST be caught and handled by the container as follows:” on page 2-16

10.9.3 Error Filters

The error page mechanism operates on the original unwrapped/unfiltered request and response objects created by the container. The mechanism described in Section 6.2.5, “Filters and the `RequestDispatcher`” may be used to specify filters that are applied before an error response is generated.

10.10 Welcome Files

Web Application developers can define an ordered list of partial URIs called welcome files in the Web application deployment descriptor. The deployment descriptor syntax for the list is described in the Web application deployment descriptor schema.

The purpose of this mechanism is to allow the deployer to specify an ordered list of partial URIs for the container to use for appending to URIs when there is a request for a URI that corresponds to a directory entry in the WAR not mapped to a Web component. This kind of request is known as a valid partial request.

The use for this facility is made clear by the following common example: A welcome file of `index.html` can be defined so that a request to a URL like `host:port/webapp/directory/`, where `directory` is an entry in the WAR that is not mapped to a servlet or JSP page, is returned to the client as `host:port/webapp/directory/index.html`.

If a Web container receives a valid partial request, the Web container must examine the welcome file list defined in the deployment descriptor. The welcome file list is an ordered list of partial URLs with no trailing or leading `/`. The Web server must append each welcome file in the order specified in the deployment descriptor to the partial request and check whether a static resource in the WAR is mapped to that request URI. If no match is found, the Web server **MUST** again append each welcome file in the order specified in the deployment descriptor to the partial request and check if a servlet is mapped to that request URI. The Web container must send the request to the first resource in the WAR that matches. The container may send the request to the welcome resource with a forward, a redirect, or a container specific mechanism that is indistinguishable from a direct request.

If no matching welcome file is found in the manner described, the container may handle the request in a manner it finds suitable. For some configurations this may mean returning a directory listing or for others returning a 404 response.

Consider a Web application where:

- The deployment descriptor lists the following welcome files.

```
<welcome-file-list>
  <welcome-file>index.html</welcome-file>
  <welcome-file>default.jsp</welcome-file>
</welcome-file-list>
```

- The static content in the WAR is as follows

```
/foo/index.html
/foo/default.jsp
/foo/orderform.html
/foo/home.gif
/catalog/default.jsp
/catalog/products/shop.jsp
/catalog/products/register.jsp
```

- A request URI of `/foo` will be redirected to a URI of `/foo/`.
- A request URI of `/foo/` will be returned as `/foo/index.html`.
- A request URI of `/catalog` will be redirected to a URI of `/catalog/`.
- A request URI of `/catalog/` will be returned as `/catalog/default.jsp`.
- A request URI of `/catalog/index.html` will cause a 404 not found
- A request URI of `/catalog/products` will be redirected to a URI of `/catalog/products/`.
- A request URI of `/catalog/products/` will be passed to the “default” servlet, if any. If no “default” servlet is mapped, the request may cause a 404 not found, may cause a directory listing including `shop.jsp` and `register.jsp`, or may cause other behavior defined by the container. See Section 12.2, “Specification of Mappings” for the definition of “default” servlet.
- All of the above static content can also be packaged in a JAR file with the content listed above packaged in the `META-INF/resources` directory of the jar file. The JAR file can then be included in the `WEB-INF/lib` directory of the web application.

10.11 Web Application Environment

Servlet containers that are not part of a Java EE technology-compliant implementation are encouraged, but not required, to implement the application environment functionality described in Section 15.2.2, “Web Application Environment and the Java EE specification. If they do not implement the facilities required to support this environment, upon deploying an application that relies on them, the container should provide a warning.

10.12 Web Application Deployment

When a web application is deployed into a container, the following steps must be performed, in this order, before the web application begins processing client requests.

- Instantiate an instance of each event listener identified by a `<listener>` element in the deployment descriptor.
- For instantiated listener instances that implement `ServletContextListener`, call the `contextInitialized()` method.
- Instantiate an instance of each filter identified by a `<filter>` element in the deployment descriptor and call each filter instance's `init()` method.
- Instantiate an instance of each servlet identified by a `<servlet>` element that includes a `<load-on-startup>` element in the order defined by the `load-on-startup` element values, and call each servlet instance's `init()` method.

10.13 Inclusion of a web.xml Deployment Descriptor

A web application is NOT required to contain a `web.xml` if it does NOT contain any Servlet, Filter, or Listener components or is using annotations to declare the same. In other words an application containing only static files or JSP pages does not require a `web.xml` to be present.

Application Lifecycle Events

11.1 Introduction

The application events facility gives the Web Application Developer greater control over the lifecycle of the `ServletContext` and `HttpSession` and `ServletRequest`, allows for better code factorization, and increases efficiency in managing the resources that the Web application uses.

11.2 Event Listeners

Application event listeners are classes that implement one or more of the servlet event listener interfaces. They are instantiated and registered in the Web container at the time of the deployment of the Web application. They are provided by the Developer in the WAR.

Servlet event listeners support event notifications for state changes in the `ServletContext`, `HttpSession` and `ServletRequest` objects. Servlet context listeners are used to manage resources or state held at a JVM level for the application. HTTP session listeners are used to manage state or resources associated with a series of requests made into a Web application from the same client or user. Servlet request listeners are used to manage state across the lifecycle of servlet requests. Async listeners are used to manage async events such as time outs and completion of async processing.

There may be multiple listener classes listening to each event type, and the Developer may specify the order in which the container invokes the listener beans for each event type.

11.2.1 Event Types and Listener Interfaces

Events types and the listener interfaces used to monitor them are shown in the following tables:

TABLE 11-1 Servlet Context Events

Event Type	Description	Listener Interface
Lifecycle	The servlet context has just been created and is available to service its first request, or the servlet context is about to be shut down.	<code>javax.servlet. ServletContextListener</code>
Changes to attributes	Attributes on the servlet context have been added, removed, or replaced.	<code>javax.servlet. ServletContextAttributeListe ner</code>

TABLE 11-2 HTTP Session Events

Event Type	Description	Listener Interface
Lifecycle	An <code>HttpSession</code> has been created, invalidated, or timed out.	<code>javax.servlet.http. HttpSessionListener</code>
Changes to attributes	Attributes have been added, removed, or replaced on an <code>HttpSession</code> .	<code>javax.servlet.http HttpSessionAttributeListener</code>
Session migration	<code>HttpSession</code> has been activated or passivated.	<code>javax.servlet.http HttpSessionActivationListener</code>
Object binding	Object has been bound to or unbound from <code>HttpSession</code>	<code>javax.servlet.http HttpSessionBindingListener</code>

TABLE 11-3 Servlet Request Events

Event Type	Description	Listener Interface
Lifecycle	A servlet request has started being processed by Web components.	<code>javax.servlet. ServletRequestListener</code>
Changes to attributes	Attributes have been added, removed, or replaced on a <code>ServletRequest</code> .	<code>javax.servlet. ServletRequestAttributeListe ner</code>
Async events	A timeout, connection termination or completion of async processing	<code>javax.servlet.AsyncListener</code>

For details of the API, refer to the API reference.

11.2.2 An Example of Listener Use

To illustrate a use of the event scheme, consider a simple Web application containing a number of servlets that make use of a database. The Developer has provided a servlet context listener class for management of the database connection.

1. When the application starts up, the listener class is notified. The application logs on to the database, and stores the connection in the servlet context.
2. Servlets in the application access the connection as needed during activity in the Web application.
3. When the Web server is shut down, or the application is removed from the Web server, the listener class is notified and the database connection is closed.

11.3 Listener Class Configuration

11.3.1 Provision of Listener Classes

The Developer of the Web application provides listener classes implementing one or more of the listener interfaces in the `javax.servlet` API. Each listener class must have a public constructor taking no arguments. The listener classes are packaged into the WAR, either under the `WEB-INF/classes` archive entry, or inside a JAR in the `WEB-INF/lib` directory.

11.3.2 Deployment Declarations

Listener classes are declared in the Web application deployment descriptor using the `listener` element. They are listed by class name in the order in which they are to be invoked. Unlike other listeners, listeners of type `AsyncListener` may only be registered (with a `ServletRequest`) programmatically.

11.3.3 Listener Registration

The Web container creates an instance of each listener class and registers it for event notifications prior to the processing of the first request by the application. The Web container registers the listener instances according to the interfaces they implement and the order in which they appear in the deployment descriptor. During Web application execution, listeners are invoked in the order of their registration.

11.3.4 Notifications At Shutdown

On application shutdown, listeners are notified in reverse order to their declarations with notifications to session listeners preceding notifications to context listeners. Session listeners must be notified of session invalidations prior to context listeners being notified of application shutdown.

11.4 Deployment Descriptor Example

The following example is the deployment grammar for registering two servlet context lifecycle listeners and an `HttpSession` listener.

Suppose that `com.acme.MyConnectionManager` and `com.acme.MyLoggingModule` both implement `javax.servlet.ServletContextListener`, and that `com.acme.MyLoggingModule` additionally implements `javax.servlet.http.HttpSessionListener`. Also, the Developer wants

`com.acme.MyConnectionManager` to be notified of servlet context lifecycle events before `com.acme.MyLoggingModule`. Here is the deployment descriptor for this application:

```
<web-app>
  <display-name>MyListeningApplication</display-name>
  <listener>
    <listener-class>com.acme.MyConnectionManager</listener-
class>
  </listener>
  <listener>
    <listener-class>com.acme.MyLoggingModule</listener-class>
  </listener>
  <servlet>
    <display-name>RegistrationServlet</display-name>
    ...etc
  </servlet>
</web-app>
```

11.5 Listener Instances and Threading

The container is required to complete instantiation of the listener classes in a Web application prior to the start of execution of the first request into the application. The container must maintain a reference to each listener instance until the last request is serviced for the Web application.

Attribute changes to `ServletContext` and `HttpSession` objects may occur concurrently. The container is not required to synchronize the resulting notifications to attribute listener classes. Listener classes that maintain state are responsible for the integrity of the data and should handle this case explicitly.

11.6 Listener Exceptions

Application code inside a listener may throw an exception during operation. Some listener notifications occur under the call tree of another component in the application. An example of this is a servlet that sets a session attribute, where the session listener throws an unhandled exception. The container must allow unhandled exceptions to be handled by the error page mechanism described in

Section 10.9, “Error Handling”. If there is no error page specified for those exceptions, the container must ensure to send a response back with status 500. In this case no more listeners under that event are called.

Some exceptions do not occur under the call stack of another component in the application. An example of this is a `SessionListener` that receives a notification that a session has timed out and throws an unhandled exception, or of a `ServletContextListener` that throws an unhandled exception during a notification of servlet context initialization, or of a `ServletRequestListener` that throws an unhandled exception during a notification of the initialization or the destruction of the request object. In this case, the Developer has no opportunity to handle the exception. The container may respond to all subsequent requests to the Web application with an HTTP status code 500 to indicate an application error.

Developers wishing normal processing to occur after a listener generates an exception must handle their own exceptions within the notification methods.

11.7 Distributed Containers

In distributed Web containers, `HttpSession` instances are scoped to the particular JVM servicing session requests, and the `ServletContext` object is scoped to the Web container’s JVM. Distributed containers are not required to propagate either servlet context events or `HttpSession` events to other JVMs. Listener class instances are scoped to one per deployment descriptor declaration per JVM.

11.8 Session Events

Listener classes provide the Developer with a way of tracking sessions within a Web application. It is often useful in tracking sessions to know whether a session became invalid because the container timed out the session, or because a Web component within the application called the `invalidate` method. The distinction may be determined indirectly using listeners and the `HttpSession` API methods.

Mapping Requests to Servlets

The mapping techniques described in this chapter are required for Web containers mapping client requests to servlets.¹

12.1 Use of URL Paths

Upon receipt of a client request, the Web container determines the Web application to which to forward it. The Web application selected must have the longest context path that matches the start of the request URL. The matched part of the URL is the context path when mapping to servlets.

The Web container next must locate the servlet to process the request using the path mapping procedure described below.

The path used for mapping to a servlet is the request URL from the request object minus the context path and the path parameters. The URL path mapping rules below are used in order. The first successful match is used with no further matches attempted:

1. The container will try to find an exact match of the path of the request to the path of the servlet. A successful match selects the servlet.
2. The container will recursively try to match the longest path-prefix. This is done by stepping down the path tree a directory at a time, using the '/' character as a path separator. The longest match determines the servlet selected.
3. If the last segment in the URL path contains an extension (e.g. `.jsp`), the servlet container will try to match a servlet that handles requests for the extension. An extension is defined as the part of the last segment after the last '.' character.

1. Versions of this specification prior to 2.5 made use of these mapping techniques as a suggestion rather than a requirement, allowing servlet containers to each have their different schemes for mapping client requests to servlets.

4. If neither of the previous three rules result in a servlet match, the container will attempt to serve content appropriate for the resource requested. If a "default" servlet is defined for the application, it will be used. Many containers provide an implicit default servlet for serving content.

The container must use case-sensitive string comparisons for matching.

12.2 Specification of Mappings

In the Web application deployment descriptor, the following syntax is used to define mappings:

- A string beginning with a `'/'` character and ending with a `'/*'` suffix is used for path mapping.
- A string beginning with a `'*.'` prefix is used as an extension mapping.
- The empty string (`""`) is a special URL pattern that exactly maps to the application's context root, i.e., requests of the form `http://host:port/<context-root>/`. In this case the path info is `'/'` and the servlet path and context path is empty string (`""`).
- A string containing only the `'/'` character indicates the "default" servlet of the application. In this case the servlet path is the request URI minus the context path and the path info is null.
- All other strings are used for exact matches only.

12.2.1 Implicit Mappings

If the container has an internal JSP container, the `*.jsp` extension is mapped to it, allowing JSP pages to be executed on demand. This mapping is termed an *implicit* mapping. If a `*.jsp` mapping is defined by the Web application, its mapping takes precedence over the implicit mapping.

A servlet container is allowed to make other implicit mappings as long as explicit mappings take precedence. For example, an implicit mapping of `*.html` could be mapped to include functionality on the server.

12.2.2 Example Mapping Set

Consider the following set of mappings:

TABLE 12-1 Example Set of Maps

Path Pattern	Servlet
/foo/bar/*	servlet1
/baz/*	servlet2
/catalog	servlet3
*.bop	servlet4

The following behavior would result:

TABLE 12-2 Incoming Paths Applied to Example Maps

Incoming Path	Servlet Handling Request
/foo/bar/index.html	servlet1
/foo/bar/index.bop	servlet1
/baz	servlet2
/baz/index.html	servlet2
/catalog	servlet3
/catalog/index.html	"default" servlet
/catalog/racecar.bop	servlet4
/index.bop	servlet4

Note that in the case of `/catalog/index.html` and `/catalog/racecar.bop`, the servlet mapped to `/catalog` is not used because the match is not exact.

Security

Web applications are created by Application Developers who give, sell, or otherwise transfer the application to a Deployer for installation into a runtime environment. Application Developers communicate the security requirements to the Deployers and the deployment system. This information may be conveyed declaratively via the application's deployment descriptor, or by using annotations within the application code.

This chapter describes the Servlet container security mechanisms and interfaces and the deployment descriptor and annotation based mechanisms for conveying the security requirements of applications.

13.1 Introduction

A web application contains resources that can be accessed by many users. These resources often traverse unprotected, open networks such as the Internet. In such an environment, a substantial number of web applications will have security requirements.

Although the quality assurances and implementation details may vary, servlet containers have mechanisms and infrastructure for meeting these requirements that share some of the following characteristics:

- **Authentication:** The means by which communicating entities prove to one another that they are acting on behalf of specific identities that are authorized for access.
- **Access control for resources:** The means by which interactions with resources are limited to collections of users or programs for the purpose of enforcing integrity, confidentiality, or availability constraints.
- **Data Integrity:** The means used to prove that information has not been modified by a third party while in transit.

- **Confidentiality or Data Privacy:** The means used to ensure that information is made available only to users who are authorized to access it.

13.2 Declarative Security

Declarative security refers to the means of expressing an application's security model or requirements, including roles, access control, and authentication requirements in a form external to the application. The deployment descriptor is the primary vehicle for declarative security in web applications.

The Deployer maps the application's logical security requirements to a representation of the security policy that is specific to the runtime environment. At runtime, the servlet container uses the security policy representation to enforce authentication and authorization.

The security model applies to the static content part of the web application and to servlets and filters within the application that are requested by the client. The security model does not apply when a servlet uses the `RequestDispatcher` to invoke a static resource or servlet using a `forward` or an `include`.

13.3 Programmatic Security

Programmatic security is used by security aware applications when declarative security alone is not sufficient to express the security model of the application. Programmatic security consists of the following methods of the `HttpServletRequest` interface:

- `authenticate`
- `login`
- `logout`
- `getRemoteUser`
- `isUserInRole`
- `getUserPrincipal`

The `login` method allows an application to perform username and password collection (as an alternative to Form-Based Login). The `authenticate` methods allow an application to instigate authentication of the request caller by the container from within an unconstrained request context.

The `logout` method is provided to allow an application to reset the caller identity of a request.

The `getRemoteUser` method returns the name of the remote user (that is, the caller) associated, by the container, with the request.

The `isUserInRole` method determines if the remote user (that is, the caller) associated with the request is in a specified security role.

The `getUserPrincipal` method determines the principal name of the remote user (that is, the caller) and returns a `java.security.Principal` object corresponding to the remote user. Calling the `getName` method on the `Principal` returned by `getUserPrincipal` returns the name of the remote user. These APIs allow servlets to make business logic decisions based on the information obtained.

If no user has been authenticated, the `getRemoteUser` method returns `null`, the `isUserInRole` method always returns `false`, and the `getUserPrincipal` method returns `null`.

The `isUserInRole` method expects a `String` user role-name parameter. A `security-role-ref` element should be declared in the deployment descriptor with a `role-name` sub-element containing the role name to be passed to the method. A `security-role-ref` element should contain a `role-link` sub-element whose value is the name of the security role that the user may be mapped into. The container uses the mapping of `security-role-ref` to `security-role` when determining the return value of the call.

For example, to map the security role reference "FOO" to the security role with role-name "manager" the syntax would be:

```
<security-role-ref>
  <role-name>FOO</role-name>
  <role-link>manager</role-link>
</security-role-ref>
```

In this case if the servlet called by a user belonging to the "manager" security role made the API call `isUserInRole("FOO")` the result would be `true`.

If no `security-role-ref` element matching a `security-role` element has been declared, the container must default to checking the `role-name` element argument against the list of `security-role` elements for the web application. The `isUserInRole` method references the list to determine whether the caller is mapped to a security role. The developer must be aware that the use of this default mechanism may limit the flexibility in changing role names in the application without having to recompile the servlet making the call.

13.4 Programmatic Access Control Annotations

This section defines the annotations and apis provided to configure the security constraints enforced by the Servlet Container.

13.4.1 @ServletSecurity Annotation

The @ServletSecurity annotation provides an alternative mechanism for defining access control constraints equivalent to those that could otherwise have been expressed declaratively via `security-constraint` elements in the portable deployment descriptor or programmatically via the `setServletSecurity` method of the `ServletRegistration` interface. Servlet containers MUST support the use of the @ServletSecurity annotation on classes (and subclasses thereof) that implement the `javax.servlet.Servlet` interface.

```
package javax.servlet.annotation;

@Inherited
@Documented
@Target (value=TYPE)
@Retention(value=RUNTIME)
public @interface ServletSecurity {
    HttpConstraint value();
    HttpMethodConstraint[] httpMethodConstraints();
}
```

TABLE 13-1 The ServletSecurity Interface

Element	Description	Default
<code>value</code>	the <code>HttpConstraint</code> that defines the protection to be applied to all HTTP methods that are NOT represented in the array returned by <code>httpMethodConstraints</code> .	@HttpConstrai nt
<code>httpMethodConstraints</code>	the array of HTTP method specific constraints.	{}

@HttpConstraint

The `@HttpConstraint` annotation is used within the `@ServletSecurity` annotation to represent the security constraint to be applied to all HTTP methods for which a corresponding `@HttpMethodConstraint` does NOT occur within the `@ServletSecurity` annotation.

```
package javax.servlet.annotation;
@Documented
@Retention(value=RUNTIME)
public @interface HttpConstraint {
    ServletSecurity.EmptyRoleSemantic value();
    java.lang.String[] rolesAllowed();
    ServletSecurity.TransportGuarantee transportGuarantee();
}
```

TABLE 13-2 The `HttpConstraint` Interface

Element	Description	Default
<code>value</code>	The default authorization semantic that applies (only) when <code>rolesAllowed</code> returns an-empty array.	PERMIT
<code>rolesAllowed</code>	An array containing the names of the authorized roles	{}
<code>transportGuarantee</code>	The data protection requirements that must be satisfied by the connections on which requests arrive.	NONE

@HttpMethodConstraint

The `@HttpMethodConstraint` annotation is used within the `@ServletSecurity` annotation to represent security constraints on specific HTTP protocol messages.

```
package javax.servlet.annotation;
@Documented
@Retention(value=RUNTIME)
public @interface HttpMethodConstraint {
    ServletSecurity.EmptyRoleSemantic value();
    java.lang.String[] rolesAllowed();
    ServletSecurity.TransportGuarantee transportGuarantee();
}
```

}

TABLE 13-3 The `HttpMethodConstraint` Interface

Element	Description	Default
<code>value</code>	The HTTP protocol method name	
<code>emptyRoleSemantic</code>	The default authorization semantic that applies (only) when <code>rolesAllowed</code> returns an empty array.	PERMIT
<code>rolesAllowed</code>	An array containing the names of the authorized roles	{}
<code>transportGuarantee</code>	The data protection requirements that must be satisfied by the connections on which requests arrive.	NONE

The `@ServletSecurity` annotation may be specified on (that is, targeted to) a `Servlet` implementation class, and its value is inherited by subclasses according to the rules defined for the `@Inherited` meta-annotation. At most one instance of the `@ServletSecurity` annotation may occur on a `Servlet` implementation class, and the `@ServletSecurity` annotation **MUST NOT** be specified on (that is, targeted to) a Java method.

When one or more `@HttpMethodConstraint` annotations are defined within a `@ServletSecurity` annotation, each `@HttpMethodConstraint` defines the security-constraint that applies to the HTTP protocol method identified within the `@HttpMethodConstraint`. The encompassing `@ServletSecurity` annotation defines the security-constraint that applies to all HTTP protocol methods other than those for which a corresponding `@HttpMethodConstraint` is defined within the `@ServletSecurity` annotation.

The security-constraint elements defined in the portable deployment descriptors are authoritative for all the `url-patterns` occurring within the constraints.

When a security-constraint in the portable deployment descriptor includes a `url-pattern` that is an exact match for a pattern mapped to a class annotated with `@ServletSecurity`, the annotation must have no effect on the constraints enforced by the `Servlet` container on the pattern.

When `metadata-complete=true` is defined for a portable deployment descriptor, the `@ServletSecurity` annotation does not apply to any of the `url-patterns` mapped to (any `Servlet` mapped to) the annotated class in the deployment descriptor.

The `@ServletSecurity` annotation is not applied to the `url-patterns` of a `ServletRegistration` created using the `addServlet(String, Servlet)` method of the `ServletContext` interface, unless the `Servlet` was constructed by the `createServlet` method of the `ServletContext` interface.

With the exceptions listed above, when a `Servlet` class is annotated with `@ServletSecurity`, the annotation defines the security constraints that apply to all the `url-patterns` mapped to all the `Servlets` mapped to the class.

When a class has not been annotated with the `@ServletSecurity` annotation, the access policy that is applied to a `Servlet` mapped from that class is established by the applicable `security-constraint` elements, if any, in the corresponding portable deployment descriptor, or barring any such elements, by the constraints, if any, established programmatically for the target `Servlet` via the `setServletSecurity` method of the `ServletRegistration` interface.

13.4.1.1 Examples

The following examples demonstrate the use of the `ServletSecurity` annotation.

CODE EXAMPLE 13-1 for all HTTP methods, no constraints

```
@ServletSecurity
public class Example1 extends HttpServlet {
}
```

CODE EXAMPLE 13-2 for all HTTP methods, no auth-constraint, confidential transport required

```
@ServletSecurity(@HttpConstraint(transportGuarantee =
TransportGuarantee.CONFIDENTIAL))
public class Example2 extends HttpServlet {
}
```

CODE EXAMPLE 13-3 for all HTTP methods, all access denied

```
@ServletSecurity(@HttpConstraint(EmptyRoleSemantic.DENY))
public class Example3 extends HttpServlet {
}
```

CODE EXAMPLE 13-4 for all HTTP methods, auth-constraint requiring membership in Role R1

```
@ServletSecurity(@HttpConstraint(rolesAllowed = "R1"))
public class Example4 extends HttpServlet {
}
```

CODE EXAMPLE 13-5 for All HTTP methods except GET and POST, no constraints; for methods GET and POST, auth-constraint requiring membership in Role R1; for POST, confidential transport required

```

@ServletSecurity((httpMethodConstraints = {
    @HttpMethodConstraint(value = "GET", rolesAllowed = "R1"),
    @HttpMethodConstraint(value = "POST", rolesAllowed = "R1",
        transportGuarantee = TransportGuarantee.CONFIDENTIAL)
    })
public class Example5 extends HttpServlet {
}

```

CODE EXAMPLE 13-6 for all HTTP methods except GET auth-constraint requiring membership in Role R1; for GET, no constraints

```

@ServletSecurity(value = @HttpConstraint(rolesAllowed = "R1"),
    httpMethodConstraints = @HttpMethodConstraint("GET"))
public class Example6 extends HttpServlet {
}

```

CODE EXAMPLE 13-7 for all HTTP methods except TRACE, auth-constraint requiring membership in Role R1; for TRACE, all access denied

```

@ServletSecurity(value = @HttpConstraint(rolesAllowed = "R1"),
    httpMethodConstraints = @HttpMethodConstraint(value="TRACE",
        emptyRoleSemantic = EmptyRoleSemantic.DENY))
public class Example7 extends HttpServlet {
}

```

13.4.1.2 Mapping @ServletSecurity to security-constraint

This section describes the mapping of the @ServletSecurity annotation to its equivalent representation as security-constraint elements. It is provided to facilitate enforcement using the existing security-constraint enforcement mechanism of the container. The enforcement by Servlet containers, of the @ServletSecurity annotation must be equivalent in effect to enforcement, by the container, of the security-constraint elements resulting from the mapping defined in this section.

The @ServletSecurity annotation is used to define one method-independent @HttpConstraint followed by a list of zero or more @HttpMethodConstraint specifications. The method-independent constraint is applied to all HTTP methods for which no HTTP method-specific constraint has been defined.

When no @HttpMethodConstraint elements are included, a @ServletSecurity annotation corresponds to a single security-constraint element containing a web-resource-collection that contains no http-method elements, and thus pertains to all HTTP methods.

The following example depicts the representation of a `@ServletSecurity` annotation with no contained `@HttpMethodConstraint` annotations as a single `security-constraint` element. The `url-pattern` elements defined by the corresponding servlet (registration) would be included in the `web-resource-collection`, and the presence and value of any contained `auth-constraint` and `user-data-constraint` elements would be determined by the mapping of the `@HttpConstraint` value as defined in Section 13.4.1.3, “Mapping `@HttpConstraint` and `@HttpMethodConstraint` to XML.” on page 13-132

CODE EXAMPLE 13-8 mapping `@ServletSecurity` with no contained `@HttpMethodConstraint`

```
@ServletSecurity(@HttpConstraint(rolesAllowed = "Role1"))
<security-constraint>
    <web-resource-collection>
        <url-pattern>...</url-pattern>
    </web-resource-collection>
    <auth-constraint>
        <role-name>Role1</role-name>
    </auth-constraint>
</security-constraint>
```

When one or more `@HttpMethodConstraint` elements are specified, the method-independent constraint corresponds to a single `security-constraint` containing a `web-resource-collection` that contains an `http-method-omission` element for each of the HTTP methods named in the method-specific constraints. Each `@HttpMethodConstraint` corresponds to another `security-constraint` containing a `web-resource-collection` containing an `http-method` element naming the corresponding HTTP method. The following example depicts the mapping of a `@ServletSecurity` annotation with a single contained `@HttpMethodConstraint` to two `security-constraint` elements. The `url-pattern` elements defined by the corresponding servlet (registration) would be included in the `web-resource-collection` of both constraints, and the presence and value of any contained `auth-constraint` and `user-data-constraint` elements would be determined by the mapping of the associated `@HttpConstraint` and `@HttpMethodConstraint` values as defined in Section 13.4.1.3, “Mapping `@HttpConstraint` and `@HttpMethodConstraint` to XML.” on page 13-132

CODE EXAMPLE 13-9 mapping `@ServletSecurity` with contained `@HttpMethodConstraint`

```
@ServletSecurity(value=@HttpConstraint(rolesAllowed = "Role1"),
    httpMethodConstraints = @HttpMethodConstraint(value = "TRACE",
    emptyRoleSemantic = EmptyRoleSemantic.DENY))
```

```
<security-constraint>
```

```

    <web-resource-collection>
      <url-pattern>...</url-pattern>
      <http-method-omission>TRACE</http-method-omission>
    </web-resource-collection>
    <auth-constraint>
      <role-name>Role1</role-name>
    </auth-constraint>
  </security-constraint>
<security-constraint>
  <web-resource-collection>
    <url-pattern>...</url-pattern>
    <http-method>TRACE</http-method>
  </web-resource-collection>
  <auth-constraint/>
</security-constraint>

```

13.4.1.3 Mapping @HttpConstraint and @HttpMethodConstraint to XML.

This section describes the mapping of the `@HttpConstraint` and `@HttpMethodConstraint` annotation values (defined for use within `@ServletSecurity`) to their corresponding `auth-constraint` and `user-data-constraint` representations. These annotations share a common model for expressing the equivalent of the `auth-constraint` and `user-data-constraint` elements used within the portable deployment descriptor. That model is composed of the following 3 elements:

- `emptyRoleSemantic`
the authorization semantic, either `PERMIT` or `DENY`, that applies when no roles are named in `rolesAllowed`. The default value for this element is `PERMIT`, and `DENY` is not supported in combination with a non-empty `rolesAllowed` list.
- `rolesAllowed`
A list containing the names of the authorized roles. When this list is empty, its meaning depends on the value of the `emptyRoleSemantic`. The role name `"*"` has no special meaning when included in the list of allowed roles. The default value for this element is an empty list.
- `transportGuarantee`

The data protection requirements, either `NONE` or `CONFIDENTIAL`, that must be satisfied by the connections on which requests arrive. This element is equivalent in meaning to a `user-data-constraint` containing a `transport-guarantee` with the corresponding value. The default value for this element is `NONE`.

The following examples depict the correspondence between the `@HttpConstraint` model described above and `auth-constraint` and `user-data-constraint` elements in `web.xml`.

CODE EXAMPLE 13-10 `emptyRoleSemantic=PERMIT, rolesAllowed={}, transportGuarantee=NONE`

```
no constraints
```

CODE EXAMPLE 13-11 `emptyRoleSemantic=PERMIT, rolesAllowed={}, transportGuarantee=CONFIDENTIAL`

```
<user-data-constraint>
  <transport-guarantee>CONFIDENTIAL</transport-guarantee>
</user-data-constraint>
```

CODE EXAMPLE 13-12 `emptyRoleSemantic=PERMIT, rolesAllowed={Role1}, transportGuarantee=NONE`

```
<auth-constraint>
  <security-role-name>Role1</security-role-name>
</auth-constraint>
```

CODE EXAMPLE 13-13 `emptyRoleSemantic=PERMIT, rolesAllowed={Role1}, transportGuarantee=CONFIDENTIAL`

```
<auth-constraint>
  <security-role-name>Role1</security-role-name>
</auth-constraint>
<user-data-constraint>
  <transport-guarantee>CONFIDENTIAL</transport-guarantee>
</user-data-constraint>
```

CODE EXAMPLE 13-14 `emptyRoleSemantic=DENY, rolesAllowed={}, transportGuarantee=NONE`

```
<auth-constraint/>
```

CODE EXAMPLE 13-15 `emptyRoleSemantic=DENY, rolesAllowed={}, transportGuarantee=CONFIDENTIAL`

```
<auth-constraint/>
<user-data-constraint>
  <transport-guarantee>CONFIDENTIAL</transport-guarantee>
</user-data-constraint>
```

13.4.2 setServletSecurity of ServletRegistration.Dynamic

The `setServletSecurity` method may be used within a `ServletContextListener` to define the security constraints to be applied to the mappings defined for a `ServletRegistration`.

```
Collection<String> setServletSecurity(ServletSecurityElement  
arg);
```

The `javax.servlet.ServletSecurityElement` argument to `setServletSecurity` is analogous in structure and model to the `ServletSecurity` interface of the `@ServletSecurity` annotation. As such, the mappings defined in Section 13.4.1.2, “Mapping `@ServletSecurity` to security-constraint” on page 13-130, apply analogously to the mapping of a `ServletSecurityElement` with contained `HttpConstraintElement` and `HttpMethodConstraintElement` values, to its equivalent security-constraint representation.

The `setServletSecurity` method returns the (possibly empty) Set of URL patterns that are already the exact target of a security-constraint element in the portable deployment descriptor (and thus were unaffected by the call).

This method throws an `IllegalStateException` if the `ServletContext` from which the `ServletRegistration` was obtained has already been initialized.

When a security-constraint in the portable deployment descriptor includes a `url-pattern` that is an exact match for a pattern mapped by a `ServletRegistration`, calls to `setServletSecurity` on the `ServletRegistration` must have no effect on the constraints enforced by the Servlet container on the pattern.

With the exceptions listed above and including when the Servlet class is annotated with `@ServletSecurity`, when `setServletSecurity` is called on a `ServletRegistration` it establishes the security constraints that apply to the `url-patterns` of the registration.

13.5 Roles

A security role is a logical grouping of users defined by the Application Developer or Assembler. When the application is deployed, roles are mapped by a Deployer to principals or groups in the runtime environment.

A servlet container enforces declarative or programmatic security for the principal associated with an incoming request based on the security attributes of the principal. This may happen in either of the following ways:

1. A deployer has mapped a security role to a user group in the operational environment. The user groups to which the calling principal belongs are retrieved from its security attributes. The principal is in the security role only if the principal belongs to the user group to which the security role has been mapped by the deployer.
2. A deployer has mapped a security role to a principal name in a security policy domain. In this case, the principal name of the calling principal is retrieved from its security attributes. The principal is in the security role only if the principal name is the same as a principal name to which the security role was mapped.

13.6 Authentication

A web client can authenticate a user to a web server using one of the following mechanisms:

- HTTP Basic Authentication
- HTTP Digest Authentication
- HTTPS Client Authentication
- Form Based Authentication

13.6.1 HTTP Basic Authentication

HTTP Basic Authentication, which is based on a username and password, is the authentication mechanism defined in the HTTP/1.0 specification. A web server requests a web client to authenticate the user. As part of the request, the web server passes the *realm* (a string) in which the user is to be authenticated. The web client obtains the username and the password from the user and transmits them to the web server. The web server then authenticates the user in the specified realm.

Basic Authentication is not a secure authentication protocol. User passwords are sent in simple base64 encoding, and the target server is not authenticated. Additional protection can alleviate some of these concerns: a secure transport mechanism (HTTPS), or security at the network level (such as the IPSEC protocol or VPN strategies) is applied in some deployment scenarios.

13.6.2 HTTP Digest Authentication

Like HTTP Basic Authentication, HTTP Digest Authentication authenticates a user based on a username and a password. However, unlike HTTP Basic Authentication, HTTP Digest Authentication does not send user passwords over the network. In HTTP Digest authentication the client sends a one-way cryptographic hash of the password (and additional data). Although passwords are not sent on the wire, HTTP Digest authentication requires that clear text password equivalents¹ be available to the authenticating container so that it can validate received authenticators by calculating the expected digest. Servlet containers SHOULD to support HTTP_DIGEST authentication.

13.6.3 Form Based Authentication

The look and feel of the “login screen” cannot be varied using the web browser’s built-in authentication mechanisms. This specification introduces a required form based authentication mechanism which allows a Developer to control the look and feel of the login screens.

The web application deployment descriptor contains entries for a login form and error page. The login form must contain fields for entering a username and a password. These fields must be named `j_username` and `j_password`, respectively.

When a user attempts to access a protected web resource, the container checks the user’s authentication. If the user is authenticated and possesses authority to access the resource, the requested web resource is activated and a reference to it is returned. If the user is not authenticated, all of the following steps occur:

1. The login form associated with the security constraint is sent to the client and the URL path triggering the authentication is stored by the container.
2. The user is asked to fill out the form, including the username and password fields.
3. The client posts the form back to the server.
4. The container attempts to authenticate the user using the information from the form.
5. If authentication fails, the error page is returned using either a forward or a redirect, and the status code of the response is set to 200.
6. If authentication succeeds, the authenticated user’s principal is checked to see if it is in an authorized role for accessing the resource.

¹ The password equivalents can be such that they can only be used to authenticate as the user at a specific realm.

7. If the user is authorized, the client is redirected to the resource using the stored URL path.

The error page sent to a user that is not authenticated contains information about the failure.

Form Based Authentication has the same lack of security as Basic Authentication since the user password is transmitted as plain text and the target server is not authenticated. Again additional protection can alleviate some of these concerns: a secure transport mechanism (HTTPS), or security at the network level (such as the IPSEC protocol or VPN strategies) is applied in some deployment scenarios.

The login method of the `HttpServletRequest` interface provides an alternative means for an application to control the look and feel of its login screens.

13.6.3.1 Login Form Notes

Form based login and URL based session tracking can be problematic to implement. Form based login should be used only when sessions are being maintained by cookies or by SSL session information.

In order for the authentication to proceed appropriately, the action of the login form must always be `j_security_check`. This restriction is made so that the login form will work no matter which resource it is for, and to avoid requiring the server to specify the action field of the outbound form.

Here is an example showing how the form should be coded into the HTML page:

```
<form method="POST" action="j_security_check">
<input type="text" name="j_username">
<input type="password" name="j_password">
</form>
```

If the form based login is invoked because of an HTTP request, the original request parameters must be preserved by the container for use if, on successful authentication, it redirects the call to the requested resource.

If the user is authenticated using form login and has created an HTTP session, the timeout or invalidation of that session leads to the user being logged out in the sense that subsequent requests must cause the user to be re-authenticated. The scope of the logout is the same as that of the authentication: for example, if the container supports single signon, such as Java EE technology compliant web containers, the user would need to reauthenticate with any of the web applications hosted on the web container.

13.6.4 HTTPS Client Authentication

End user authentication using HTTPS (HTTP over SSL) is a strong authentication mechanism. This mechanism requires the client to possess a Public Key Certificate (PKC). Currently, PKCs are useful in e-commerce applications and also for a single-signon from within the browser.

13.6.5 Additional Container Authentication Mechanisms

Servlet containers should provide public interfaces that may be used to integrate and configure additional HTTP message layer authentication mechanisms for use by the container on behalf of deployed applications. These interfaces should be offered for use by parties other than the container vendor (including application developers, system administrators, and system integrators).

To facilitate portable implementation and integration of additional container authentication mechanisms, it is recommended that all Servlet containers implement the Servlet Container Profile of The Java™ Authentication SPI for Containers (i.e., JSR 196). The SPI is available for download at:
<http://www.jcp.org/en/jsr/detail?id=196>

13.7 Server Tracking of Authentication Information

As the underlying security identities (such as users and groups) to which roles are mapped in a runtime environment are environment specific rather than application specific, it is desirable to:

1. Make login mechanisms and policies a property of the environment the web application is deployed in.
2. Be able to use the same authentication information to represent a principal to all applications deployed in the same container, and
3. Require re-authentication of users only when a security policy domain boundary has been crossed.

Therefore, a servlet container is required to track authentication information at the container level (rather than at the web application level). This allows users authenticated for one web application to access other resources managed by the container permitted to the same security identity.

13.8 Specifying Security Constraints

Security constraints are a declarative way of defining the protection of web content. A security constraint associates authorization and or user data constraints with HTTP operations on web resources. A security constraint, represented as a `security-constraint` in a deployment descriptor, consists of the following elements:

- web resource collection (`web-resource-collection` in deployment descriptor)
- authorization constraint (`auth-constraint` in deployment descriptor)
- user data constraint (`user-data-constraint` in deployment descriptor)

The HTTP operations and web resources to which a security constraint applies (i.e. the constrained requests) are identified by one or more web resource collections. A web resource collection consists of the following elements:

- URL patterns (`url-pattern` in deployment descriptor)
- HTTP methods (`http-method` or `http-method-omission` elements in the deployment descriptor)

An authorization constraint establishes a requirement for authentication and names the authorization roles permitted to perform the constrained requests. A user must be a member of at least one of the named roles to be permitted to perform the constrained requests. The special role name `"*"` is a shorthand for all role names defined in the deployment descriptor. An authorization constraint that names no roles indicates that access to the constrained requests must not be permitted under any circumstances. An authorization constraint consists of the following element:

- role name (`role-name` in deployment descriptor)

A user data constraint establishes a requirement that the constrained requests be received over a protected transport layer connection. The strength of the required protection is defined by the value of the transport guarantee. A transport guarantee of `INTEGRAL` is used to establish a requirement for content integrity and a transport guarantee of `CONFIDENTIAL` is used to establish a requirement for confidentiality. The transport guarantee of `"NONE"` indicates that the container must accept the constrained requests when received on any connection including an unprotected one. A user data constraint consists of the following element:

- transport guarantee (`transport-guarantee` in deployment descriptor)

If no authorization constraint applies to a request, the container must accept the request without requiring user authentication. If no user data constraint applies to a request, the container must accept the request when received over any connection including an unprotected one.

13.8.1 Combining Constraints

For the purpose of combining constraints, an HTTP method is said to occur within a `web-resource-collection` when no HTTP methods are named in the collection, or the collection specifically names the HTTP method in a contained `http-method` element, or the collection contains one or more `http-method-omission` elements, none of which names the HTTP method.

When a `url-pattern` and HTTP method pair occurs in combination(i.e, within a `web-resource-collection`) in multiple security constraints, the constraints (on the pattern and method) are defined by combining the individual constraints. The rules for combining constraints in which the same pattern and method occur are as follows:

The combination of authorization constraints that name roles or that imply roles via the name "*" shall yield the union of the role names in the individual constraints as permitted roles. A security constraint that does not contain an authorization constraint shall combine with authorization constraints that name or imply roles to allow unauthenticated access. The special case of an authorization constraint that names no roles shall combine with any other constraints to override their affects and cause access to be precluded.

The combination of `user-data-constraints` that apply to a common `url-pattern` *and* `http-method` shall yield the union of connection types accepted by the individual constraints as acceptable connection types. A security constraint that does not contain a `user-data-constraint` shall combine with other `user-data-constraint` to cause the unprotected connection type to be an accepted connection type.

13.8.2 Example

The following example illustrates the combination of constraints and their translation into a table of applicable constraints. Suppose that a deployment descriptor contained the following security constraints.

```
<security-constraint>

  <web-resource-collection>
    <web-resource-name>precluded methods</web-resource-name>
    <url-pattern>/*</url-pattern>
    <url-pattern>/acme/wholesale/*</url-pattern>
    <url-pattern>/acme/retail/*</url-pattern>
    <http-method-omission>GET</http-method-omission>
    <http-method-omission>POST</http-method-omission>
  </web-resource-collection>

  <auth-constraint/>

</security-constraint>

<security-constraint>

  <web-resource-collection>
    <web-resource-name>wholesale</web-resource-name>
    <url-pattern>/acme/wholesale/*</url-pattern>
    <http-method>GET</http-method>
    <http-method>PUT</http-method>
  </web-resource-collection>

  <auth-constraint>
    <role-name>SALESCLERK</role-name>
  </auth-constraint>

</security-constraint>
```

```
<security-constraint>

  <web-resource-collection>
    <web-resource-name>wholesale 2</web-resource-name>
    <url-pattern>/acme/wholesale/*</url-pattern>
    <http-method>GET</http-method>
    <http-method>POST</http-method>
  </web-resource-collection>

  <auth-constraint>
    <role-name>CONTRACTOR</role-name>
  </auth-constraint>

  <user-data-constraint>
    <transport-guarantee>CONFIDENTIAL</transport-guarantee>
  </user-data-constraint>

</security-constraint>

<security-constraint>

  <web-resource-collection>
    <web-resource-name>retail</web-resource-name>
    <url-pattern>/acme/retail/*</url-pattern>
    <http-method>GET</http-method>
    <http-method>POST</http-method>
  </web-resource-collection>

  <auth-constraint>
    <role-name>CONTRACTOR</role-name>
    <role-name>HOMEOWNER</role-name>
  </auth-constraint>

</security-constraint>
```

The translation of this hypothetical deployment descriptor would yield the constraints defined in TABLE 13-4.

TABLE 13-4 Security Constraint Table

url-pattern	http-method	permitted roles	supported connection types
/*	all methods except GET, POST	access precluded	not constrained
/acme/wholesale/*	all methods except GET, POST	access precluded	not constrained
/acme/wholesale/*	GET	CONTRACTOR SALESCLERK	not constrained
/acme/wholesale/*	POST	CONTRACTOR	CONFIDENTIAL
/acme/retail/*	all methods except GET, POST	access precluded	not constrained
/acme/retail/*	GET	CONTRACTOR HOMEOWNER	not constrained
/acme/retail/*	POST	CONTRACTOR HOMEOWNER	not constrained

13.8.3 Processing Requests

When a Servlet container receives a request, it shall use the algorithm described in “Use of URL Paths” on page 119 to select the constraints (if any) defined on the `url-pattern` that is the best match to the request URI. If no constraints are selected, the container shall accept the request. Otherwise the container shall determine if the HTTP method of the request is constrained at the selected pattern. If it is not, the request shall be accepted. Otherwise, the request must satisfy the constraints that apply to the HTTP method at the `url-pattern`. Both of the following rules must be satisfied for the request to be accepted and dispatched to the associated servlet.

1. The characteristics of the connection on which the request was received must satisfy at least one of the supported connection types defined by the constraints. If this rule is not satisfied, the container shall reject the request and redirect it to the HTTPS port.²
2. The authentication characteristics of the request must satisfy any authentication and role requirements defined by the constraints. If this rule is not satisfied because access has been precluded (by an authorization constraint naming no roles), the request shall be rejected as forbidden and a 403 (SC_FORBIDDEN) status code shall be returned to the user. If access is restricted to permitted roles and the request has not been authenticated, the request shall be rejected as unauthorized and a 401 (SC_UNAUTHORIZED) status code shall be returned to cause authentication. If access is restricted to permitted roles and the authentication identity of the request is not a member of any of these roles, the request shall be rejected as forbidden and a 403 (SC_FORBIDDEN) status code shall be returned to the user.

13.9 Default Policies

By default, authentication is not needed to access resources. Authentication is required when the security constraints (if any) that contain the `url-pattern` that is the best match for the request URI combine to impose an `auth-constraint` (naming roles) on the HTTP method of the request. Similarly, a protected transport is not required unless the security constraints that apply to the request combine to impose a `user-data-constraint` (with a `protected-transport-guarantee`) on the HTTP method of the request.

13.10 Login and Logout

The container establishes the caller identity of a request prior to dispatching the request to the servlet engine. The caller identity remains unchanged throughout the processing of the request or until the application successfully calls `authenticate`, `login` or `logout` on the request. For asynchronous requests, the caller identity established at the initial dispatch remains unchanged until the processing of the overall request completes, or the application successfully calls `authenticate`, `login` or `logout` on the request.

2. As an optimization, a container should reject the request as forbidden and return a 403 (SC_FORBIDDEN) status code if it knows that access will ultimately be precluded (by an authorization constraint naming no roles).

Being logged into an application during the processing of a request, corresponds precisely to there being a valid non-null caller identity associated with the request as may be determined by calling `getRemoteUser` or `getUserPrincipal` on the request. A `null` return value from either of these methods indicates that the caller is not logged into the application with respect to the processing of the request.

Containers may create HTTP Session objects to track login state. If a developer creates a session while a user is not authenticated, and the container then authenticates the user, the session visible to developer code after login must be the same session object that was created prior to login occurring so that there is no loss of session information.

Deployment Descriptor

This chapter specifies the Java™ Servlet Specification version 3.0 requirements for Web container support of deployment descriptors. The deployment descriptor conveys the elements and configuration information of a Web application between Application Developers, Application Assemblers, and Deployers.

For Java Servlets v.2.4 and greater, the deployment descriptor is defined in terms of an XML schema document.

For backwards compatibility of applications written to the 2.2 version of the API, Web containers are also required to support the 2.2 version of the deployment descriptor. For backwards compatibility of applications written to the 2.3 version of the API, Web containers are also required to support the 2.3 version of the deployment descriptor. The 2.2 version is available at http://java.sun.com/j2ee/dtds/web-app_2_2.dtd and 2.3 version is available at http://java.sun.com/dtd/web-app_2_3.dtd.

14.1 Deployment Descriptor Elements

The following types of configuration and deployment information are required to be supported in the Web application deployment descriptor for all servlet containers:

- `ServletContext` Init Parameters
- Session Configuration
- Servlet Declaration
- Servlet Mappings
- Application Lifecycle Listener classes
- Filter Definitions and Filter Mappings
- MIME Type Mappings
- Welcome File list
- Error Pages
- Locale and Encoding Mappings

- Security configuration, including login-config, security-constraint, security-role, security-role-ref and run-as

14.2 Rules for Processing the Deployment Descriptor

This section lists some general rules that Web containers and developers must note concerning the processing of the deployment descriptor for a Web application.

- Web containers must remove all leading and trailing whitespace, which is defined as “S(white space)” in XML 1.0 (<http://www.w3.org/TR/2000/WD-xml-2e-20000814>), for the element content of the text nodes of a deployment descriptor.
- The deployment descriptor must be valid against the schema. Web containers and tools that manipulate Web applications have a wide range of options for checking the validity of a WAR. This includes checking the validity of the deployment descriptor document held within.

Additionally, it is recommended that Web containers and tools that manipulate Web applications provide a level of semantic checking. For example, it should be checked that a role referenced in a security constraint has the same name as one of the security roles defined in the deployment descriptor.

In cases of non-conformant Web applications, tools and containers should inform the developer with descriptive error messages. High-end application server vendors are encouraged to supply this kind of validity checking in the form of a tool separate from the container.

- The sub elements under `web-app` can be in an arbitrary order in this version of the specification. Because of the restriction of XML Schema, The multiplicity of the elements `distributable`, `session-config`, `welcome-file-list`, `jsp-config`, `login-config`, and `locale-encoding-mapping-list` was changed from “optional” to “0 or more”. The containers must inform the developer with a descriptive error message when the deployment descriptor contains more than one element of `session-config`, `jsp-config`, and `login-config`. The container must concatenate the items in `welcome-file-list` and `locale-encoding-mapping-list` when there are multiple occurrences. The multiple occurrence of `distributable` must be treated exactly in the same way as the single occurrence of `distributable`.
- URI paths specified in the deployment descriptor are assumed to be in URL-decoded form. The containers must inform the developer with a descriptive error message when URL contains CR (#xD) or LF (#xA). The containers must preserve all other characters including whitespace in URL.

- Containers must attempt to canonicalize paths in the deployment descriptor. For example, paths of the form `/a/.. /b` must be interpreted as `/b`. Paths beginning or resolving to paths that begin with `../` are not valid paths in the deployment descriptor.
- URI paths referring to a resource relative to the root of the WAR, or a path mapping relative to the root of the WAR, unless otherwise specified, should begin with a leading `/`.
- In elements whose value is an enumerated type, the value is case sensitive.

14.3 Deployment Descriptor

The deployment descriptor for this revision of the specification is available at http://java.sun.com/xml/ns/javaee/web-app_3_0.xsd


14.4 Deployment Descriptor Diagram

This section illustrates the elements in deployment descriptor. Attributes are not shown in the diagrams. See Deployment Descriptor Schema for the detailed information.

1. web-app Element

The web-app element is the root deployment descriptor for a Web application. This element contains the following elements. This element has a required attribute `version` to specify to which version of the schema the deployment descriptor conforms. All sub elements under this element can be in an arbitrary order.

FIGURE 14-1 web-app Element Structure



2. description Element

The `description` element is to provide a text describing the parent element. This element occurs not only under the `web-app` element but also under other multiple elements. It has an optional attribute `xml:lang` to indicate which language is used in the description. The default value of this attribute is English (“en”).

3. display-name Element

The `display-name` contains a short name that is intended to be displayed by tools. The display name need not to be unique. This element has an optional attribute `xml:lang` to specify the language.

4. icon Element

The `icon` contains `small-icon` and `large-icon` elements that specify the file names for small and large GIF or JPEG icon images used to represent the parent element in a GUI tool.

5. distributable Element

The `distributable` indicates that this Web application is programmed appropriately to be deployed into a distributed servlet container.

6. context-param Element


The `context-param` contains the declaration of a Web application’s servlet context initialization parameters.

7. filter Element

The `filter` declares a filter in the Web application. The filter is mapped to either a servlet or a URL pattern in the `filter-mapping` element, using the `filter-name` value to reference. Filters can access the initialization parameters declared in the deployment descriptor at runtime via the `FilterConfig` interface. The `filter-name` element is the logical name of the filter. It must be unique within the Web application. The element content of `filter-name` element must not be empty. The `filter-class` is the fully qualified class name of the filter. The

init-param element contains name-value pair as an initialization parameter of this filter. The optional async-supported element, when specified, indicates that the filter supports asynchronous request processing.


FIGURE 14-2 filter Element Structure



8. filter-mapping Element

The `filter-mapping` is used by the container to decide which filters to apply to a request in what order. The value of the `filter-name` must be one of the filter declarations in the deployment descriptor. The matching request can be specified either `url-pattern` or `servlet-name`.


FIGURE 14-3 filter-mapping Element Structure



9. listener Element

The `listener` indicates the deployment properties for an application listener bean. The sub-element `listener-class` declares that a class in the application must be registered as a Web application listener bean. The value is the fully qualified classname of the listener class.

FIGURE 14-4 listener Element Structure




10. servlet Element

The `servlet` is used to declare a servlet. It contains the declarative data of a servlet. The `jsp-file` element contains the full path to a JSP file within the web application beginning with a `"/`. If a `jsp-file` is specified and the `load-on-startup` element is present, then the JSP should be precompiled and loaded. The `servlet-name` element contains the canonical name of the servlet. Each servlet name is unique within the web application. The element content of `servlet-name` must not be empty. The `servlet-class` contains the fully qualified class name of the servlet. The `run-as` element specifies the identity to be used for the execution of a component. It contains an optional `description`, and the name of a security role specified by the `role-name` element. The element `load-on-startup` indicates that this servlet should be loaded (instantiated and have its `init()` called) on the startup of the Web application. The element content of this element must be an integer indicating the order in which the servlet should be loaded. If the value is a negative integer, or the element is not present, the container is free to load the servlet whenever it chooses. If the value is a positive integer or 0, the container must load and initialize the servlet as the application is deployed. The container must guarantee that servlets marked with lower integers are loaded before servlets marked with higher integers. The container may choose the order of loading of servlets with the same `load-on-startup` value. The `security-role-ref` element declares the security role reference in a component's or in a deployment component's code. It consists of an optional `description`, the security role name used in the code (`role-name`), and an optional link to a security role (`role-link`). If the security role is not specified, the deployer must choose an appropriate security role. The optional `async-supported` element, when specified, indicates that the Servlet can support asynchronous request processing. If a servlet supports fileupload functionality and processing of mime-multipart requests, the configuration for the same can be provided via the `multipart-config` element in the descriptor. The

multipart-config element can be used to specify the location where the files can be stored, maximum size of the file being uploaded, maximum request size and the size threshold after which the file will be written to the disk.


FIGURE 14-5 servlet Element Structure



11. servlet-mapping Element

The `servlet-mapping` defines a mapping between a servlet and a URL pattern.


FIGURE 14-6 `servlet-mapping` Element Structure



12. session-config Element

The `session-config` defines the session parameters for this Web application. The sub-element `session-timeout` defines the default session time out interval for all sessions created in this Web application. The specified time out must be expressed in a whole number of minutes. If the time out is 0 or less, the container ensures the default behavior of sessions is never to time out. If this element is not specified, the container must set its default time out period.


FIGURE 14-7 `session-config` Element Structure



13. mime-mapping Element

The `mime-mapping` defines a mapping between an extension and a mime type. The `extension` element contains a string describing an extension, such as “txt”.


FIGURE 14-8 mime-mapping Element Structure



14. welcome-file-list Element

The `welcome-file-list` contains an ordered list of welcome files. The sub-element `welcome-file` contains a file name to use as a default welcome file, such as `index.html`

FIGURE 14-9 welcome-file-list Element Structure




15. error-page Element

The `error-page` contains a mapping between an error code or an exception type to the path of a resource in the Web application. The sub-element `exception-type` contains a fully qualified class name of a Java exception type. The sub-

element `location` element contains the location of the resource in the web application relative to the root of the web application. The value of the location must have a leading `'/'`.


FIGURE 14-10 error-page Element Structure



16. jsp-config Element

The `jsp-config` is used to provide global configuration information for the JSP files in a web application. It has two sub-elements, `taglib` and `jsp-property-group`. The `taglib` element can be used to provide information on a tag library that is used by a JSP page within the Web application. See JavaServer Pages specification version 2.1 for detail.

FIGURE 14-11 jsp-config Element Structure




17. security-constraint Element

The `security-constraint` is used to associate security constraints with one or more web resource collections. The sub-element `web-resource-collection` identifies a subset of the resources and HTTP methods on those resources within a Web application to which a security constraint applies. The `auth-constraint` indicates the user roles that should be permitted access to this resource collection. The `role-name` used here must either correspond to the `role-name` of one of the `security-role` elements defined for this Web application, or be the specially reserved role-name "*" that is a compact syntax for indicating all roles in the web application. If both "*" and role names appear, the container interprets this as all roles. If no roles are defined, no user is allowed access to the portion of the Web application described by the containing `security-constraint`. The container matches role names case sensitively when determining access. The `user-data-constraint` indicates how data communicated between the client

and container should be protected by the sub-element `transport-guarantee`. The legal values of the `transport-guarantee` is either one of NONE, INTEGRAL, or CONFIDENTIAL.

FIGURE 14-12 security-constraint Element Structure




18. login-config Element

The `login-config` is used to configure the authentication method that should be used, the realm name that should be used for this application, and the attributes that are needed by the form login mechanism. The sub-element `auth-method` configures the authentication mechanism for the Web application. The element content must be either BASIC, DIGEST, FORM, CLIENT-CERT, or a

vendor-specific authentication scheme. The `realm-name` indicates the realm name to use for the authentication scheme chosen for the Web application. The `form-login-config` specifies the login and error pages that should be used in FORM based login. If FORM based login is not used, these elements are ignored.


FIGURE 14-13 login-config Element Structure



19. security-role Element

The `security-role` defines a security role. The sub-element `role-name` designates the name of the security role. The name must conform to the lexical rules for NMTOKEN.

FIGURE 14-14 security-role Element Structure




20. env-entry Element

The `env-entry` declares an application's environment entry. The sub-element `env-entry-name` contains the name of a deployment component's environment entry. The name is a JNDI name relative to the `java:comp/env` context. The name must be unique within a deployment component. The `env-entry-type` contains the fully-qualified Java type of the environment entry value that is

expected by the application's code. The sub-element `env-entry-value` designates the value of a deployment component's environment entry. The value must be a `String` that is valid for the constructor of the specified type that takes a single `String` as a parameter, or a single character for `java.lang.Character`. The optional `injection-target` element is used to define the injection of the named resource into fields or JavaBeans properties. An `injection-target` specifies a class and a name within that class into which a resource should be injected. The `injection-target-class` specifies the fully qualified class name that is the target of the injection. The `injection-target-name` specifies the target within the specified class. The target is first looked for as a JavaBean property name. If not found, the target is looked for as a field name. The specified resource will be injected into the target during initialization of the class by either calling the set method for the target property or by setting a value into the name

filed. If an injection-target is specified for the environment entry, the env-entry-type may be omitted or MUST match the type of the injection target. If no injection-target is specified, the env-entry-type is required.

FIGURE 14-15 env-entry Element Structure




21. ejb-ref Element

The `ejb-ref` declares the reference to an enterprise bean's home. The `ejb-ref-name` specifies the name used in the code of the deployment component that is referencing the enterprise bean. The `ejb-ref-type` is the expected type of the referenced enterprise bean, which is either `Entity` or `Session`. The `home` defines the fully qualified name of the referenced enterprise bean's home interface. The `remote` defines the fully qualified name of the referenced enterprise bean's remote interface. The `ejb-link` specifies that an EJB reference is linked to the

enterprise bean. See Java Platform, Enterprise Edition, version 6 for more detail. In addition to these elements, the injection-target element can be used to define injection of the named enterprise bean into a component field or property.


FIGURE 14-16 ejb-ref Element Structure



22. ejb-local-ref Element

The `ejb-local-ref` declares the reference to the enterprise bean's local home. The `local-home` defines the fully qualified name of the enterprise bean's local home interface. The `local` defines the fully qualified name of the enterprise bean's local interface.

FIGURE 14-17 `ejb-local-ref` Element Structure




23. service-ref Element

The `service-ref` declares the reference to a Web service. The `service-ref-name` declares the logical name that the components in the module use to look up the Web service. It is recommended that all service reference names start with `/service/`. The `service-interface` defines the fully qualified class name of the JAX-WS Service interface that the client depends on. In most cases, the value will be `javax.xml.rpc.Service`. A JAX-WS generated Service Interface class may also be specified. The `wsdl-file` element contains the URI location of a WSDL file. The location is relative to the root of the module. The `jaxrpc-mapping-file` contains the name of a file that describes the JAX-WS mapping between the Java interfaces used by the application and the WSDL description in the `wsdl-file`. The file name is a relative path within the module file. The `service-`

qname element declares the specific WSDL service element that is being referred to. It is not specified if no `wSDL-file` is declared. The `port-component-ref` element declares a client dependency on the container for resolving a Service Endpoint Interface to a WSDL port. It optionally associates the Service Endpoint Interface with a particular port-component. This is only used by the container for a `Service.getPort(Class)` method call. The `handler` element declares the handler for a port-component. Handlers can access the `init-param` name-value pairs using the `HandlerInfo` interface. If `port-name` is not specified, the handler is assumed to be associated with all ports of the service. See JSR-109 Specification [<http://www.jcp.org/en/jsr/detail?id=109>] for detail. The container that is not a part of a Java EE implementation is not required to support this element.


FIGURE 14-18 service-ref Element Structure



24. resource-ref Element

The `resource-ref` contains the declaration of a deployment component's reference to the external resource. The `res-ref-name` specifies the name of a resource manager connection factory reference. The name is a JNDI name relative to the `java:comp/env` context. The name must be unique within a deployment file. The `res-type` element specifies the type of the data source. The type is the fully qualified Java language class or the interface expected to be implemented by the data source. The `res-auth` specifies whether the deployment component code signs on programmatically to the resource manager, or whether the container will sign on to the resource manager on behalf of the deployment component. In the latter case, the container uses the information supplied by the deployer. The `res-sharing-scope` specifies whether connections obtained through the given resource manager connection factory reference can be shared. The value, if specified, must be either `Shareable` or `Unshareable`. The optional `injection-target` element is used to define injection of the named resource into fields or JavaBeans properties.


FIGURE 14-19 resource-ref Element Structure



25. resource-env-ref Element

The `resource-env-ref` contains the deployment component's reference to the administered object associated with a resource in the deployment component's environment. The `resource-env-ref-name` specifies the name of the resource environment reference. The value is the environment entry name used in the deployment component code and is a JNDI name relative to the `java:comp/env` context and must be unique within the deployment component. The `resource-env-ref-type` specifies the type of the resource environment reference. It is the fully qualified name of a Java language class or the interface. The optional `injection-target` element is used to define injection of the named resource into fields or JavaBeans properties. The `resource-env-ref-type` MUST be supplied unless an injection target is specified, in which case the type of the target is used. If both are specified, the type MUST be assignment compatible with the type of the injection target.

FIGURE 14-20 resource-env-ref Element Structure



26. message-destination-ref Element


The `message-destination-ref` element contains a declaration of deployment component's reference to a message destination associated with a resource in deployment component's environment. The `message-destination-ref-name` element specifies the name of a message destination reference; its value is the environment entry name used in deployment component code. The name is a

JNDI name relative to the `java:comp/env` context and must be unique within an `ejb-jar` for enterprise beans or a deployment file for others. The `message-destination-type` specifies the type of the destination. The type is specified by the Java interface expected to be implemented by the destination. The `message-destination-usage` specifies the use of the message destination indicated by the reference. The value indicates whether messages are consumed from the message destination, produced for the destination, or both. The Assembler makes use of this information in linking producers of a destination with its consumers. The `message-destination-link` links a message destination reference or message-driven bean to a message destination. The Assembler sets the value to reflect the flow of messages between producers and consumers in the application. The value must be the `message-destination-name` of a message destination in the same deployment file or in another deployment file in the same Java EE application unit. Alternatively, the value may be composed of a path name specifying a deployment file containing the referenced message destination with the `message-destination-name` of the destination appended and separated from the path name by "#". The path name is relative to the deployment file containing deployment component that is referencing the message destination. This allows multiple message destinations with the same name to be uniquely identified. The optional `injection-target` element is used to define injection of the named resource into fields or JavaBeans properties. The `message-destination-type` MUST be specified unless an injection target is specified, in which case the type of the target is used. If both are specified, the type MUST be assignment compatible with the type of the injection target.

Example:

```
<message-destination-ref>
  <message-destination-ref-name>
    jms/StockQueue
  </message-destination-ref-name>
  <message-destination-type>
    javax.jms.Queue
  </message-destination-type>
  <message-destination-usage>
    Consumes
  </message-destination-usage>
  <message-destination-link>
    CorporateStocks
  </message-destination-link>
</message-destination-ref>
```

FIGURE 14-21 message-destination-ref Element Structure




27. message-destination Element

The message-destination specifies a message destination. The logical destination described by this element is mapped to a physical destination by the deployer. The message-destination-name element specifies a name for a message destination. This name must be unique among the names of message destinations within the deployment file.

Example:

```
<message-destination>
  <message-destination-name>
    CorporateStocks
  </message-destination-name>
</message-destination>
```

FIGURE 14-22 message-destination Element Structure




28. locale-encoding-mapping-list Element

The `locale-encoding-mapping-list` contains the mapping between the locale and the encoding, specified by the sub-element `locale-encoding-mapping`.

Example:

```
<locale-encoding-mapping-list>
  <locale-encoding-mapping>
    <locale>ja</locale>
    <encoding>Shift_JIS</encoding>
  </locale-encoding-mapping>
</locale-encoding-mapping-list>
```

FIGURE 14-23 locale-encoding-mapping-list Element Structure



14.5 Examples

The following examples illustrate the usage of the definitions listed in the deployment descriptor schema.

14.5.1 A Basic Example

CODE EXAMPLE 14-1 Basic Deployment Descriptor Example

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<web-app xmlns="http://java.sun.com/xml/ns/j2ee"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://java.sun.com/xml/ns/j2ee
  http://java.sun.com/xml/ns/j2ee/web-app_2_5.xsd"
  version="2.5">

  <display-name>A Simple Application</display-name>
  <context-param>
    <param-name>Webmaster</param-name>
    <param-value>webmaster@mycorp.com</param-value>
  </context-param>
  <servlet>
    <servlet-name>catalog</servlet-name>
    <servlet-class>com.mycorp.CatalogServlet
      </servlet-class>
    <init-param>
      <param-name>catalog</param-name>
      <param-value>Spring</param-value>
    </init-param>
  </servlet>
  <servlet-mapping>
    <servlet-name>catalog</servlet-name>
    <url-pattern>/catalog/*</url-pattern>
  </servlet-mapping>
  <session-config>
    <session-timeout>30</session-timeout>
  </session-config>
  <mime-mapping>
    <extension>pdf</extension>
    <mime-type>application/pdf</mime-type>
  </mime-mapping>
  <welcome-file-list>
    <welcome-file>index.jsp</welcome-file>
    <welcome-file>index.html</welcome-file>
    <welcome-file>index.htm</welcome-file>
  </welcome-file-list>
  <error-page>
    <error-code>404</error-code>
    <location>/404.html</location>
  </error-page>
</web-app>
```

14.5.2 An Example of Security

CODE EXAMPLE 14-2 Deployment Descriptor Example Using Security

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<web-app xmlns="http://java.sun.com/xml/ns/j2ee"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://java.sun.com/xml/ns/j2ee
  http://java.sun.com/xml/ns/j2ee/web-app_2_5.xsd"
  version="2.5">

  <display-name>A Secure Application</display-name>
  <servlet>
    <servlet-name>catalog</servlet-name>
    <servlet-class>com.mycorp.CatalogServlet
    </servlet-class>
    <init-param>
      <param-name>catalog</param-name>
      <param-value>Spring</param-value>
    </init-param>
    <security-role-ref>
      <role-name>MGR</role-name>
      <!-- role name used in code -->
      <role-link>manager</role-link>
    </security-role-ref>
  </servlet>
  <security-role>
    <role-name>manager</role-name>
  </security-role>
  <servlet-mapping>
    <servlet-name>catalog</servlet-name>
    <url-pattern>/catalog/*</url-pattern>
  </servlet-mapping>
  <security-constraint>
    <web-resource-collection>
      <web-resource-name>SalesInfo
      </web-resource-name>
      <url-pattern>/salesinfo/*</url-pattern>
      <http-method>GET</http-method>
      <http-method>POST</http-method>
    </web-resource-collection>
    <auth-constraint>
      <role-name>manager</role-name>
    </auth-constraint>
    <user-data-constraint>
      <transport-guarantee>CONFIDENTIAL
      </transport-guarantee>
```

CODE EXAMPLE 14-2 Deployment Descriptor Example Using Security

```
    </user-data-constraint>  
  </security-constraint>  
</web-app>
```


Requirements related to other Specifications

This chapter lists the requirements for web containers that are included in products that also include other Java technologies.

In the following sections any reference to Java EE applies to not only the full Java EE profile but also any profile that includes support for Servlet, like the Java EE Web Profile. For more information on profiles please refer to the Java EE platform specification.

15.1 Sessions

Distributed servlet containers that are part of a Java EE implementation must support the mechanism necessary for migrating other Java EE objects from one JVM to another.

15.2 Web Applications

15.2.1 Web Application Class Loader

Servlet containers that are part of a Java EE product should not allow the application to override Java SE or Java EE platform classes, such as those in `java.*` and `javax.*` namespaces, that either Java SE or Java EE do not allow to be modified.

15.2.2 Web Application Environment

Java EE defines a naming environment that allows applications to easily access resources and external information without explicit knowledge of how the external information is named or organized.

As servlets are an integral component type of Java EE technology, provision has been made in the Web application deployment descriptor for specifying information allowing a servlet to obtain references to resources and enterprise beans. The deployment elements that contain this information are:

- `env-entry`
- `ejb-ref`
- `ejb-local-ref`
- `resource-ref`
- `resource-env-ref`
- `service-ref`
- `message-destination-ref`
- `persistence-context-ref`
- `persistence-unit-ref`

The developer uses these elements to describe certain objects that the Web application requires to be registered in the JNDI namespace in the Web container at runtime.

The requirements of the Java EE environment with regard to setting up the environment are described in Chapter 5 of the Java EE Specification.

Servlet containers that are part of a Java EE technology-compliant implementation are required to support this syntax. Consult the Java EE Specification for more details. This type of servlet container must support lookups of such objects and calls made to those objects when performed on a thread managed by the servlet container. This type of servlet container should support this behavior when performed on threads created by the developer, but are not currently required to do so. Such a requirement will be added in the next version of this specification. Developers are cautioned that depending on this capability for application-created threads is not recommended, as it is non-portable.

15.2.3 JNDI Name for Web Module Context Root URL

The Java EE Platform Specification defines a standardized global JNDI namespace and a series of related namespaces that map to various scopes of a Java EE application. These namespaces can be used by applications to portably retrieve references to components and resources. This section defines the JNDI names by which the base url for a web application is required to be registered.

The name of the pre-defined `java.net.URL` resource for the context root of a web application has the following syntax:

```
java:global[/<app-name>]/<module-name>!ROOT
```

 in the global namespace and

```
java:app/<module-name>!ROOT
```

 in the application-specific namespace.

Please see section EE 8.1.1 (Component creation) and EE 8.1.2 (Application assembly) for the rules to determine the app name and module name

The `<app-name>` is applicable only when the webapp is packaged within a `.ear` file.

The `java:app` prefix allows a component executing within a Java EE application to access an application-specific namespace. The `java:app` name allows a module in an enterprise application to reference the context root of another module in the same enterprise application. The `<module-name>` is a required part of the syntax for `java:app url`.

Examples

The above URL can then be used within an application as follows:

If a web application is deployed standalone with `module-name` as `myWebApp`. The URL can then be injected into another web module as follows:

CODE EXAMPLE 15-1

```
@Resource(lookup="java:global/myWebApp!ROOT")
URL myWebApp;
```

When packaged in an ear file named `myApp` it can be used as follows:

CODE EXAMPLE 15-2

```
@Resource(lookup="java:global/myApp/myWebApp!ROOT")
URL myWebApp;
```

15.3 Security

This section details the additional security requirements for web containers when included in a product that also contains EJB, JACC and or JASPIC. The following sections call out the requirements

15.3.1 Propagation of Security Identity in EJB™ Calls

A security identity, or principal, must always be provided for use in a call to an enterprise bean. The default mode in calls to enterprise beans from web applications is for the security identity of a web user to be propagated to the EJB container.

In other scenarios, web containers are required to allow web users that are not known to the web container or to the EJB container to make calls:

- Web containers are required to support access to web resources by clients that have not authenticated themselves to the container. This is the common mode of access to web resources on the Internet.
- Application code may be the sole processor of signon and customization of data based on caller identity.

In these scenarios, a web application deployment descriptor may specify a `run-as` element. When a `run-as` role is specified for a Servlet, the Servlet container must propagate a principal mapped to the role as the security identity in any call from the Servlet to an EJBs, including calls originating from the Servlet's `init` and `destroy` methods. The security role name must be one of the security role names defined for the web application.

For web containers running as part of a Java EE platform, the use of `run-as` elements must be supported both for calls to EJB components within the same Java EE application, and for calls to EJB components deployed in other Java EE applications.

15.3.2 Container Authorization Requirements

In a Java EE product or in a product that includes support for Java Authorization Contracts for Containers (JACC, i.e, JSR 115), all Servlet containers **MUST** implement support for JACC. The JACC Specification is available for download at <http://www.jcp.org/en/jsr/detail?id=115>

15.3.3 Container Authentication Requirements

In a Java EE product, or a product that includes support for The Java Authentication SPI for Containers (JASPIC, i.e, JSR 196), all Servlet containers **MUST** implement the Servlet Container Profile of the JASPIC specification. The JASPIC Specification is available for download at <http://www.jcp.org/en/jsr/detail?id=196>

15.4 Deployment

This section details the deployment descriptor, packaging and deployment descriptor processing requirements of a Java EE technology compliant container and products that include support for JSP and or Web Services.

15.4.1 Deployment Descriptor Elements

The following additional elements exist in the Web application deployment descriptor to meet the requirements of Web containers that are JSP pages enabled or part of a Java EE application server. They are not required to be supported by containers wishing to support only the servlet specification:

- `jsp-config`
- Syntax for declaring resource references (`env-entry`, `ejb-ref`, `ejb-local-ref`, `resource-ref`, `resource-env-ref`)
- Syntax for specifying the message destination (`message-destination`, `message-destination-ref`)
- Reference to a Web service (`service-ref`)
- Reference to a Persistence context (`persistence-context-ref`)
- Reference to a Persistence Unit (`persistence-unit-ref`)

The syntax for these elements is now held in the JavaServer Pages specification version 2.2, and the Java EE specification.

15.4.2 Packaging and Deployment of JAX-WS Components

Web containers may choose to support running components written to implement a Web service endpoint as defined by the JAX-RPC and/or JAX-WS specifications. Web containers embedded in a Java EE conformant implementation are required to support JAX-RPC and JAX-WS web service components. This section describes the packaging and deployment model for web containers when included in a product which also supports JAX-RPC and JAX-WS.

JSR-109 [<http://jcp.org/jsr/detail/109.jsp>] defines the model for packaging a Web service interface with its associated WSDL description and associated classes. It defines a mechanism for JAX-WS and JAX-RPC enabled Web containers to link to a component that implements this Web service. A JAX-WS or JAX-RPC Web service implementation component uses the APIs defined by the JAX-WS and/or JAX-RPC

specifications, which defines its contract with the JAX-WS and/or JAX-RPC enabled Web containers. It is packaged into the WAR file. The Web service developer makes a declaration of this component using the usual `<servlet>` declaration.

JAX-WS and JAX-RPC enabled Web containers must support the developer in using the Web deployment descriptor to define the following information for the endpoint implementation component, using the same syntax as for HTTP Servlet components using the `servlet` element. The child elements are used to specify endpoint information in the following way:

- the `servlet-name` element defines a logical name which may be used to locate this endpoint description among the other Web components in the WAR
- the `servlet-class` element provides the fully qualified Java class name of this endpoint implementation
- the `description` element(s) may be used to describe the component and may be displayed in a tool
- the `load-on-startup` element specifies the order in which the component is initialized relative to other Web components in the Web container
- the `security-role-ref` element may be used to test whether the authenticated user is in a logical security role
- the `run-as` element may be used to override the identity propagated to EJBs called by this component

Any servlet initialization parameters defined by the developer for this Web component may be ignored by the container. Additionally, the JAX-WS and JAX-RPC enabled Web component inherits the traditional Web component mechanisms for defining the following information:

- mapping of the component to the Web container's URL namespace using the servlet mapping technique
- authorization constraints on Web components using security constraints
- the ability to use servlet filters to provide low-level byte stream support for manipulating JAX-WS and/or JAX-RPC messages using the filter mapping technique
- the time out characteristics of any HTTP sessions that are associated with the component
- links to Java EE objects stored in the JNDI namespace

All of the above requirements can be met using the pluggability mechanism defined in Section 8.2, "Pluggability" on page 8-69.

15.4.3 Rules for Processing the Deployment Descriptor

The containers and tools that are part of Java EE technology-compliant implementation are required to validate the deployment descriptor against the XML schema for structural correctness. The validation is recommended, but not required for the web containers and tools that are not part of a Java EE technology compliant implementation.

15.5 Annotations and Resource Injection

The Java Metadata specification (JSR-175), which is part of J2SE 5.0 and greater, provides a means of specifying configuration data in Java code. Metadata in Java code is also referred to as annotations. In Java EE, annotations are used to declare dependencies on external resources and configuration data in Java code without the need to define that data in a configuration file.

This section describes the behavior of annotations and resource injection in Java EE technology compliant Servlet containers. This section expands on the Java EE specification section 5 titled “Resources, Naming, and Injection.”

Annotations must be supported on the following container managed classes that implement the following interfaces and are declared in the web application deployment descriptor or using the annotations defined in Section 8.1, “Annotations and pluggability” on page 8-65 or added programmatically.

TABLE 15-1 Components and Interfaces supporting Annotations and Dependency Injection

Component Type	Classes implementing the following interfaces
Servlets	<code>javax.servlet.Servlet</code>
Filters	<code>javax.servlet.Filter</code>
Listeners	<code>javax.servlet.ServletContextListener</code> <code>javax.servlet.ServletContextAttributeListener</code> <code>javax.servlet.ServletRequestListener</code> <code>javax.servlet.ServletRequestAttributeListener</code> <code>javax.servlet.http.HttpSessionListener</code> <code>javax.servlet.http.HttpSessionAttributeListener</code> <code>javax.servlet.AsyncListener</code>

Web containers are not required to perform resource injection for annotations occurring in classes other than those listed above in TABLE 15-1.

References must be injected prior to any lifecycle methods being called and the component instance being made available the application.

In a web application, classes using resource injection will have their annotations processed only if they are located in the `WEB-INF/classes` directory, or if they are packaged in a jar file located in `WEB-INF/lib`. Containers may optionally process resource injection annotations for classes found elsewhere in the application's classpath.

The web application deployment descriptor contains a `metadata-complete` attribute on the `web-app` element. The `metadata-complete` attribute defines whether the `web.xml` descriptor is complete, or whether other sources of metadata used by the deployment process should be considered. Metadata may come from the `web.xml` file, `web-fragment.xml` files, annotations on class files in `WEB-INF/classes`, and annotations on classes in jar files in the `WEB-INF/lib` directory. If `metadata-complete` is set to "true", the deployment tool only examines the `web.xml` file and must ignore annotations such as `@WebServlet`, `@WebFilter`, and `@WebListener` present in the class files of the application, and must also ignore any `web-fragment.xml` descriptor packaged in a jar file in `WEB-INF/lib`. If the `metadata-complete` attribute is not specified or is set to "false", the deployment tool must examine the class files and `web-fragment.xml` files for metadata, as previously specified.

The `web-fragment.xml` also contains the `metadata-complete` attribute on the `web-fragment` element. The attribute defines whether the `web-fragment.xml` descriptor is complete for the given fragment, or whether it should scan for annotations in the classes in the associated jar file. If `metadata-complete` is set to "true" the deployment tool only examines the `web-fragment.xml` and must ignore annotations such as `@WebServlet`, `@WebFilter` and `@WebListener` present in the class files of the fragment. If `metadata-complete` is not specified or is set to "false" the deployment tool must examine the class files for metadata.

Following are the annotations that are required by a Java EE technology compliant web container.

15.5.1 @DeclareRoles

This annotation is used to define the security roles that comprise the security model of the application. This annotation is specified on a class, and it is used to define roles that could be tested (i.e., by calling `isUserInRole`) from within the methods of the annotated class. Roles that are implicitly declared as a result of their use in a `@RolesAllowed` need not be explicitly declared using the `@DeclareRoles` annotation. The `@DeclareRoles` annotation may only be defined in classes implementing the `javax.servlet.Servlet` interface or a subclass thereof.

Following is an example of how this annotation would be used.

CODE EXAMPLE 15-3 @DeclareRoles Annotation Example

```
@DeclareRoles("BusinessAdmin")
public class CalculatorServlet {
    //...
}
```

Declaring @DeclareRoles("BusinessAdmin") is equivalent to defining the following in the web.xml.

CODE EXAMPLE 15-4 @DeclareRoles web.xml

```
<web-app>
  <security-role>
    <role-name>BusinessAdmin</role-name>
  </security-role>
</web-app>
```

This annotation is not used to relink application roles to other roles. When such linking is necessary, it is accomplished by defining an appropriate security-role-ref in the associated deployment descriptor.

When a call is made to `isUserInRole` from the annotated class, the caller identity associated with the invocation of the class is tested for membership in the role with the same name as the argument to `isCallerInRole`. If a `security-role-ref` has been defined for the argument `role-name` the caller is tested for membership in the role mapped to the `role-name`.

For further details on the @DeclareRoles annotation refer to the Common Annotations for the Java™ Platform™ specification (JSR 250) section 2.10.

15.5.2 @EJB Annotation

Enterprise JavaBeans™ 3.0 (EJB) components may be referenced from a web component using the @EJB annotation. The @EJB annotation provides the equivalent functionality of declaring the `ejb-ref` or `ejb-local-ref` elements in the deployment descriptor. Fields that have a corresponding @EJB annotation are injected with a reference to the corresponding EJB component.

An example:

```
@EJB private ShoppingCart myCart;
```

In the case above a reference to the EJB component “myCart” is injected as the value of the private field “myCart” prior to the class declaring the injection being made available.

The behavior the `@EJB` annotation is further detailed in section 15.5 of the EJB 3.0 specification (JSR220).

15.5.3 @EJBs Annotation

The `@EJBs` annotation allows more than one `@EJB` annotations to be declared on a single resource.

An example:

CODE EXAMPLE 15-5 @EJBs Annotation Example

```
@EJBs({@EJB( Calculator ), @EJB( ShoppingCart )})
public class ShoppingCartServlet {
    //...
}
```

The example above the EJB components `ShoppingCart` and `Calculator` are made available to `ShoppingCartServlet`. The `ShoppingCartServlet` must still look up the references using JNDI but the EJBs do not need to be declared in the `web.xml` file.

The `@EJBs` annotation is discussed in further detail in section 15.5 of the EJB 3.0 specification (JSR220).

15.5.4 @Resource Annotation

The `@Resource` annotation is used to declare a reference to a resource such as a data source, Java Messaging Service (JMS) destination, or environment entry. This annotation is equivalent to declaring a `resource-ref`, `message-destination-ref` or `env-ref`, or `resource-env-ref` element in the deployment descriptor.

The `@Resource` annotation is specified on a class, method or field. The container is responsible for injecting references to resources declared by the `@Resource` annotation and mapping it to the proper JNDI resources. See the Java EE Specification Chapter 5 for further details.

An example of a `@Resource` annotation follows:

CODE EXAMPLE 15-6 `@Resource` Example

```
@Resource private javax.sql.DataSource catalogDS;  
public getProductsByCategory() {  
    // get a connection and execute the query  
    Connection conn = catalogDS.getConnection();  
    ..  
}
```

In the example code above, a servlet, filter, or listener declares a field `catalogDS` of type `javax.sql.DataSource` for which the reference to the data source is injected by the container prior to the component being made available to the application. The data source JNDI mapping is inferred from the field name “`catalogDS`” and type (`javax.sql.DataSource`). Moreover, the `catalogDS` resource no longer needs to be defined in the deployment descriptor.

The semantics of the `@Resource` annotation are further detailed in the Common Annotations for the Java™ Platform™ specification (JSR 250) Section 2.3 and Java EE Specification specification 5.2.5.

15.5.5 `@PersistenceContext` Annotation

This annotation specifies the container managed entity manager for referenced persistence units.

An example:

CODE EXAMPLE 15-7 `@PersistenceContext` Example

```
@PersistenceContext (type=EXTENDED)  
EntityManager em;
```

The behavior the `@PersistenceContext` annotation is further detailed in section 10.4.1 of the Java Persistence API, Version 2.0 (JSR317).

15.5.6 `@PersistenceContexts` Annotation

The `PersistenceContexts` annotation allows more than one `@PersistenceContext` to be declared on a resource. The behavior the `@PersistenceContext` annotation is further detailed in section 10.4.1 of the Java Persistence API, version 2.0 (JSR 317).

15.5.7 @PersistenceUnit Annotation

The `@PersistenceUnit` annotation provides Enterprise Java Beans components declared in a servlet a reference to an entity manager factory. The entity manager factory is bound to a separate `persistence.xml` configuration file as described in section 5.10 of the EJB 3.0 specification (JSR220).

An example:

CODE EXAMPLE 15-8 @PersistenceUnit Example

```
@PersistenceUnit
EntityManagerFactory emf;
```

The behavior the `@PersistenceUnit` annotation is further detailed in section 10.4.2 of the Java Persistence API, version 2.0 (JSR317).

15.5.8 @PersistenceUnits Annotation

This annotation allows for more than one `@PersistenceUnit` annotations to be declared on a resource. The behavior the `@PersistenceUnits` annotation is further detailed in section 10.4.2 of the Java Persistence API, version 2.0 (JSR317).

15.5.9 @PostConstruct Annotation

The `@PostConstruct` annotation is declared on a method that does not take any arguments, and must not throw any checked exceptions. The return value must be void. The method **MUST** be called after the resources injections have been completed and before any lifecycle methods on the component are called.

An example:

CODE EXAMPLE 15-9 @PostConstruct Example

```
@PostConstruct
public void postConstruct() {
    ...
}
```

The example above shows a method using the `@PostConstruct` annotation.

The `@PostConstruct` annotation MUST be supported by all classes that support dependency injection and called even if the class does not request any resources to be injected. If the method throws an unchecked exception the class MUST not be put into service and no method on that instance can be called.

Refer to the Java EE specification section 2.5 and the Common Annotations for the Java™ Platform™ specification section 2.5 for more details.

15.5.10 `@PreDestroy` Annotation

The `@PreDestroy` annotation is declared on a method of a container managed component. The method is called prior to component being removed by the container.

An example:

CODE EXAMPLE 15-10 `@PreDestroy` Example

```
@PreDestroy
public void cleanup() {
    // clean up any open resources
    ...
}
```

The method annotated with `@PreDestroy` must return `void` and must not throw a checked exception. The method may be public, protected, package private or private. The method must not be static however it may be final.

Refer to the JSR 250 section 2.6 for more details.

15.5.11 `@Resources` Annotation

The `@Resources` annotation acts as a container for multiple `@Resource` annotations because the Java MetaData specification does not allow for multiple annotations with the same name on the same annotation target.

An example:

CODE EXAMPLE 15-11 `@Resources` Example

```
@Resources ({
    @Resource (name="myDB" type=javax.sql.DataSource) ,
    @Resource (name="myMQ" type=javax.jms.ConnectionFactory)
})
```

CODE EXAMPLE 15-11 @Resources Example

```
public class CalculatorServlet {  
    //...  
}
```

In the example above a JMS connection factory and a data source are made available to the `CalculatorServlet` by means of an `@Resources` annotation.

The semantics of the `@Resources` annotation are further detailed in the Common Annotations for the Java™ Platform™ specification (JSR 250) section 2.4.

15.5.12 @RunAs Annotation

The `@RunAs` annotation is equivalent to the `run-as` element in the deployment descriptor. The `@RunAs` annotation may only be defined in classes implementing the `javax.servlet.Servlet` interface or a subclass thereof.

An example:

CODE EXAMPLE 15-12 @RunAs Example

```
@RunAs("Admin")  
public class CalculatorServlet {  
  
    @EJB private ShoppingCart myCart;  
  
    public void doGet(HttpServletRequest req, HttpServletResponse  
res) {  
        //....  
        myCart.getTotal();  
        //....  
    }  
}  
  
    //....  
}
```

The `@RunAs("Admin")` statement would be equivalent to defining the following in the `web.xml`.

CODE EXAMPLE 15-13 @RunAs web.xml Example

```
<servlet>  
    <servlet-name>CalculatorServlet</servlet-name>  
    <run-as>Admin</run-as>  
</servlet>
```

The example above shows how a servlet uses the `@RunAs` annotation to propagate the security identity “Admin” to an EJB component when the `myCart.getTotal()` method is called. For further details on propagating identities see Section 15.3.1, “Propagation of Security Identity in EJB™ Calls” on page 15-180.

For further details on the `@RunAs` annotation refer to the Common Annotations for the Java™ Platform™ specification (JSR 250) section 2.6.

15.5.13 `@WebServiceRef` Annotation

The `@WebServiceRef` annotation provides a reference to a web service in a web component in same way as a `resource-ref` element would in the deployment descriptor.

An example:

```
@WebServiceRef private MyService service;
```

In this example a reference to the web service “MyService” will be injected to the class declaring the annotation.

This annotation and behavior are further detailed in the JAX-WS Specification (JSR 224) section 7.

15.5.14 `@WebServiceRefs` Annotation

This annotation allows for more than one `@WebServiceRef` annotations to be declared on a single resource. The behavior of this annotation is further detailed in the JAX-WS Specification (JSR 224) section 7.

15.5.15 Managed Beans and JSR 299 requirements

In a product that also supports Managed Beans, implementations **MUST** support use of Managed Beans as Servlets, Filters and Listeners. In a product that also supports JSR 299, implementations **MUST** similarly support use of JSR 299-style managed beans.

In a product that also supports JSR-299, an implementation **must** support use of 299-style managed beans as Servlet, Filter and Listener classes in an application. Servlet annotations may be directly applied to these beans. JSR-299 specifies the requirements for these container-managed bean instances with respect to instantiation, injection and other services. JSR-299 defines `@Dependent` pseudo-scope, Servlets, Filters and Listeners **MUST** be in that scope.

Change Log

This document is the final release of the Java Servlet 3.0 Servlet specification developed under the Java Community ProcessSM (JCP).

A.1 Changes since Servlet 3.0

1. Section 2.3.3.3, “Asynchronous processing”. And javadoc of `AsyncContext`.
 - a. Clarified the behavior of `AsyncListener.onStartAsync`.
 - b. Fixed errors and comments in Code Examples.
 - c. Clarified the behavior of `AsyncContext.getRequest` and `AsyncContext.getResponse` after the asynchronous request is completed or dispatched.
2. Added Section 2.3.3.5, “Upgrade Processing”, and new classes `ProtocolHandler` and `WebConnection`.
3. Section 3.2, “File upload”. Clarified when `multi-part/form-data` are processed.
4. Added Asynchronous IO in Section 3.7, “Non Blocking IO” and Section 5.7, “Lifetime of the Response Object”.
5. Section 5.1, “Buffering”. And javadoc of `ServletResponse`. Clarified the behavior of `ServletResponse.reset`.
6. Section 6.2.1, “Filter Lifecycle” (4). Required filters and servlet processing in the same thread.
7. Section 9.4, “The Forward Method”. Clarified the behavior of the response when the request is put in asynchronous mode.

8. Section 15.3.1, “Propagation of Security Identity in EJB™ Calls”. Explicitly mentioned the `Servlet.init` and `Servlet.destroy`.
9. Added generic in `ServletRequestWrapper`, `ServletResponseWrapper` and `HandlesTypes`.
10. Javadoc of `HttpServletResponse.sendRedirect`: Supported network-path reference.
11. Add new methods `ServletRequest.getContentLengthLong` and `ServletResponse.setContentLengthLong`.

A.2 Changes since Servlet 3.0 Proposed Final Draft

1. Re-factored some of the Async APIs - moved `addAsyncListener` to `AsyncContext` and renamed it to `addListener`. Moved `setAsyncTimeout` to `AsyncContext` and renamed it to `setTimeout`.
2. Clarified some of the semantics around concurrent access to the request and response in async processing.
3. Updated pluggability rules for resource reference elements.
4. Added a new annotation - `@ServletSecurity` (and associated annotation for the fields) for defining security as opposed to re-using the `@RolesAllowed`, `@PermitAll`, `@DenyAll`

A.3 Changes since Servlet 3.0 Public Review

1. Updated `isAsyncStarted` to return false once a dispatch to the container or a call to complete is done from the async handler
2. Added ordering support for fragments
3. Added support for file upload
4. Added support for loading static resources and JSPs from JAR files that are included in the `META-INF/resources` directory of the JAR file which is then bundled in the `WEB-INF/lib` directory

5. Changed annotation names based on feedback on Public Review of the specification
6. Added programmatic login / logout support
7. Added support for security related common annotations - @RolesAllowed, @PermitAll, @DenyAll
8. Clarified welcome files

A.4 Changes since Servlet 3.0 EDR

1. The suspend / resume APIs are no longer present in the specification. They have been replaced by startAsync and AsyncContext which now has forward and complete methods.
2. Annotation names have changed and there are only top level annotations. The method level annotations for declaring the servlet methods are no longer being used.
3. The rules for assembling web.xml from fragments and annotations is described.

A.5 Changes since Servlet 2.5 MR6

1. Added support for annotations and web fragments
2. Added support for suspend / resume to allow async support in servlets.
3. Added support for initializing servlets and filters from the ServletContext at initialization time.
4. Added support for HttpOnly cookies and allow configuring cookies.
5. Added convenience methods to ServletRequest to get Response and ServletContext

A.6 Changes since Servlet 2.5 MR 5

A.6.1 Clarify SRV 8.4 "The Forward Method"

Change the last sentence of the section which currently is:

"Before the forward method of the `RequestDispatcher` interface returns, the response content must be sent and committed, and closed by the servlet container."

to read:

"Before the forward method of the `RequestDispatcher` interface returns without exception, the response content must be sent and committed, and closed by the servlet container. If an error occurs in the target of the `RequestDispatcher.forward()` the exception may be propagated back through all the calling filters and servlets and eventually back to the container."

A.6.2 Update Deployment descriptor "http-method values allowed"

The facet for `http-method` element in the deployment descriptor is currently more restrictive than the `http` specification. The following change is being made to the descriptor to allow the set of method names as defined by the `http` specification. The pattern value of `http-methodType` is being changed from

```
<xsd:pattern value="[\p{L}-[\p{Cc}\p{Z}]]+"/>
```

to closely match what the HTTP specification lists as allowable HTTP methods names.

```
<xsd:pattern value="[#33;-&#126;-[\\(\)&#60;&#62;@,;:&#34;/\[\]?=\\{\}\p{Z}]]+"/>
```

A.6.3 Clarify SRV 7.7.1 "Threading Issues"

Change the paragraph which currently is:

"Multiple servlets executing request threads may have active access to a single session object at the same time. The Developer has the responsibility for synchronizing access to session resources as appropriate."

to read:

"Multiple servlets executing request threads may have active access to the same session object at the same time. The container must ensure that manipulation of internal data structures representing the session attributes is performed in a threadsafe manner. The Developer has the responsibility for threadsafe access to the attribute objects themselves. This will protect the attribute collection inside the HttpSession object from concurrent access, eliminating the opportunity for an application to cause that collection to become corrupted."

A.7 Changes Since Servlet 2.5 MR 2

A.7.1 Updated Annotation Requirements for Java EE containers

Added EJBs, PreDestroy, PersistenceContext, PersistenceContexts, PersistenceUnit, and PersistenceUnits with descriptions to the list of required Java EE container annotations in Section 15.5, "Annotations and Resource Injection".

A.7.2 Updated Java Enterprise Edition Requirements

Updated the Annotations to the final Java EE annotation names. Also updated the "full" attribute in the `web.xml` to be "metadata-complete".

A.7.3 Clarified `HttpServletRequest.getRequestURL()`

The API documentation for

`javax.servlet.http.HttpServletRequest.getRequestURL()` was clarified.

The text in italics was added:

If this request has been forwarded using `RequestDispatcher.forward(ServletRequest, ServletResponse)`, the server path in the reconstructed URL must reflect the path used to obtain the `RequestDispatcher`, and not the server path specified by the client. Because this method returns a `StringBuffer`, not a string, you can modify the URL easily, for example, to append query parameters.

A.7.4 Removal of `IllegalStateException` from `HttpSession.getId()`

The `HttpSessionBindingListener` calls the `valueUnbound` event after the session has been expired, unfortunately, the `HttpSession.getId()` method is often used in this scenario and is supposed to throw an `IllegalStateException`. The servlet EG agreed to remove the exception from the API to prevent these types of exceptions.

A.7.5 `ServletContext.getContextPath()`

The method `getContextPath()` was added to the `ServletContext` in the API. The description is as follows:

```
public java.lang.String getContextPath()
```

Returns the context path of the web application. The context path is the portion of the request URI that is used to select the context of the request. The context path always comes first in a request URI. The path starts with a "/" character but does not end with a "/" character. For servlets in the default (root) context, this method returns "".

It is possible that a servlet container may match a context by more than one context path. In such cases `getContextPath()` will return the actual context path used by the request and it may differ from the path returned by this method. The context path returned by this method should be considered as the prime or preferred context path of the application.

Returns: The context path of the web application.

`HttpServletRequest.getContextPath()` was updated to clarify its relationship with the `ServletContext.getContextPath()` method. The clarification is as follows.

It is possible that a servlet container may match a context by more than one context path. In such cases this method will return the actual context path used by the request and it may differ from the path returned by the `ServletContext.getContextPath()` method. The context path returned by `ServletContext.getContextPath()` should be considered as the prime or preferred context path of the application.

A.7.6 Requirement for `web.xml` in web applications

Section 10.13, "Inclusion of a `web.xml` Deployment Descriptor" was added which removes requirement for Java EE compliant web applications. The section is as follows:

A web application is NOT required to contain a web.xml if it does NOT contain any Servlet, Filter, or Listener components. In other words an application containing only static files or JSP pages does not require a web.xml to be present.

A.8 Changes Since Servlet 2.4

A.8.1 Session Clarification

Clarified Section 7.3, "Session Scope" to allow for better support of session ids being used in more than one context. This was done to support the Portlet specification (JSR 168). Added the following paragraph at the end of Section 7.3:

"Additionally, sessions of a context must be resumable by requests into that context regardless of whether their associated context was being accessed directly or as the target of a request dispatch at the time the sessions were created."

Made the changes in Section 9.3, "The Include Method" by replacing the following text:

"It cannot set headers or call any method that affects the headers of the response. Any attempt to do so must be ignored."

with the following:

"It cannot set headers or call any method that affects the headers of the response, with the exception of the `HttpServletRequest.getSession()` and `HttpServletRequest.getSession(boolean)` methods. Any attempt to set the headers must be ignored, and any call to `HttpServletRequest.getSession()` or `HttpServletRequest.getSession(boolean)` that would require adding a Cookie response header must throw an `IllegalStateException` if the response has been committed."

A.8.2 Filter All Dispatches

Modified Section 6.2.5, "Filters and the RequestDispatcher" to clarify a way to map a filter to all servlet dispatches by appending the following text to the end of the section:

Finally, the following code uses the special servlet name '*':

CODE EXAMPLE A-1 Example of special servlet name '*'

```
<filter-mapping>
  <filter-name>All Dispatch Filter</filter-name>
  <servlet-name>*</servlet-name>
  <dispatcher>FORWARD</dispatcher>
</filter-mapping>
```

This code would result in the All Dispatch Filter being invoked on request dispatcher forward() calls for all request dispatchers obtained by name or by path.

A.8.3 Multiple Occurrences of Servlet Mappings

Previous versions of the servlet schema allows only a single url-pattern or servlet name per servlet mapping. For servlets mapped to multiple URLs this results in needless repetition of whole mapping clauses.

The deployment descriptor `servlet-mappingType` was updated to:

CODE EXAMPLE A-2 `servlet-mappingType` descriptor

```
<xsd:complexType name="servlet-mappingType">
  <xsd:sequence>
    <xsd:element name="servlet-name" type="j2ee:servlet-
nameType" />
    <xsd:element name="url-pattern" type="j2ee:url-patternType"
minOccurs="1"
maxOccurs="unbounded" />
  </xsd:sequence>
  <xsd:attribute name="id" type="xsd:ID" />
</xsd:complexType>
```

A.8.4 Multiple Occurrences Filter Mappings

Previous versions of the servlet schema allows only a single url-pattern in a filter mapping. For filters mapped to multiple URLs this results in needless repetition of whole mapping clauses.

The deployment descriptor schema the `filter-mappingType` was updated to:

CODE EXAMPLE A-3 Updated `filter-mappingType` schema

```
<xsd:complexType name="filter-mappingType">
  <xsd:sequence>
    <xsd:element name="filter-name" type="j2ee:filter-nameType"/>
    <xsd:choice minOccurs="1" maxOccurs="unbounded">
      <xsd:element name="url-pattern" type="j2ee:url-
patternType"/>
      <xsd:element name="servlet-name" type="j2ee:servlet-
nameType"/>
    </xsd:choice>
    <xsd:element name="dispatcher" type="j2ee:dispatcherType"
minOccurs="0"
maxOccurs="4"/>
  </xsd:sequence>
  <xsd:attribute name="id" type="xsd:ID"/>
</xsd:complexType>
```

This change allows multiple patterns and servlet names to be defined in a single mapping as can be seen in the following example:

CODE EXAMPLE A-4 Filter mapping example

```
<filter-mapping>
  <filter-name>Demo Filter</filter-name>
  <url-pattern>/foo/*</url-pattern>
  <url-pattern>/bar/*</url-pattern>
  <servlet-name>Logger</servlet-name>
  <dispatcher>REQUEST</dispatcher>
  <dispatcher>ERROR</dispatcher>
</filter-mapping>
```

Section 6.2.4, "Configuration of Filters in a Web Application" was updated to clarify the cases where there are multiple mappings with the following text:

"If a filter mapping contains both `<servlet-name>` and `<url-pattern>`, the container must expand the filter mapping into multiple filter mappings (one for each `<servlet-name>` and `<url-pattern>`), preserving the order of the `<servlet-name>` and `<url-pattern>` elements."

An examples was also provided to clarify cases when there are multiple mappings.

A.8.5 Support Alternative HTTP Methods with Authorization Constraints

The previous Servlet 2.4 schema restricted HTTP methods to GET, POST, PUT, DELETE, HEAD, OPTIONS, and TRACE. The schema `http-methodType` was changed from:

CODE EXAMPLE A-5 Servlet 2.4 `http-methodType` schema

```
<xsd:complexType name="http-methodType">
  ...
  <xsd:simpleContent>
    <xsd:restriction base="j2ee:string">
      <xsd:enumeration value="GET" />
      <xsd:enumeration value="POST" />
      <xsd:enumeration value="PUT" />
      <xsd:enumeration value="DELETE" />
      <xsd:enumeration value="HEAD" />
      <xsd:enumeration value="OPTIONS" />
      <xsd:enumeration value="TRACE" />
    </xsd:restriction>
  </xsd:simpleContent>
</xsd:complexType>
```

To the following:

CODE EXAMPLE A-6 Servlet 2.5 `http-methodType` schema

```
<xsd:simpleType name="http-methodType">
  <xsd:annotation>
    <xsd:documentation>
      A HTTP method type as defined in HTTP 1.1 section 2.2.
    </xsd:documentation>
  </xsd:annotation>

  <xsd:restriction base="xsd:token">
    <xsd:pattern value="[\p{L}-[\p{Cc}\p{Z}]]+"/>
  </xsd:restriction>
</xsd:simpleType>
```

The `http-method` elements now need to be a token as described in HTTP 1.1 specification section 2.2.

A.8.6 Minimum J2SE Requirement

Servlet 2.5 Containers now require J2SE 5.0 as the minimum Java version. Section 1.2, "What is a Servlet Container?" was updated to reflect this requirement.

A.8.7 Annotations and Resource Injection

Java EE technology compliant containers require annotations and resource injection on servlets, filters, and listeners. Section 15.5, "Annotations and Resource Injection" describes the annotations and resource injection in further detail.

A.8.8 SRV.9.9 ("Error Handling") Requirement Removed

Section 10.9.1, "Request Attributes" defines the following requirement:

If the location of the error handler is a servlet or a JSP page:

[...]

The response setStatus method is disabled and ignored if called.

[...]

The JSP 2.1 EG has asked that this requirement above be removed to allow JSP error pages to update the response status.

A.8.9 HttpServletRequest.isRequestedSessionIdValid() Clarification

The API clarification better describes what happens when a client did not specify a session id. The API documentation was updated to specify when false is returned. The API documentation now states:

Returns **false** if the client did not specify any session ID.

A.8.10 SRV.5.5 ("Closure of Response Object") Clarification

The behavior in Section 5.6, "Closure of Response Object" the response's content length is set to 0 via response.setHeader("Content-Length", "0") and any subsequently setHeader() calls are ignored.

Section 5.6, “Closure of Response Object” was updated to allow all headers to be set by changing:

“The amount of content specified in the `setContentLength` method of the response and has been written to the response”

To the following:

“The amount of content specified in the `setContentLength` method of the response has been greater than zero and has been written to the response”

A.8.11 `ServletRequest.setCharacterEncoding()` Clarified

The API was updated to describe the behavior if the method is called after the `getReader()` was called. If the `getReader()` is called there will be no effect.

A.8.12 Java Enterprise Edition Requirements

Chapter 15, “Requirements related to other Specifications” details all requirements of a Java EE container. Previously the requirements were mixed into each chapter.

A.8.13 Servlet 2.4 MR Change Log Updates Added

Added the changes from the Servlet 2.4 Maintenance Review. These changes include grammar and typographical fixes.

A.8.14 Synchronized Access Session Object Clarified

Section 7.7.1, “Threading Issues” was updated to clarify that access to the session object should be synchronized.

A.9 Changes Since Servlet 2.3

- Optional “X-Powered-By” header is added in the response (5.2)
- Clarification of “overlapping constraint” (12.8.1, 12.8.2)
- Add the section to clarify the process order at the time of web application deployment (9.12)

- Clarification that the security model is also applied to filter (12.2)
- Change the status code from 401 to 200 when FORM authentication is failed as there is no appropriate error status code in HTTP/1.1 (12.5.3)
- Clarification of the wrapper objects (6.2.2)
- Clarification of overriding the platform classes (9.7.2)
- Clarification of welcome file (9.10)
- Clarification of internationalization - the relationship among `setLocale`, `setContentType`, and `setCharacterEncoding` (5.4, 14.2.22)
- Clarification of `ServletRequestListener` and `ServletRequestAttributeListener` description (14.2.18, 14.2.20)
- Add `HttpSessionActivationListener` and `HttpSessionBindingListener` into the Table 10-1.
- Change the word "auth constraint" to "authorization constraint" (12.8)
- Add "Since" tag in the newly added methods in javadoc(14.2.16, 14.2.22)
- Fix the data type of `<session-timeout>` to `xsdIntegerType` in schema(13.3)
- Clarification when the listener throws the unhandled exception(10.6)
- Clarification of the "shared library"(9.7.1)
- Clarification of the container's mechanism for the extension(9.7.1, third paragraph)
- `HttpSession.logout` method was removed. The portable authentication mechanism will be addressed in the next version of this specification and logout will also be discussed in that scope.(12.10)
- It is now a recommendation, instead of a requirement, that the reference to the request and response object should not be given to the object in other threads - based on the requirement from JSR-168. Warnings are added when the thread created by the application uses the objects managed by the container.(2.3.3.3)
- It is now a recommendation, that the dispatch should occur in the same thread of the same JVM as the original request - based on the requirement from JSR-168(8.2)
- Clarification of "wrap" (6.2.2)
- Clarification of handling the path parameter for the mapping(11.1)
- Add the description about the "HTTP chunk" in `HttpServlet.doGet` method(15.1.2)
- J2SE 1.3 is the minimum version of the underlying Java platform with which servlet containers must be built (1.2)
- Clarification of `ServletResponse.setBufferSize` method (5.1)
- Clarification of `ServletRequest.getServerName` and `getServerPort` (14.2.16.1)
- Clarification of Internationalization (5.4, 14.2.22)
- Clarification of the redirection of the welcome file (9.10)
- Clarification of `ServletContextListener.contextInitialized` (14.2.12.1)
- Clarification of `HttpServletRequest.getRequestId` - making it clear that it returns the session ID specified by the client (15.1.3.2)
- Clarification of the class loader for the extensions - the class loader must be the same for all web applications within the same JVM (9.7.1)
- Clarification of the case when `ServletRequestListener` throws an unhandled exception (10.6, 14.2.20)
- Clarification of the scope of `ServletRequestListener` (14.2.20)

- Add the description about the case when the container has a caching mechanism (1.2)
- Validating deployment descriptor against the schema is required for Java EE containers (13.2)
- Sub elements under `<web-app>` can be in an arbitrary order (13.2)
- One example of the container's rejecting the web application was removed due to the contradiction with SRV.11.1 (9.5)
- `url-patternType` is changed from `j2ee:string` to `xsd:string` (13)
- The sub-elements under `<web-app>` in deployment descriptor can be in the arbitrary order (13)
- The container must inform a developer with a descriptive error message when deployment descriptor file contains an illegal character or multiple elements of `<session-config>`, `<jsp-config>`, or `<login-config>` (13)
- Extensibility of deployment descriptor was removed (13)
- Section SRV.1.6 added - describing the compatibility issue with the previous version of this specification (1.6)
- New attributes are added in `RequestDispatcher.forward` method (8.4.2)
- New methods in `ServletRequest` interface and `ServletRequestWrapper` (14.2.16.1)
- The interface `SingleThreadModel` was deprecated ((2.2.1, 2.3.3.1, 14.2.24)
- Change the name of the method `ServletRequestEvent.getRequest` to `ServletRequestEvent.getServletRequest` (14.2.19.2)
- Clarification of the "request" to access to WEB-INF directory (9.5)
- Clarification of the behavior of `ServletRequest.setAttribute` - change "value" to "object" in "If the value passed in is null," (14.2.16.1)
- Fix the inconsistency between this specification and `HttpServletRequest.getServletPath` - the return value starts with "/" (15.1.3.2)
- Fix the inconsistency between this specification and `HttpServletRequest.getPathInfo` - the return value starts with "/" (15.1.3.2)
- Fix the inconsistency between this specification and `HttpServletRequest.getPathTranslated` - add the case when the container cannot translate the path (15.1.3.2)
- Allow `HttpServletRequest.getAuthType` to return not only pre-defined four authentication scheme but also the container-specific scheme (15.1.3.2)
- Change the behavior of `HttpSessionListener.sessionDestroyed` to notify before the session is invalidated (15.1.14.1)
- Fix the wrong status code of 403 to 404 (9.5, 9.6)
- Element "taglib" should be "jsp-config" (13.2)
- Fix the version number of JSP specification to 2.0
- Fix the wrong formats (5.5, 6.2.5, 12.8.3, 12.9)
- HTTP/1.1 is now required (1.2)
- `<url-pattern>` in `<web-resource-collection>` is mandatory (13.4)
- Clarification of `IllegalArgumentException` in the distributed environments (7.7.2)
- Clarification of error page handling (9.9.1, 9.9.2, 9.9.3, 6.2.5)
- Clarification of Security Constraints, especially in the case of overlapping constraints (12.8)
- Clarification of the case when `<session-timeout>` element is not specified (13.4)
- Clarification of the case when the resource is permanently unavailable (2.3.3.2)

- Add missing `getParameterMap()` in the enumerated list (4.1)
- Clarification of the status code when `/WEB-INF/` resource is accessed (9.5)
- Clarification of the status code when `/META-INF/` resource is accessed (9.6)
- Change `xsd:string` to `j2ee:string` in deployment descriptor (13.4)
- Extensibility of deployment descriptors (SRV.13)
- XML Schema definition of deployment descriptor (SRV.13)
- Request listeners (SRV.10 and API change)
New API: `ServletRequestListener`, `ServletRequestAttributeListener` and associated event classes
- Ability to use Filters under the Request Dispatcher (6.2.5)
- Required class loader extension mechanism (9.7.1)
- Listener exception handling (10.6)
- Listener order vs. `servlet init()/destroy()` clarification (`ServletContextListener` javadoc change)
- Servlets mapped to `WEB-INF /` response handling (9.5)
- Request dispatcher / path matching rules (8.1)
- Welcome files can be servlets (9.10)
- Internationalization enhancements (5.4, 14.2.22, 15.1.5)
- `SC_FOUND(302)` addition (15.1.5)
- “Relative path” in `getRequestDispatcher()` must be relative against the current servlet (8.1)
- Bug fix in the example of XML (13.7.2)
- Clarification of access by `getResource` “only to the resource” (3.5)
- Clarification of `SERVER_NAME` and `SERVER_PORT` in `getServerName()` and `getServerPort()` (14.2.16)
- Clarification: “run-as” identity must apply to all calls from a servlet including `init()` and `destroy()` (12.7)
- Login/logout description and methods added (12.10, 15.1.7)

Glossary

A

Application Developer

The producer of a web application. The output of an Application Developer is a set of servlet classes, JSP pages, HTML pages, and supporting libraries and files (such as images, compressed archive files, etc.) for the web application. The Application Developer is typically an application domain expert. The developer is required to be aware of the servlet environment and its consequences when programming, including concurrency considerations, and create the web application accordingly.

Application Assembler

Takes the output of the Application Developer and ensures that it is a deployable unit. Thus, the input of the Application Assembler is the servlet classes, JSP pages, HTML pages, and other supporting libraries and files for the web application. The output of the Application Assembler is a web application archive or a web application in an open directory structure.

D

Deployer

The Deployer takes one or more web application archive files or other directory structures provided by an Application Developer and deploys the application into a specific operational environment. The operational environment includes

a specific servlet container and web server. The Deployer must resolve all the external dependencies declared by the developer. To perform his role, the deployer uses tools provided by the Servlet Container Provider.

The Deployer is an expert in a specific operational environment. For example, the Deployer is responsible for mapping the security roles defined by the Application Developer to the user groups and accounts that exist in the operational environment where the web application is deployed.

P

principal A principal is an entity that can be authenticated by an authentication protocol. A principal is identified by a *principal name* and authenticated by using *authentication data*. The content and format of the principal name and the authentication data depend on the authentication protocol.

R

role (development) The actions and responsibilities taken by various parties during the development, deployment, and running of a web application. In some scenarios, a single party may perform several roles; in others, each role may be performed by a different party.

role (security) An abstract notion used by an Application Developer in an application that can be mapped by the Deployer to a user, or group of users, in a security policy domain.

S

security policy domain The scope over which security policies are defined and enforced by a security administrator of the security service. A security policy domain is also sometimes referred to as a *realm*.

security technology domain The scope over which the same security mechanism, such as Kerberos, is used to enforce a security policy. Multiple security policy domains can exist within a single technology domain.

Servlet Container Provider	<p>A vendor that provides the runtime environment, namely the servlet container and possibly the web server, in which a web application runs as well as the tools necessary to deploy web applications.</p> <p>The expertise of the Container Provider is in HTTP-level programming. Since this specification does not specify the interface between the web server and the servlet container, it is left to the Container Provider to split the implementation of the required functionality between the container and the server.</p>
servlet definition	<p>A unique name associated with a fully qualified class name of a class implementing the Servlet interface. A set of initialization parameters can be associated with a servlet definition.</p>
servlet mapping	<p>A servlet definition that is associated by a servlet container with a URL path pattern. All requests to that path pattern are handled by the servlet associated with the servlet definition.</p>
System Administrator	<p>The person responsible for the configuration and administration of the servlet container and web server. The administrator is also responsible for overseeing the well-being of the deployed web applications at run time.</p> <p>This specification does not define the contracts for system management and administration. The administrator typically uses runtime monitoring and management tools provided by the Container Provider and server vendors to accomplish these tasks.</p>

U

uniform resource locator (URL)

A compact string representation of resources available via the network. Once the resource represented by a URL has been accessed, various operations may be performed on that resource.¹ A URL is a type of uniform resource identifier (URI). URLs are typically of the form:

```
<protocol>://<servername>/<resource>
```

For the purposes of this specification, we are primarily interested in HTTP-based URLs which are of the form:

```
http[s]://<servername>[:port]/<url-path>[?<query-string>]
```

For example:

```
http://java.sun.com/products/servlet/index.html
```

```
https://javashop.sun.com/purchase
```

In HTTP-based URLs, the ‘/’ character is reserved to separate a hierarchical path structure in the URL-path portion of the URL. The server is responsible for determining the meaning of the hierarchical structure. There is no correspondence between a URL-path and a given file system path.

W

web application

A collection of servlets, JSP pages, HTML documents, and other web resources which might include image files, compressed archives, and other data. A web application may be packaged into an archive or exist in an open directory structure.

All compatible servlet containers must accept a web application and perform a deployment of its contents into their runtime. This may mean that a container can run the application directly from a web application archive file or it may mean that it will move the contents of a web application into the appropriate locations for that particular container.

1. See RFC 1738

**web application
archive**

A single file that contains all of the components of a web application. This archive file is created by using standard JAR tools which allow any or all of the web components to be signed.

Web application archive files are identified by the `.war` extension. A new extension is used instead of `.jar` because that extension is reserved for files which contain a set of class files and that can be placed in the classpath or double clicked using a GUI to launch an application. As the contents of a web application archive are not suitable for such use, a new extension was in order.

**web application,
distributable**

A web application that is written so that it can be deployed in a web container distributed across multiple Java virtual machines running on the same host or different hosts. The deployment descriptor for such an application uses the `distributable` element.

